

## SAFETY DATA SHEET

### Section 1. Identification

**Product identifier** : U3080S FC1  
**Product name** : AEROSOL 1K UNIVERSALPRIMER WEISS  
**Other means of identification** : 4024669634280  
**Date of issue** : 18 June 2025  
**Version** : 2

#### Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** : Coating component.  
**Uses advised against** : Not for sale to or use by consumers.

**Supplier's details** : Axalta Coating Systems Australia Pty Limited  
 16 Darling Street, Marsden Park NSW 2765, Australia  
 Importer: Resene Automotive & Light Industrial  
 4 Te Apunga Place, Mt Wellington, Auckland, New Zealand  
 Telephone: +64 (09) 259 2738  
**Product information** : +61 (0)2 8818 4300

**Emergency telephone number** : +(64) 9801 0034 NZ Poisons Information Center: 0800 764 766 or +(64) 3 479 7248

### Section 2. Hazards identification

This material is classified as hazardous according to criteria in the Hazardous Substances (Hazard Classification) Notice 2020.

This material is classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

**HSNO Classification** : AEROSOLS - Category 1  
 EYE IRRITATION - Category 2  
 SKIN SENSITISATION - Category 1  
 CARCINOGENICITY - Category 2  
 REPRODUCTIVE TOXICITY - Category 2  
 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2

#### GHS label elements

**Symbol**



**Signal word**

: Danger

## Section 2. Hazards identification

**Hazard statements** : Extremely flammable aerosol. Pressurised container: may burst if heated.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
Suspected of causing cancer.  
Suspected of damaging fertility or the unborn child.  
May cause damage to organs through prolonged or repeated exposure.

### Precautionary statements

**Prevention** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not breathe dust or mist. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Do not pierce or burn, even after use. Wear protective gloves, protective clothing and eye or face protection.

**Response** : IF exposed or concerned: Get medical advice or attention. Take off contaminated clothing and wash it before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

**Storage** : Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

**Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.

**Other hazards which do not result in classification** : None known.

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture

| Ingredient name                                             | % (w/w)  | CAS number |
|-------------------------------------------------------------|----------|------------|
| dimethyl ether                                              | 10 - <30 | 115-10-6   |
| acetone                                                     | 10 - <30 | 67-64-1    |
| butanone                                                    | 10 - <30 | 78-93-3    |
| n-butyl acetate                                             | 3 - <5   | 123-86-4   |
| 2-methoxy-1-methylethyl acetate                             | 3 - <5   | 108-65-6   |
| xylene                                                      | 1 - <3   | 1330-20-7  |
| reaction product: bisphenol-A-(epichlorhydrin); epoxy resin | 0.3 - <1 | 25068-38-6 |
| ethylbenzene                                                | 0.3 - <1 | 100-41-4   |

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

**Occupational exposure limits, if available, are listed in Section 8.**

## Section 4. First aid measures

### Description of necessary first aid measures

- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Ingestion** : Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Inhalation** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.
- Skin contact** : May cause an allergic skin reaction.
- Eye contact** : Causes serious eye irritation.

#### Over-exposure signs/symptoms

- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Skin** : Adverse symptoms may include the following:  
irritation  
redness  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations

## Section 4. First aid measures

**Eyes** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

### **Indication of immediate medical attention and special treatment needed, if necessary**

**Specific treatments** : Not available.

**Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Firefighting measures

### **Extinguishing media**

**Suitable** : Use an extinguishing agent suitable for the surrounding fire.

**Not suitable** : None known.

**Specific hazards arising from the chemical** : Extremely flammable aerosol. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
halogenated compounds  
metal oxide/oxides

**Hazchem code** : Not available.

**Special precautions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

**Personal precautions, protective equipment and emergency procedures** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### **Methods and material for containment and cleaning up**

## Section 6. Accidental release measures

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

## Section 7. Handling and storage

- Precautions for safe handling** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Pressurised container: protect from sunlight and do not expose to temperature exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid breathing gas. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
- Conditions for safe storage, including any incompatibilities** : Store between the following temperatures: -15 to 30°C (5 to 86°F). Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

| Ingredient name | Exposure limits                                                                                                                                                                                                                  |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| dimethyl ether  | <b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 11/2023)</b><br>WES-TWA 8 hours: 400 ppm.<br>WES-TWA 8 hours: 766 mg/m³.<br>WES-STEL 15 minutes: 500 ppm.<br>WES-STEL 15 minutes: 958 mg/m³.    |
| acetone         | <b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 11/2023)</b><br>WES-TWA 8 hours: 500 ppm.<br>WES-TWA 8 hours: 1185 mg/m³.<br>WES-STEL 15 minutes: 2375 mg/m³.<br>WES-STEL 15 minutes: 1000 ppm. |

## Section 8. Exposure controls/personal protection

|                                 |                                                                                                                                                                                                                                                                                                           |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| butanone                        | <p><b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 11/2023)</b><br/> WES-TWA 8 hours: 150 ppm.<br/> WES-TWA 8 hours: 445 mg/m<sup>3</sup>.<br/> WES-STEL 15 minutes: 890 mg/m<sup>3</sup>.<br/> WES-STEL 15 minutes: 300 ppm.</p>                                        |
| Kaolin                          | <p><b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 11/2023)</b><br/> WES-TWA 8 hours: 10 mg/m<sup>3</sup>.<br/> WES-TWA 8 hours: 2 mg/m<sup>3</sup>. Form: The value for respirable dust..</p>                                                                           |
| propane                         | <p><b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 11/2023)</b><br/> Oxygen depletion [asphyxiant] , Explosive potential.</p>                                                                                                                                            |
| n-butyl acetate                 | <p><b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 11/2023)</b><br/> WES-TWA 8 hours: 150 ppm.<br/> WES-TWA 8 hours: 713 mg/m<sup>3</sup>.<br/> WES-STEL 15 minutes: 950 mg/m<sup>3</sup>.<br/> WES-STEL 15 minutes: 200 ppm.</p>                                        |
| titanium dioxide                | <p><b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 11/2023)</b><br/> WES-TWA 8 hours: 10 mg/m<sup>3</sup>.</p>                                                                                                                                                           |
| 2-methoxy-1-methylethyl acetate | <p><b>EH40/2005 WELs (United Kingdom (UK), 1/2020)</b><br/> Absorbed through skin.<br/> STEL 15 minutes: 548 mg/m<sup>3</sup>.<br/> TWA 8 hours: 50 ppm.<br/> TWA 8 hours: 274 mg/m<sup>3</sup>.<br/> STEL 15 minutes: 100 ppm.</p>                                                                       |
| butane                          | <p><b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 11/2023)</b><br/> WES-TWA 8 hours: 800 ppm.<br/> WES-TWA 8 hours: 1900 mg/m<sup>3</sup>.</p>                                                                                                                          |
| xylene                          | <p><b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 11/2023)</b><br/> <b>[xylene (o-, m-, p-isomers)]</b> Ototoxicant.<br/> WES-TWA 8 hours: 50 ppm.<br/> WES-TWA 8 hours: 217 mg/m<sup>3</sup>.</p>                                                                      |
| Isobutane                       | <p><b>ACGIH TLV (United States, 1/2024) [Butane]</b><br/> Explosive potential.<br/> STEL 15 minutes: 1000 ppm.</p>                                                                                                                                                                                        |
| ethylbenzene                    | <p><b>HSWA 2015 - HSW (GRWM) 2016. Workplace exposure standards (WES) (New Zealand, 11/2023)</b><br/> Absorbed through skin , Ototoxicant.<br/> WES-TWA 8 hours: 20 ppm.<br/> WES-TWA 8 hours: 88 mg/m<sup>3</sup>.<br/> WES-STEL 15 minutes: 176 mg/m<sup>3</sup>.<br/> WES-STEL 15 minutes: 40 ppm.</p> |

## Section 8. Exposure controls/personal protection

- Appropriate engineering controls** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
- Skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## Section 9. Physical and chemical properties

### Appearance

- Physical state** : Liquid.
- Colour** : White.
- Odour** : Not available.
- Odour threshold** : Not available.
- pH** : Not applicable.
- Melting point** : Technically not possible to measure
- Boiling point** : Not applicable.

## Section 9. Physical and chemical properties

|                                                       |                                                                                                                                          |
|-------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Flash point</b>                                    | : Closed cup: -1°C (30.2°F)                                                                                                              |
| <b>Evaporation rate</b>                               | : Not available.                                                                                                                         |
| <b>Flammability (solid, gas)</b>                      | : Not available.                                                                                                                         |
| <b>Lower and upper explosive (flammable) limits</b>   | : Lower: 1%<br>Upper: 11.5%                                                                                                              |
| <b>Vapour pressure</b>                                | : 185.6 kPa (1392.23 mm Hg)                                                                                                              |
| <b>Vapour density</b>                                 | : Not available.                                                                                                                         |
| <b>Density</b>                                        | : 0.85 g/cm <sup>3</sup>                                                                                                                 |
| <b>Solubility(ies)</b>                                | :<br>Not available.                                                                                                                      |
| <b>Partition coefficient: n-octanol/water</b>         | : Not applicable.                                                                                                                        |
| <b>Auto-ignition temperature</b>                      | : 287°C (548.6°F)                                                                                                                        |
| <b>Decomposition temperature</b>                      | : Not applicable.                                                                                                                        |
| <b>Viscosity</b>                                      | : Dynamic (room temperature): Not available.<br>Kinematic (room temperature): Not available.<br>Kinematic (40°C (104°F)): Not available. |
| <b>Flow time (ISO 2431)</b>                           | : Not available.                                                                                                                         |
| <b><u>Aerosol product</u></b>                         |                                                                                                                                          |
| <b>Type of aerosol</b>                                | : Spray                                                                                                                                  |
| <b>Heat of combustion</b>                             | : 25.83 kJ/g                                                                                                                             |
| <b>Ignition distance</b>                              | : Not available.                                                                                                                         |
| <b>Enclosed space ignition - Time equivalent</b>      | : Not available.                                                                                                                         |
| <b>Enclosed space ignition - Deflagration density</b> | : Not available.                                                                                                                         |
| <b>Flame projection</b>                               | : Not available.                                                                                                                         |
| <b>Flame height</b>                                   | : Not applicable.                                                                                                                        |
| <b>Flame duration</b>                                 | : Not applicable.                                                                                                                        |

## Section 10. Stability and reactivity

|                                           |                                                                                                        |
|-------------------------------------------|--------------------------------------------------------------------------------------------------------|
| <b>Chemical stability</b>                 | : The product is stable.                                                                               |
| <b>Possibility of hazardous reactions</b> | : Under normal conditions of storage and use, hazardous reactions will not occur.                      |
| <b>Conditions to avoid</b>                | : Avoid all possible sources of ignition (spark or flame).                                             |
| <b>Incompatible materials</b>             | : No specific data.                                                                                    |
| <b>Hazardous decomposition products</b>   | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |



## Section 11. Toxicological information

### Information on likely routes of exposure

- Inhalation** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.
- Skin contact** : May cause an allergic skin reaction.
- Eye contact** : Causes serious eye irritation.

### Symptoms related to the physical, chemical and toxicological characteristics

- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
reduced foetal weight  
increase in foetal deaths  
skeletal malformations
- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Acute toxicity

| Product/ingredient name         | Result                 | Species | Dose                 | Exposure |
|---------------------------------|------------------------|---------|----------------------|----------|
| dimethyl ether                  | LC50 Inhalation Gas.   | Rat     | 164000 ppm           | 4 hours  |
|                                 | LC50 Inhalation Vapour | Rat     | 309 g/m <sup>3</sup> | 4 hours  |
|                                 | LD50 Dermal            | Rat     | >99999 mg/kg         | -        |
|                                 | LD50 Oral              | Rat     | >99999 mg/kg         | -        |
| acetone                         | LC50 Inhalation Vapour | Rat     | 21 mg/l              | 4 hours  |
|                                 | LD50 Dermal            | Rabbit  | 2001 mg/kg           | -        |
|                                 | LD50 Oral              | Rat     | 5800 mg/kg           | -        |
| butanone                        | LD50 Dermal            | Rabbit  | 6480 mg/kg           | -        |
|                                 | LD50 Oral              | Rat     | 2737 mg/kg           | -        |
| n-butyl acetate                 | LC50 Inhalation Vapour | Rat     | 21.1 mg/l            | 4 hours  |
|                                 | LD50 Dermal            | Rabbit  | >17600 mg/kg         | -        |
|                                 | LD50 Oral              | Rat     | 10768 mg/kg          | -        |
| 2-methoxy-1-methylethyl acetate | LD50 Dermal            | Rabbit  | >5 g/kg              | -        |
|                                 | LD50 Oral              | Rat     | 8532 mg/kg           | -        |
| xylene                          | LC50 Inhalation Gas.   | Rat     | 5000 ppm             | 4 hours  |
|                                 | LD50 Oral              | Rat     | 4300 mg/kg           | -        |
| ethylbenzene                    | LD50 Dermal            | Rabbit  | >5000 mg/kg          | -        |

## Section 11. Toxicological information

|  |           |     |            |   |
|--|-----------|-----|------------|---|
|  | LD50 Oral | Rat | 3500 mg/kg | - |
|--|-----------|-----|------------|---|

### Irritation/Corrosion

| Product/ingredient name                                     | Result                   | Species | Score | Exposure        | Observation |
|-------------------------------------------------------------|--------------------------|---------|-------|-----------------|-------------|
| acetone                                                     | Eyes - Mild irritant     | Human   | -     | 186300 ppm      | -           |
|                                                             | Eyes - Mild irritant     | Rabbit  | -     | 10 uL           | -           |
|                                                             | Eyes - Moderate irritant | Rabbit  | -     | 24 hours 20 mg  | -           |
|                                                             | Eyes - Severe irritant   | Rabbit  | -     | 20 mg           | -           |
|                                                             | Skin - Mild irritant     | Rabbit  | -     | 395 mg          | -           |
|                                                             | Skin - Mild irritant     | Rabbit  | -     | 24 hours 500 mg | -           |
| butanone                                                    | Skin - Mild irritant     | Rabbit  | -     | 24 hours 14 mg  | -           |
|                                                             | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 mg | -           |
| xylene                                                      | Eyes - Mild irritant     | Rabbit  | -     | 87 mg           | -           |
|                                                             | Eyes - Severe irritant   | Rabbit  | -     | 24 hours 5 mg   | -           |
|                                                             | Skin - Mild irritant     | Rat     | -     | 8 hours 60 uL   | -           |
|                                                             | Skin - Moderate irritant | Rabbit  | -     | 100 %           | -           |
|                                                             | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 mg | -           |
|                                                             | Eyes - Mild irritant     | Rabbit  | -     | 100 mg          | -           |
| reaction product: bisphenol-A-(epichlorhydrin); epoxy resin | Skin - Moderate irritant | Rabbit  | -     | 24 hours 500 uL | -           |
|                                                             | Skin - Severe irritant   | Rabbit  | -     | 24 hours 2 mg   | -           |
|                                                             | Skin - Mild irritant     | Rabbit  | -     | 24 hours 15 mg  | -           |

### Sensitisation

Not available.

### Potential chronic health effects

|                        |                                                                                                                                                                          |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>General</b>         | : May cause damage to organs through prolonged or repeated exposure. Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. |
| <b>Inhalation</b>      | : No known significant effects or critical hazards.                                                                                                                      |
| <b>Ingestion</b>       | : No known significant effects or critical hazards.                                                                                                                      |
| <b>Skin contact</b>    | : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.                                                                    |
| <b>Eye contact</b>     | : No known significant effects or critical hazards.                                                                                                                      |
| <b>Carcinogenicity</b> | : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.                                                                                 |
| <b>Mutagenicity</b>    | : No known significant effects or critical hazards.                                                                                                                      |
| <b>Teratogenicity</b>  | : Suspected of damaging the unborn child.                                                                                                                                |

## Section 11. Toxicological information

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : Suspected of damaging fertility.

### Chronic toxicity

Not available.

### Carcinogenicity

Not available.

### Mutagenicity

Not available.

### Teratogenicity

Not available.

### Reproductive toxicity

Not available.

### Specific target organ toxicity

| Name                                                        | Category   | Route of exposure | Target organs |
|-------------------------------------------------------------|------------|-------------------|---------------|
| butanone                                                    | Category 2 | -                 | -             |
| xylene                                                      | Category 2 | -                 | -             |
| reaction product: bisphenol-A-(epichlorhydrin); epoxy resin | Category 2 | -                 | -             |
| ethylbenzene                                                | Category 2 | -                 | -             |

### Aspiration hazard

Not available.

### Numerical measures of toxicity

#### Acute toxicity estimates

| Route                | ATE value      |
|----------------------|----------------|
| Oral                 | 22621.19 mg/kg |
| Dermal               | 49766.62 mg/kg |
| Inhalation (vapours) | 263.88 mg/l    |

## Section 12. Ecological information

**Ecotoxicity** : No known significant effects or critical hazards.

### Aquatic and terrestrial toxicity

| Product/ingredient name | Result                               | Species                                        | Exposure |
|-------------------------|--------------------------------------|------------------------------------------------|----------|
| acetone                 | Acute EC50 20.565 mg/l Marine water  | Algae - <i>Ulva pertusa</i>                    | 96 hours |
|                         | Acute LC50 4.42589 ml/L Marine water | Crustaceans - <i>Acartia tonsa</i> - Copepodid | 48 hours |
|                         | Acute LC50 10 mg/l Fresh water       | Daphnia - <i>Daphnia magna</i>                 | 48 hours |
|                         | Acute LC50 5600 ppm Fresh water      | Fish - <i>Poecilia reticulata</i>              | 96 hours |
|                         | Chronic NOEC 4.95 mg/l Marine water  | Algae - <i>Ulva pertusa</i>                    | 96 hours |
|                         | Chronic NOEC 0.016 ml/L Fresh water  | Crustaceans - <i>Daphniidae</i>                | 21 days  |
|                         | Chronic NOEC 1 g/L Fresh water       | Daphnia - <i>Daphnia magna</i>                 | 21 days  |

## Section 12. Ecological information

|                 |                                                                                                                                               |                                                                                                                                                                          |                                              |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|
| butanone        | Acute EC50 >500 mg/l Marine water<br>Acute EC50 5091 mg/l Fresh water                                                                         | Algae - <i>Skeletonema costatum</i><br>Daphnia - <i>Daphnia magna</i> -<br>Larvae                                                                                        | 96 hours<br>48 hours                         |
| n-butyl acetate | Acute LC50 3220 mg/l Fresh water                                                                                                              | Fish - <i>Pimephales promelas</i>                                                                                                                                        | 96 hours                                     |
| xylene          | Acute LC50 185 ppm Marine water<br>EC50 3.82 mg/l                                                                                             | Fish - <i>Menidia beryllina</i><br>Crustaceans - <i>Penaeus monodon</i>                                                                                                  | 96 hours<br>48 hours                         |
| ethylbenzene    | Acute LC50 13.4 mg/l Fresh water<br>Acute EC50 4600 µg/l Fresh water<br>Acute EC50 3600 µg/l Fresh water<br>Acute LC50 13.3 mg/l Marine water | Fish - <i>Pimephales promelas</i><br>Algae - <i>Raphidocelis subcapitata</i><br>Algae - <i>Raphidocelis subcapitata</i><br>Crustaceans - <i>Artemia sp.</i> -<br>Nauplii | 96 hours<br>72 hours<br>96 hours<br>48 hours |
|                 | Acute LC50 13.9 mg/l Fresh water                                                                                                              | Daphnia - <i>Daphnia magna</i> -<br>Neonate                                                                                                                              | 48 hours                                     |

### Persistence/degradability

| Product/ingredient name | Test       | Result         | Dose | Inoculum |
|-------------------------|------------|----------------|------|----------|
| xylene                  | OECD 301 F | 90 % - 28 days | -    | -        |

| Product/ingredient name | Aquatic half-life | Photolysis | Biodegradability |
|-------------------------|-------------------|------------|------------------|
| xylene                  | -                 | -          | Readily          |

### Bioaccumulative potential

| Product/ingredient name                                     | LogP <sub>ow</sub> | BCF         | Potential |
|-------------------------------------------------------------|--------------------|-------------|-----------|
| dimethyl ether                                              | 0.07               | -           | Low       |
| acetone                                                     | -0.23              | -           | Low       |
| butanone                                                    | 0.3                | -           | Low       |
| n-butyl acetate                                             | 2.3                | -           | Low       |
| 2-methoxy-1-methylethyl acetate                             | 1.2                | -           | Low       |
| xylene                                                      | 3.12               | 8.1 to 25.9 | Low       |
| reaction product: bisphenol-A-(epichlorhydrin); epoxy resin | 2.64 to 3.78       | 31          | Low       |
| ethylbenzene                                                | 3.6                | -           | Low       |

### Mobility in soil

**Soil/water partition coefficient** : Not available.

**Other adverse effects** : No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its

## Section 13. Disposal considerations

container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

## Section 14. Transport information

|                            | New Zealand Class (5433)                                                                 | IMDG                                                                                     | IATA                                                                                       |
|----------------------------|------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| UN number                  | UN1950                                                                                   | UN1950                                                                                   | UN1950                                                                                     |
| UN proper shipping name    | AEROSOLS                                                                                 | AEROSOLS                                                                                 | Aerosols, flammable                                                                        |
| Transport hazard class(es) | 2.1<br> | 2.1<br> | 2.1<br> |
| Packing group              | -                                                                                        | -                                                                                        | -                                                                                          |
| Environmental hazards      | No.                                                                                      | No.                                                                                      | No.                                                                                        |

**Hazchem code** : Not available.

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to IMO instruments** : Not available.

The actual shipping description for this product may vary based several factors including, but not limited to, the volume of material, size of the container, mode of transport and use of exemptions or exceptions found in the applicable regulations. The information provided in Section 14 is one possible shipping description for this product. Consult your shipping specialist or supplier for appropriate assignment information.

## Section 15. Regulatory information

**HSNO Approval Number** : HSR002517

**HSNO Group Standard** : Aerosols (Flammable, Carcinogenic) Group Standard 2020

**HSNO Classification** : AEROSOLS - Category 1  
 EYE IRRITATION - Category 2  
 SKIN SENSITISATION - Category 1  
 CARCINOGENICITY - Category 2  
 REPRODUCTIVE TOXICITY - Category 2  
 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2

## Section 16. Other information

### History

|                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Date of issue</b>        | : 18 June 2025                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Version</b>              | : 2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Prepared by</b>          | Product stewardship and regulatory compliance.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Key to abbreviations</b> | : ACGIH = Association Advancing Occupational and Environmental Health<br>ATE = Acute Toxicity Estimate<br>BCF = Bioconcentration Factor<br>GHS = Globally Harmonized System of Classification and Labelling of Chemicals<br>HSWA = Health and Safety at Work Act 2015<br>IATA = International Air Transport Association<br>IBC = Intermediate Bulk Container<br>IMDG = International Maritime Dangerous Goods<br>LogPow = logarithm of the octanol/water partition coefficient<br>MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)<br>TLV = Threshold Limit Value<br>WES = Workplace Exposure Standards |

■ Indicates information that has changed from previously issued version.

### Notice to reader

This product is intended for industrial use only.

Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

© 2022 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.