



Safety Data Sheet

© 2023, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	06-2070-8	Version number:	4.00
Issue Date:	06/08/2023	Supersedes date:	02/08/2020

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

SECTION 1: Identification

1.1. Product identifier

3M 08684, 08782, 08783 Polyurethane General Purpose Seam Sealer, Grey

Product Identification Numbers

FI-3000-0104-2 FI-3000-0113-3

1.2. Recommended use and restrictions on use

Recommended use

Automotive., General purpose seam sealer

For Industrial or Professional use only

1.3. Supplier's details

Address: 3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland
Telephone: (09) 477 4040
E Mail: innovation@nz.mmm.com
Website: 3m.co.nz

1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

SECTION 2: Hazard identification

Classified as hazardous in accordance with the relevant criteria of the HSNO Act 1996 and the Hazardous Substances (Hazard Classification) Notice 2020.

Refer to Section 14 of this Safety Data Sheet for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

Respiratory sensitisation: Category 1

Skin sensitisation: Category 1

Carcinogenicity: Category 2

Specific target organ toxicity – single exposure: Category 2

Specific target organ toxicity – repeated exposure: Category 2

2.2. Label elements

SIGNAL WORD

Danger

Symbols:

Health Hazard |

Pictograms



HAZARD STATEMENTS:

H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H371	May cause damage to organs: sensory organs.
H373	May cause damage to organs through prolonged or repeated exposure: nervous system sensory organs.

PRECAUTIONARY STATEMENTS

Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280E	Wear protective gloves.
P284	Wear respiratory protection.

Response

P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Storage

P405	Store locked up.
------	------------------

Disposal

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

2.3. Other hazards

A similar mixture has been tested for eye damage/irritation and the test results do not meet the criteria for classification. Persons previously sensitized to isocyanates may develop a cross-sensitization reaction to other isocyanates.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	% by Weight
Poly(Vinyl Chloride)	9002-86-2	20 - 40
Sulphonic acids, C10-18-alkane, Ph esters	70775-94-9	20 - 40
Polyurethane prepolymer	Trade Secret	15 - 40
Xylene	1330-20-7	3 - 7
Titanium dioxide	13463-67-7	1 - 3
Calcium oxide	1305-78-8	1 - 3
Ethylbenzene	100-41-4	0.5 - 1.5
Distillates (petroleum), hydrotreated light	64742-47-8	0.5 - 1.5
P,P'-Methylenebis(phenyl isocyanate)	101-68-8	< 1

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

The most important symptoms and effects based on the CLP classification include:

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products**Substance**

Carbon monoxide.
Carbon dioxide.
Hydrogen Chloride
Hydrogen cyanide.
Oxides of nitrogen.

Condition

During combustion.
During combustion.
During combustion.
During combustion.
During combustion.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

5.4. Hazchem code: Not applicable.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a container approved for transportation by appropriate authorities, but do not seal the container for 48 hours to avoid pressure build-up. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

Refer to Section 15 - Controls for more information

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Keep away from reactive metals (eg. Aluminum, zinc etc.) to avoid the formation of hydrogen gas that could create an explosion hazard. Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Keep container tightly closed to prevent contamination with water or air. If contamination is suspected, do not reseal container. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

7.3. Certified handler

Not required

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Ethylbenzene	100-41-4	ACGIH	TWA:20 ppm	A3: Confirmed animal carcin., Ototoxicant
Ethylbenzene	100-41-4	New Zealand	TWA(8 hours):88 mg/m3(20	Skin

		WES	ppm);STEL(15 minutes):176 mg/m3(40 ppm) TWA:0.005 ppm	
P,P'-Methylenebis(phenyl isocyanate)	101-68-8	ACGIH		
P,P'-Methylenebis(phenyl isocyanate)	101-68-8	New Zealand WES	TWA(inhalable fraction and vapor)(8 hours):0.02 mg/m3;STEL(inhalable fraction and vapor)(15 minutes):0.07 mg/m3 TWA:2 mg/m3	Dermal sensitiser, Respiratory sensitiser
Calcium oxide	1305-78-8	ACGIH		
Calcium oxide	1305-78-8	New Zealand WES	TWA(8 hours): 2 mg/m3	
Xylene	1330-20-7	ACGIH	TWA:20 ppm;STEL:150 ppm	A4: Not class. as human carcinogen
Xylene	1330-20-7	New Zealand WES	TWA(8 hours):217 mg/m3(50 ppm)	
Titanium dioxide	13463-67-7	ACGIH	TWA(Respirable nanoscale particles):0.2 mg/m3;TWA(Respirable finescale particles):2.5 mg/m3 TWA(8 hours):10 mg/m3	A3: Confirmed animal carcinogen.
Titanium dioxide	13463-67-7	New Zealand WES		
Jet fuels (non-aerosol), as total hydrocarbon vapour	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3	A3: Confirmed animal carcin., SKIN
Kerosine (petroleum)	64742-47-8	ACGIH	TWA(as total hydrocarbon vapor, non-aerosol):200 mg/m3	A3: Confirmed animal carcin., SKIN
Dust, inert or nuisance	9002-86-2	New Zealand WES	TWA(as respirable dust)(8 hours):3 mg/m3;TWA(as inhalable dust)(8 hours):10 mg/m3	
Poly(Vinyl Chloride)	9002-86-2	ACGIH	TWA(respirable fraction):1 mg/m3	A4: Not class. as human carcinogen

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

New Zealand WES : New Zealand Workplace Exposure Standards.

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

ppm: parts per million

mg/m³: milligrams per cubic metre

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety glasses with side shields.

Refer AS/NZS 1336 - Recommended practices for occupational eye protection and for performance specifications AS/NZS 1337, Parts 1 - 6 - Personal eye-protection.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Fluoroelastomer

Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Refer AS/NZS 1715 - Selection, use and maintenance of respiratory protective equipment and AS/NZS 1716 - Respiratory protective devices.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	Solid.
Specific Physical Form:	Paste
Colour	Grey
Odour	Light Odour
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Melting point/Freezing point	<i>No data available.</i>
Boiling point/Initial boiling point/Boiling range	137 °C
Flash point	75 °C
Evaporation rate	<i>No data available.</i>
Flammability (solid, gas)	Not classified
Flammable Limits(LEL)	0.6 % volume
Flammable Limits(UEL)	7 % volume
Vapour pressure	<i>No data available.</i>
Vapor Density and/or Relative Vapor Density	<i>No data available.</i>
Density	1.17 g/cm ³ [@ 20 °C]
Relative density	1.17 [Ref Std: WATER=1]
Water solubility	Immiscible
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	>= 200 °C
Decomposition temperature	<i>No data available.</i>
Viscosity/Kinematic Viscosity	<i>No data available.</i>
Volatile organic compounds (VOC)	<i>No data available.</i>
Percent volatile	± 5 %
VOC less H₂O & exempt solvents	<i>No data available.</i>

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Heat.

High shear and high temperature conditions

Sparks and/or flames.

10.5 Incompatible materials

Amines.

Alcohols.

Water

Reaction with water, alcohols, and amines is not hazardous if container can vent to the atmosphere to prevent pressure buildup.

Accelerators

Combustibles.

Finely divided active metals

Strong acids.

Strong bases.

Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Carbon dioxide.	Moisture.

Refer to Section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Allergic respiratory reaction: Signs/symptoms may include difficulty breathing, wheezing, cough, and tightness of chest. May cause additional health effects (see below).

Skin contact

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye contact

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

Additional Health Effects:**Single exposure may cause target organ effects:**

Auditory effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears.

Prolonged or repeated exposure may cause target organ effects:

Neurological effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and changes in blood pressure and heart rate.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Additional information:

Persons previously sensitised to isocyanates may develop a cross-sensitisation reaction to other isocyanates.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Poly(Vinyl Chloride)	Dermal		LD50 estimated to be > 5,000 mg/kg
Poly(Vinyl Chloride)	Ingestion		LD50 estimated to be > 5,000 mg/kg
Sulphonic acids, C10-18-alkane, Ph esters	Dermal	Rat	LD50 > 1,000 mg/kg
Sulphonic acids, C10-18-alkane, Ph esters	Ingestion	Rat	LD50 > 5,000 mg/kg
Xylene	Dermal	Rabbit	LD50 > 4,200 mg/kg
Xylene	Inhalation-Vapor (4 hours)	Rat	LC50 29 mg/l
Xylene	Ingestion	Rat	LD50 3,523 mg/kg
Titanium dioxide	Dermal	Rabbit	LD50 > 10,000 mg/kg
Titanium dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 6.82 mg/l
Titanium dioxide	Ingestion	Rat	LD50 > 10,000 mg/kg
Calcium oxide	Ingestion	Rat	LD50 > 2,500 mg/kg
Calcium oxide	Dermal	similar compounds	LD50 > 2,500 mg/kg
Ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg
Ethylbenzene	Inhalation-Vapor (4 hours)	Rat	LC50 17.4 mg/l
Ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg
Distillates (petroleum), hydrotreated light	Inhalation-	Professio	LC50 estimated to be 20 - 50 mg/l

	Vapor	nal judgeme nt	
Distillates (petroleum), hydrotreated light	Dermal	Rabbit	LD50 > 5,000 mg/kg
Distillates (petroleum), hydrotreated light	Ingestion	Rat	LD50 > 5,000 mg/kg
P,P'-Methylenebis(phenyl isocyanate)	Dermal	Rabbit	LD50 > 5,000 mg/kg
P,P'-Methylenebis(phenyl isocyanate)	Inhalation- Dust/Mist (4 hours)	Rat	LC50 0.368 mg/l
P,P'-Methylenebis(phenyl isocyanate)	Ingestion	Rat	LD50 31,600 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Poly(Vinyl Chloride)	Profession nal judgemen t	No significant irritation
Xylene	Rabbit	Mild irritant
Titanium dioxide	Rabbit	No significant irritation
Calcium oxide	Human	Corrosive
Ethylbenzene	Rabbit	Mild irritant
Distillates (petroleum), hydrotreated light	Rabbit	Mild irritant
P,P'-Methylenebis(phenyl isocyanate)	official classificat ion	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Overall product	Rabbit	Mild irritant
Xylene	Rabbit	Mild irritant
Titanium dioxide	Rabbit	No significant irritation
Calcium oxide	Rabbit	Corrosive
Ethylbenzene	Rabbit	Moderate irritant
Distillates (petroleum), hydrotreated light	Rabbit	Mild irritant
P,P'-Methylenebis(phenyl isocyanate)	official classificat ion	Severe irritant

Sensitisation:

Skin Sensitisation

Name	Species	Value
Titanium dioxide	Human and animal	Not classified
Ethylbenzene	Human	Not classified
Distillates (petroleum), hydrotreated light	Guinea pig	Not classified
P,P'-Methylenebis(phenyl isocyanate)	official classificat ion	Sensitising

Respiratory Sensitisation

Name	Species	Value
P,P'-Methylenebis(phenyl isocyanate)	Human	Sensitising

Germ Cell Mutagenicity

Name	Route	Value
Poly(Vinyl Chloride)	In Vitro	Not mutagenic
Xylene	In Vitro	Not mutagenic
Xylene	In vivo	Not mutagenic
Titanium dioxide	In Vitro	Not mutagenic
Titanium dioxide	In vivo	Not mutagenic
Calcium oxide	In Vitro	Not mutagenic
Ethylbenzene	In vivo	Not mutagenic
Ethylbenzene	In Vitro	Some positive data exist, but the data are not sufficient for classification
Distillates (petroleum), hydrotreated light	In Vitro	Not mutagenic
Distillates (petroleum), hydrotreated light	In vivo	Not mutagenic
P,P'-Methylenebis(phenyl isocyanate)	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Poly(Vinyl Chloride)	Not specified.	Rat	Some positive data exist, but the data are not sufficient for classification
Xylene	Dermal	Rat	Not carcinogenic
Xylene	Ingestion	Multiple animal species	Not carcinogenic
Xylene	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Titanium dioxide	Ingestion	Multiple animal species	Not carcinogenic
Titanium dioxide	Inhalation	Rat	Carcinogenic.
Ethylbenzene	Inhalation	Multiple animal species	Carcinogenic.
Distillates (petroleum), hydrotreated light	Not specified.	Not available	Not carcinogenic
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Poly(Vinyl Chloride)	Not specified.	Not classified for development	Mouse	NOAEL Not available	during gestation
Xylene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Xylene	Ingestion	Not classified for development	Mouse	NOAEL Not available	during organogenesis
Xylene	Inhalation	Not classified for development	Multiple animal species	NOAEL Not available	during gestation
Ethylbenzene	Inhalation	Not classified for development	Rat	NOAEL 4.3 mg/l	premating & during gestation
Distillates (petroleum), hydrotreated light	Not specified.	Not classified for female reproduction	Rat	NOAEL Not available	1 generation
Distillates (petroleum), hydrotreated light	Not specified.	Not classified for male reproduction	Rat	NOAEL Not available	1 generation
Distillates (petroleum), hydrotreated light	Not specified.	Not classified for development	Rat	NOAEL Not available	1 generation
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	Not classified for development	Rat	NOAEL 0.004 mg/l	during organogenesis

Lactation

Name	Route	Species	Value
Xylene	Ingestion	Mouse	Not classified for effects on or via lactation

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Xylene	Inhalation	auditory system	Causes damage to organs	Rat	LOAEL 6.3 mg/l	8 hours
Xylene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Xylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Xylene	Inhalation	eyes	Not classified	Rat	NOAEL 3.5 mg/l	not available
Xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
Xylene	Ingestion	eyes	Not classified	Rat	NOAEL 250 mg/kg	not applicable
Calcium oxide	Inhalation	respiratory irritation	May cause respiratory irritation	Not available	NOAEL Not available	occupational exposure
Ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Poly(Vinyl Chloride)	Inhalation	respiratory system	Not classified	Multiple animal species	NOAEL 0.013 mg/l	22 months
Xylene	Inhalation	nervous system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.4 mg/l	4 weeks
Xylene	Inhalation	auditory system	May cause damage to organs though prolonged or repeated exposure	Rat	LOAEL 7.8 mg/l	5 days
Xylene	Inhalation	liver	Not classified	Multiple animal species	NOAEL Not available	
Xylene	Inhalation	heart endocrine system gastrointestinal tract hematopoietic system muscles kidney and/or bladder respiratory system	Not classified	Multiple animal species	NOAEL 3.5 mg/l	13 weeks
Xylene	Ingestion	auditory system	Not classified	Rat	NOAEL 900 mg/kg/day	2 weeks
Xylene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days
Xylene	Ingestion	liver	Not classified	Multiple animal	NOAEL Not available	

				species		
Xylene	Ingestion	heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system immune system nervous system respiratory system	Not classified	Mouse	NOAEL 1,000 mg/kg/day	103 weeks
Titanium dioxide	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 0.01 mg/l	2 years
Titanium dioxide	Inhalation	pulmonary fibrosis	Not classified	Human	NOAEL Not available	occupational exposure
Ethylbenzene	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.1 mg/l	2 years
Ethylbenzene	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 1.1 mg/l	103 weeks
Ethylbenzene	Inhalation	hematopoietic system	Not classified	Rat	NOAEL 3.4 mg/l	28 days
Ethylbenzene	Inhalation	auditory system	Not classified	Rat	NOAEL 2.4 mg/l	5 days
Ethylbenzene	Inhalation	endocrine system	Not classified	Mouse	NOAEL 3.3 mg/l	103 weeks
Ethylbenzene	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Inhalation	bone, teeth, nails, and/or hair muscles	Not classified	Multiple animal species	NOAEL 4.2 mg/l	90 days
Ethylbenzene	Inhalation	heart immune system respiratory system	Not classified	Multiple animal species	NOAEL 3.3 mg/l	2 years
Ethylbenzene	Ingestion	liver kidney and/or bladder	Not classified	Rat	NOAEL 680 mg/kg/day	6 months
P,P'-Methylenebis(phenyl isocyanate)	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.004 mg/l	13 weeks

Aspiration Hazard

Name	Value
Xylene	Aspiration hazard
Ethylbenzene	Aspiration hazard
Distillates (petroleum), hydrotreated light	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Ecotoxic to the aquatic environment.

Acute Aquatic Toxicity: Category 3

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Poly(Vinyl Chloride)	9002-86-2	N/A	Data not available or insufficient for classification	N/A	N/A	N/A
Polyurethane prepolymer	Trade Secret	N/A	Data not available or insufficient for classification	N/A	N/A	NA
Sulphonic acids, C10-18-alkane, Ph esters	70775-94-9	Medaka	Experimental	96 hours	LC50	>100 mg/l
Sulphonic acids, C10-18-alkane, Ph esters	70775-94-9	Water flea	Experimental	48 hours	No tox obs at lmt of water sol	>100 mg/l
Sulphonic acids, C10-18-alkane, Ph esters	70775-94-9	Green algae	Experimental	72 hours	EC10	>=2 mg/l
Xylene	1330-20-7	Activated sludge	Estimated	3 hours	NOEC	157 mg/l
Xylene	1330-20-7	Green algae	Estimated	73 hours	EC50	4.36 mg/l
Xylene	1330-20-7	Rainbow trout	Estimated	96 hours	LC50	2.6 mg/l
Xylene	1330-20-7	Water flea	Estimated	48 hours	EC50	3.82 mg/l
Xylene	1330-20-7	Green algae	Estimated	73 hours	NOEC	0.44 mg/l
Xylene	1330-20-7	Rainbow trout	Estimated	56 days	NOEC	>1.3 mg/l
Xylene	1330-20-7	Water flea	Estimated	7 days	NOEC	0.96 mg/l
Calcium oxide	1305-78-8	Common Carp	Experimental	96 hours	LC50	1,070 mg/l
Titanium dioxide	13463-67-7	Activated sludge	Experimental	3 hours	NOEC	>=1,000 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	EC50	>10,000 mg/l
Titanium dioxide	13463-67-7	Fathead minnow	Experimental	96 hours	LC50	>100 mg/l
Titanium dioxide	13463-67-7	Water flea	Experimental	48 hours	EC50	>100 mg/l
Titanium dioxide	13463-67-7	Diatom	Experimental	72 hours	NOEC	5,600 mg/l
Ethylbenzene	100-41-4	Green algae	Estimated	73 hours	EC50	4.36 mg/l
Ethylbenzene	100-41-4	Rainbow trout	Estimated	96 hours	LC50	2.6 mg/l
Ethylbenzene	100-41-4	Water flea	Estimated	48 hours	EC50	3.82 mg/l
Ethylbenzene	100-41-4	Activated sludge	Experimental	49 hours	EC50	130 mg/l
Ethylbenzene	100-41-4	Green algae	Estimated	73 hours	NOEC	0.44 mg/l
Ethylbenzene	100-41-4	Rainbow trout	Estimated	56 days	NOEC	>1.3 mg/l
Ethylbenzene	100-41-4	Water flea	Estimated	7 days	NOEC	0.96 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Green algae	Experimental	72 hours	EL50	>1,000 mg/l
Distillates (petroleum),	64742-47-8	Rainbow trout	Experimental	96 hours	LL50	>1,000 mg/l

hydrotreated light						
Distillates (petroleum), hydrotreated light	64742-47-8	Water flea	Experimental	48 hours	EL50	>1,000 mg/l
Distillates (petroleum), hydrotreated light	64742-47-8	Green algae	Experimental	72 hours	NOEL	1,000 mg/l
P,P'-Methylenebis(p henyl isocyanate)	101-68-8	Activated sludge	Estimated	3 hours	EC50	>100 mg/l
P,P'-Methylenebis(p henyl isocyanate)	101-68-8	Green algae	Estimated	72 hours	EC50	>1,640 mg/l
P,P'-Methylenebis(p henyl isocyanate)	101-68-8	Water flea	Estimated	24 hours	EC50	>1,000 mg/l
P,P'-Methylenebis(p henyl isocyanate)	101-68-8	Zebra Fish	Estimated	96 hours	LC50	>1,000 mg/l
P,P'-Methylenebis(p henyl isocyanate)	101-68-8	Green algae	Estimated	72 hours	NOEC	1,640 mg/l
P,P'-Methylenebis(p henyl isocyanate)	101-68-8	Water flea	Estimated	21 days	NOEC	10 mg/l

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Poly(Vinyl Chloride)	9002-86-2	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Polyurethane prepolymer	Trade Secret	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Sulphonic acids, C10-18-alkane, Ph esters	70775-94-9	Estimated Biodegradation	28 days	BOD	51 %BOD/ThO D	
Xylene	1330-20-7	Experimental Biodegradation	28 days	BOD	90-98 %BOD/ThO D	OECD 301F - Manometric respirometry
Calcium oxide	1305-78-8	Data not availbl-insufficient	N/A	N/A	N/A	N/A
Titanium	13463-67-7	Data not	N/A	N/A	N/A	N/A

dioxide		availbl-insufficient				
Ethylbenzene	100-41-4	Estimated Biodegradation	28 days	BOD	90-98 %BOD/ThO D	OECD 301F - Manometric respirometry
Distillates (petroleum), hydrotreated light	64742-47-8	Estimated Biodegradation	28 days	BOD	69 %BOD/ThO D	OECD 301F - Manometric respirometry
P,P'-Methylenebis(p henyl isocyanate)	101-68-8	Estimated Hydrolysis		Hydrolytic half-life	20 hours (t 1/2)	

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Poly(Vinyl Chloride)	9002-86-2	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Polyurethane prepolymer	Trade Secret	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Sulphonic acids, C10-18-alkane, Ph esters	70775-94-9	Experimental BCF - Fish	36 days	Bioaccumulation factor	56-212	
Xylene	1330-20-7	Experimental BCF - Fish	56 days	Bioaccumulation factor	25.9	
Calcium oxide	1305-78-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Titanium dioxide	13463-67-7	Experimental BCF - Fish	42 days	Bioaccumulation factor	9.6	
Ethylbenzene	100-41-4	Experimental BCF - Fish	56 days	Bioaccumulation factor	25.9	
Distillates (petroleum), hydrotreated light	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
P,P'-Methylenebis(p henyl isocyanate)	101-68-8	Experimental BCF - Fish	28 days	Bioaccumulation factor	200	OECD305-Bioconcentration

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Disposal methods

In accordance with the Hazardous Substances (Disposal) Notice 2017 and the relevant criteria of the HSNO Act 1996.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

Packaging (that may or may not contain any residual substance) may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

SECTION 14: Transport Information

New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport

UN No.: Not applicable.

Proper Shipping Name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Hazchem Code: Not applicable.

IERG: Not applicable.

International Air Transport Association (IATA) - Air Transport

UN No.: Not applicable.

Proper Shipping Name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

International Maritime Dangerous Goods Code (IMDG) - Marine Transport

UN No.: Not applicable.

Proper Shipping Name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Marine Pollutant: Not applicable.

SECTION 15: Regulatory information

HSNO Approval number HSR002679

Group standard name Surface Coatings and Colourants (Carcinogenic) Group Standard 2020

HSNO Hazard classification Refer to Section 2: Hazard identification

NZ Inventory of Chemicals (NZIoC) Status

All applicable chemical ingredients in this material are in compliance with NZIoC listing requirements.

Controls in accordance with The Health and Safety at Work Act 2015, Health and Safety at Work (Hazardous Substances) Regulations 2017 and the HSNO Act 1996, Hazardous Substances (Hazardous Property Controls) Notice

2017

Certified handler	Not required
Location Compliance Certificate	Not required
Hazardous atmosphere zone	Not required
Fire extinguishers	Not required
Emergency response plan	100 L or 100 kg (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L or 1 000 kg (for Acute toxicity Category 4, Skin sensitisation Category 1, Respiratory sensitisation Category 1, Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for all other substances)
Secondary containment	100 L or 100 kg (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L or 1 000 kg (for Acute toxicity Category 4, Skin sensitisation Category 1, Respiratory sensitisation Category 1, Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for all other substances)
Tracking	Not required
Warning signage	100 L or 100 kg (for Hazardous to the aquatic environment Category 1 substances); or 1 000 L or 1 000 kg (for Serious eye damage Category 1, Hazardous to the aquatic environment Category 2 or Hazardous to the aquatic environment Category 3 substances); or 10 000 L or 10 000 kg (for Acute toxicity Category 4 or Hazardous to the aquatic environment Category 4 substances)

SECTION 16: Other information**Revision information:**

Complete document review.

Document group:	06-2070-8	Version number:	4.00
Issue Date:	06/08/2023	Supersedes date:	02/08/2020

Key to abbreviations and acronyms**GHS** refers to the Globally Harmonised System of Classification and Labelling of Chemicals, 7th revised edition of 2017**HSNO** means Hazardous Substances and New Organisms Act 1996

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: <http://solutions.3mnz.co.nz>