



# 1948 siaflex

Flexible and versatile



### Flexible and versatile

As an all-round series for wet and dry sanding, 1948 siaflex produces outstanding results in all available grits and in a variety of automotive applications.

- ▶ High performance for stock removal with good finish
- ▶ Highly flexible and adaptable to contours
- ▶ Minimal clogging thanks to open coating in 220 - 600 grit range
- ▶ Long lifetime
- ▶ Suitable for general use in dry and wet sanding applications
- ▶ Versatile all-round product with an attractive range of options

### Product profile

|                  |                                    |             |
|------------------|------------------------------------|-------------|
| Grit type:       | Blue-fired / white aluminium oxide |             |
| Grit range:      | 40; 60-1500                        |             |
| Backing:         | Latex paper (FSC-certified)        |             |
| Coating:         | Electrostatic                      | P040 – P180 |
|                  | Electrostatic open                 | P220 – P600 |
|                  | Electrostatic                      | 800         |
| Bonding:         | Resin over resin                   |             |
| Special coating: | Stearate                           | P180 – 800  |

### Use



### Applications

- Sanding of coatings and impurities
- Sanding out unevenness at the edges of repaired surfaces
- Flatting of bodyfiller and primer filler
- Fine sanding of primer filler
- Keying of old and new lacquers
- Removal of orange peel effect and dust inclusions

### Materials

Colour; Primer filler; Bodyfiller; Lacquer; Old lacquer; Primer coat; Epoxy primer coat; Cathodic dip primer coat; Plastics; Acrylic glass; Gelcoat polyester; Glass-fibre reinforced plastic (GRP); Composite; Aluminium; steel

### Technology

Open coating; Plain; S Performance; siafast; siasoft