



7983 siasponge flex

Adapts perfectly to the workpiece

Medium 120–180

Fine 240–320

Superfine 500–600

Ultrafine 800–1000

Microfine 1200–1500



Adapts perfectly to the workpiece

Be it curves, shapes or contours – an even and perfect sanding pattern can be achieved with 7983 siasponge flex. The extra-soft foam of siasponge flex ensures maximum conformability.

- ▶ Can be used wet or dry
- ▶ Colour coded for easy identification
- ▶ Low clogging thanks to 3D properties imparted by foam, binder system and grit
- ▶ For hard-to-reach areas and round profiles
- ▶ Consistent surface finishes even on curved workpieces
- ▶ Regular scratch depth due to consistent grinding performance
- ▶ Minimal risk of sanding through from high contact pressure

Product profile

Grit type:	Aluminium oxide
Grit range:	60-220; 280
Backing:	PU foam (soft)
Coating:	Mechanical
Bonding:	Elastic binder
Coating:	2-sided

Applications

- Keying of wood and plastics
- Keying of conventional old and new varnishes, primer filler and paints
- Fine sanding of primer filler in hard-to-reach areas
- Producing a matt finish on varnishes
- Flatting of bodyfiller and primer filler
- Intermediate sanding of varnishes

Use



Materials

Colour; Primer filler; Primer coat; Plastics; Old lacquer; Composite