

C-POWER




DESCRIPTION

C-Power is a powerful high strength biodegradable cleaner that is excellent for all hard surfaces around your home or work. It leaves a clean surface with the refreshing citrus fragrance. C-Power is also ideal for washing vinyl or wooden floors and as a vehicle prewash and degreaser before repainting.




PROPERTIES

| | |
|----------------------|--------------------------|
| Product Type: | Cleaner |
| Colour: | Clear |
| Density: | Approx 1.00 kg/L |
| Solubility in Water: | Soluble |
| Scent: | Strong citrus fragrance. |



DILUTION

| | |
|-----------------------|--|
| Light soiling | 100 parts water to 1 part C-Power |
| Moderate soiling: | 50 parts water to 1 part C-Power |
| Remove silicone oils: | 20 parts water to 1 part C-Power (test a small area first) |



APPLICATION

Substrates

- Vinyl
- Laminates
- Flooring
- Hard surfaces with grease and oil build up
- Construction clean up
- Truck curtains
- Pre clean before painting
- Bare metal (with red scotch)
- Vehicle wash to remove silicon grooming oils etc (use at 20:1, patch test first))



DIRECTIONS FOR USE

- Wear gloves to protect skin.
- Dilute with water.
- Spray on or apply with a sponge or cloth.
- Wipe off with a clean cloth or sponge.
- For vehicle prewash - wash vehicle down with water, apply C-Power, and wash off. Do not allow C-Power to dry on the vehicle.

Can be also be pressure sprayed on and fed into water blasters.



HEALTH & SAFETY

ALWAYS READ THE SAFETY DATY SHEET (SDS) PRIOR TO USE.

Observe the precautionary notices displayed on the container.

If solution gets in eyes, rinse cautiously with water for 15 minutes, seek medical attention if irritation occurs.

If solution gets on skin, remove all contaminated clothing and wash body with soap and water, seek medical attention if irritation occurs.

For further information, contact Resene Automotive and Light Industrial Ph 0800 108 008 or NZ National Poison Centre Ph 0800 Poison.

Transport & Storage

| | |
|--------|-------------|
| Sizes: | 1L, 4L, 20L |
|--------|-------------|

Dangerous Goods

| | |
|----------------|--------|
| UN: | UN3082 |
| Hazchem: | 3Z |
| Packing Group: | III |

No warranty either expressed or implied is made by RALI in this document, which is a technical data information sheet. The description of the product and its properties is for the sole purpose of identifying the product and does not constitute a warranty that the product or its properties shall conform to that description, nor is the description of the product and its properties a warranty by RALI that the goods are suitable for a particular purpose. Do not apply paint if relative humidity is above 85% or temperature is within 3 deg C of Dew Point being the MPT or Minimum Paint Temperature