



# ENGINE DEGREASER

### Description



Engine degreaser is a general purpose cleaner/degreaser specially formulated for the motor industry to remove grease and oil from engine parts and workshop areas such as flooring.

### Products



#### Product Type:

**Colour:** Clear

#### Pot Life:

#### Induction Time:

**Density:** 0.813 kg/L.


**Solubility in water:** Negligible

#### Recommended DFT:

#### Theoretical Coverage:

**Other Properties:** Has a solvent odour


### Substrates



Workshop floors

Engines

### Directions For Use



Spray or brush on.

Leave 5-10 minutes and hose off with water.

Repeat if necessary.

### Spray

#### Equipment:



Can be sprayed on or brushed on.

### Health & Safety



Irritant-Avoid contact with eyes or skin. If swallowed, DO NOT induce vomiting. Contact a doctor or Poisons Information Centre. For further safety information consult the current Safety Data Sheet (SDS).

### Transport & Storage

**Sizes:** 1L, 5L, 20L

**Dangerous Goods:** 3b

No warranty either expressed or implied is made by RALI in this document, which is a technical data information sheet. The description of the product and its properties is for the sole purpose of identifying the product and does not constitute a warranty that the product or its properties shall conform to that description, nor is the description of the product and its properties a warranty by RALI that the goods are suitable for a particular purpose. Do not apply paint if relative humidity is above 85% or temperature is within 3 deg C of Dew Point being the MPT or Minimum Paint Temperature.



**UN:** 1263  
**Hazchem:** 3[Y]  
**Packing Group:** III  
**Shipment name:**  
**Flash point:** 38°C

No warranty either expressed or implied is made by RALI in this document, which is a technical data information sheet. The description of the product and its properties is for the sole purpose of identifying the product and does not constitute a warranty that the product or its properties shall conform to that description, nor is the description of the product and its properties a warranty by RALI that the goods are suitable for a particular purpose. Do not apply paint if relative humidity is above 85% or temperature is within 3 deg C of Dew Point being the MPT or Minimum Paint Temperature.