

Soft Wash

Description	A fully biodegradable everything from dish wa	multipurpose detergent for general household use. Ideal for ashing to hard surfaces.	
Products	Product Type:	Solvents Mixture	
AB	Colour:		
	Pot Life:	N/A	
©Ψ <u></u>	Induction Time:		
	Density:	Approx. 1.00 kg/L	
	Solubility in water:	Soluble	
Substrates	Soft Wash is a general p	ourpose biodegradable detergent for general household use.	
Dilution	Dishwashing: 20 parts water to 1 part Soft Wash.		
A : 5	Hard Surfaces: 10 parts water to 1 part Soft Wash.		
Directions For	Dishwashing: use as per normal dishwashing detergent.		
Use	Hard surfaces: Apply by sponge or cloth. Dry off if necessary.		
	Ensure correct dilution for use.		
	Note: Wear gloves if you have sensitive skin.		
Health &	If swallowed, rinse out with fresh water and contact the Poison Centre or consult a doctor.		
Safety	Wear rubber gloves, if you have sensitive skin.		
	If contact with solution is made, remove all contaminated clothing and wash body with soap and water.		
	If inhaled and breathing becomes difficult, remove to fresh air and keep in rest position. If condition continues seek medical assistance.		
	If solution gets in eyes, rinse cautiously with water for several minutes. Continue rinsing if		
	eye irritation persists.		
	For further information NZ National Poison Cen	contact Resene Automotive and Light Industrial Ph 0800 108 008 or tre Ph 0800 Poison.	

No warranty either expressed or implied is made by RALI in this document, which is a technical data information sheet. The description of the product and its properties is for the sole purpose of identifying the product and does not constitute a warranty that the product or its properties shall conform to that description, nor is the description of the product and its properties a warranty by RALI that the goods are suitable for a particular purpose. Do not apply paint if relative humidity is above 85% or temperature is within 3 deg C of Dew Point being the MPT or Minimum Paint Temperature.

Resene		Technical Data Sheet		
and the second sec	e & Light Industrial	May 2011	This data sheet supersedes all previous issues	
Transport &	Sizes:	4L, 20L		
Storage	Dangerous Goods:			
	UN:	NA		
	Hazchem:			
	Packing Group:			
	Shipment name:	Non-flammable		

No warranty either expressed or implied is made by RALI in this document, which is a technical data information sheet. The description of the product and its properties is for the sole purpose of identifying the product and does not constitute a warranty that the product or its properties shall conform to that description, nor is the description of the product and its properties a warranty by RALI that the goods are suitable for a particular purpose. Do not apply paint if relative humidity is above 85% or temperature is within 3 deg C of Dew Point being the MPT or Minimum Paint Temperature.

Resene Automotive & Light Industrial |4 Te Apunga Place |P O Box 62 282| Mt Wellington Mail Centre | Auckland 1541 |DDI +64 9 259 2738 | FAX +64 9 259 2737 | www.rali.co.nz or email info@rali.co.nz