



SAFETY DATA SHEET

Section 1. Identification of the material and the supplier

Product: **Colad® Undercoating M80**
Product Code: 4010 (Black) / 4020(White) / 4030(Grey)
Product Use: Undercoating
Restriction of Use: Refer to Section 15

New Zealand Supplier: **Auto Body Equipment**
Address: 17 The Boulevard
Te Rapa, Hamilton, 3200
New Zealand

Telephone: +64 7 849 3514
Email: office@abe.co.nz
Emergency No: 0800 764 766 (National Poison Centre)

Date of SDS Preparation: 24 August 2018

Section 2. Hazards Identification

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval No: Surface Coatings and Colourants (Flammable) – HSR002662

Pictograms



Flammable



Irritant



Asp/ Chronic



Ecotoxic

Signal Word: **DANGER**

HSNO Classes	Hazard Code	Hazard Statement	GHS Category
3.1B	H225	Highly flammable liquid and vapour.	Flam. Liq. 2
6.1E (asp)	H304	May be fatal if swallowed and enters airways.	Asp. Tox. 1
6.3B	H316	Causes mild skin irritation.	Skin Irrit. 3
6.4A	H319	Causes serious eye irritation.	Eye Irrit. 2A
6.8B	H361	Suspected of damaging fertility or the unborn child.	Repr. 2
6.9B	H373	May cause damage to organs through prolonged or repeated exposure.	STOT RE 2
6.9N	H336	May cause drowsiness or dizziness.	STOT SE 3
9.1B	H411	Toxic to aquatic life with long lasting effects.	Aquatic Chronic 2

Prevention Code	Prevention Statement
P102	Keep out of reach of children.
P103	Read label before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, sparks, open flames or hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe fumes, vapours or spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective clothing.
P281	Use personal protective equipment as required.

Response Code	Response Statement
P101	If medical advice is needed, have product container or label at hand.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P331	Do NOT induce vomiting.
P391	Collect spillage.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303 + P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305 + P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P370 + P378	In case of fire: Use CO2, sand, extinguishing powder for extinction.

Storage Code	Storage Statement
P405	Store locked up.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.

Disposal Code	Disposal Statement
P501	Dispose of according to Local Regulations or Authorities

Section 3. Composition / Information on Hazardous Ingredients

Ingredients	Wt%	CAS NUMBER.
Naphtha (petroleum), hydrotreated light	20-70	64742-49-0
Ethyl acetate	10-<25	141-78-6
Naphtha (Petroleum) hydrodesulfurized heavy	0.5-10	64742-82-1
Solvent naphtha (petroleum), light arom.	1-<5	64742-95-6
Non hazardous	To bal	

Section 4. First Aid Measures

Routes of Exposure:

If in Eyes Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.

If on Skin	Rinse skin with water/shower. If skin irritation occurs: get medical advice/attention.
If Swallowed	Do NOT induce vomiting. Rinse mouth. Never give anything to the mouth of an unconscious person. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs. IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
If Inhaled	Remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Apply artificial respiration if not breathing. Get medical advice if breathing becomes difficult.

Most important symptoms and effects, both acute and delayed

Symptoms:

Ingestion:	Not applicable.
Inhalation:	Not applicable.
Skin:	Causes mild skin irritation.
Eye:	Causes serious eye irritation.
Chronic:	Suspected of damaging fertility or the unborn child. Prolonged or repeated exposure may cause damage to the organs. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness.

Section 5.	Fire Fighting Measures
-------------------	-------------------------------

Hazard Type	Flammable Liquid
Hazards from products	None known.
Suitable Extinguishing media	CO2, sand, extinguishing powder. Do not use water with full jet.
Precautions for firefighters and special protective clothing	Wear full protective gear.
HAZCHEM CODE	3YE

Section 6.	Accidental Release Measures
-------------------	------------------------------------

Wear protective gear as detailed in Section 8. Evacuate all unnecessary personnel. Keep away from ignition sources.

Prevent seepage into sewage system, workpits and cellars.
 Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Ensure adequate ventilation.
 Do not flush with water or aqueous cleansing agents

Dispose of waste according to the applicable local and national regulations.

Section 7.	Handling and Storage
-------------------	-----------------------------

Precautions for Handling:

- Keep out of reach of children.
- Read label before use.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.

- Keep away from heat, sparks, open flames or hot surfaces. No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical, ventilating, lighting.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Do not breathe fumes, mist, vapours or spray.
- Wash hands thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Use only outdoors or in a well-ventilated area.
- Wear protective clothing.
- Use personal protective equipment as required.

Precautions for Storage:

- Store away from incompatible materials listed in Section 10.
- Store locked up.
- Store in a well-ventilated place. Keep container tightly closed.
- Keep cool, dry and in well-sealed receptacles.

Section 8 Exposure Controls / Personal Protection

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance	TWA		STEL	
	ppm	mg/m ³	ppm	mg/m ³
Ethyl acetate [141-78-6]	200	720		

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices NOV 2017 9TH EDITION.

DNELs		
64742-49-0 Naphtha (petroleum), hydrotreated light		
Oral	Long-term - systemic effects, general population	149 mg/kg bw/day (General Population)
Dermal	Long-term - systemic effects, general population	149 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects, worker	300 mg/kg bw/day (Worker)
	Long-term - systemic effects, general population	477 mg/m3 (General Population)
	Long-term - systemic effects, worker	2085 mg/m3 (Worker)

Engineering Controls

Ensure there is adequate ventilation available.

Personal Protection Equipment



Eyes	Tightly sealed goggles with side shields. Avoid wearing contact lenses.
Skin	Wear Fluorocarbon rubber (Viton) gloves with penetration time of >480 min. Wear protective clothing.
Respiratory	In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Filter A/P2 / Filter AX
General	Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing

	Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes.
--	---

Section 9 Physical and Chemical Properties

Form	Fluid
Colour	Black/Whitish or Grey
Odour	Characteristic
Odour Threshold	Not available
pH @20°C	Not available
Boiling Point	78°C
Melting Point	Not available
Freezing Point	Not available
Flash Point	-9°C (DIN 53213)
Flammability	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Upper and Lower Explosive Limits	1.1 – 10.5% (vol)
Vapour Pressure @20°C	97 hPa @20°C / 306 hPa @ 50°C
Density@ 20°C	1.02 - 1.04 g/cm ³ (DIN 51757)
Specific Gravity	Not available
Water Solubility	Not miscible or difficult to mix.
Partition Coefficient:	Not available
Ignition Temperature	200°C
Decomposition Temperature	Not available
Dynatic Viscosity @20°C	690 mPas
Particle Characteristics	Not available
Solvent content	Organic Solvents: 53.0%
Solids content	47.0% (DIN 53216)
VOC(EU)	Black: 53.09 % White: 54.32% Grey: 52.99% 552.20g/l 554.0 g/l 551.1 g/l

Section 10. Stability and Reactivity

Stability of Substance	This product is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reactions known.
Conditions to Avoid	Keep away from ignition sources and heat.
Incompatible Materials	None known.
Hazardous Decomposition Products	None known.

Section 11 Toxicological Information

Acute Effects:

Swallowed	Not applicable.
Dermal	Not applicable.
Inhalation	Not applicable.
Eye	Causes serious eye irritation.
Skin	Causes mild skin irritation.

Chronic Effects:

Carcinogenicity	Not applicable.
Reproductive Toxicity	Suspected of damaging fertility or the unborn child.
Germ Cell	Not applicable.

Mutagenicity	
Aspiration	May be fatal if swallowed and enters airways.
STOT/SE	May cause dizziness and drowsiness.
STOT/RE	May cause damage to organs through prolonged or repeated exposure.

Acute Toxicity -

Chemical Name	LD50 (Oral)	LD50 (Dermal)	LC50 (inhalation)
Product			
Solvent naphtha (petroleum), light arom. (Cas No 64742-95-6)	>6800mg/kg(Rat)	>3400mg/kg(Rat)	>10.2mg/l (Rat)
Ethyl Acetate (Cas No 141-78-6)	4100mg/kg (mouse)	-	-

Section 12. Ecotoxicological Information

HSNO Classes: 9.1B = Toxic to aquatic life with long lasting effects.

Persistence and degradability	No data available
Bioaccumulation	No data available
Mobility in Soil	No data available
Other adverse effects	Slightly hazardous for water. Do not allow undiluted product to reach ground water, water course or sewage system. Also poisonous for fish and plankton in water bodies.

Aquatic toxicity for individual chemicals:

Naphtha (petroleum), hydrotreated light (cas No : 64742-49-0)
EC50/48 h 10 mg/l (PHAEOPHYTA)

Do not allow to enter waterways.

Section 13. Disposal Considerations

Disposal Method:

Spent media that has removed toxic chemicals should be examined for specific hazards. Spilled product liquid may be recovered for use if it has not come in contact with liquids or been exposed to significant amounts of gaseous contaminants. Dispose of according to Local Regulations.

Ensure any container holding waste product or contaminated spill media is labelled "Hazardous Waste – "Flammable Liquid, Ecotoxic " and that the label also has the Flammable and Ecotoxic Pictogram, and the business name, address, and phone number.

Precautions or methods to avoid: Must not be disposed together with household garbage. Avoid release to the environment.

Section 14 Transport Information

This product is classified as a Dangerous Good for transport in NZ ; NZS 5433:2012



Road and Rail Transport

UN No: 1139

Product Name: Colad Undercoating 4010/4020/4030
Date of SDS: 24 August 2018

Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: 64 9 475 5240 www.techcomp.co.nz

Class-primary 3
Packing Group II
Proper Shipping Name: COATING SOLUTION

Air Transport

UN No: 1139
Class-primary 3
Packing Group II
Proper Shipping Name: COATING SOLUTION

Marine Transport

UN No: 1139
Class-primary 3
Packing Group II
Proper Shipping Name: COATING SOLUTION
Marine Pollutant: Yes

Limited Quantities Statement:

If the product's individual container is below 5L, it can be transported as a non-DG as long as the product packaging is still labelled as per DG requirements and the driver is given safety information in accordance with Chapter 3.4 of the UNRTDG.

Section 15 Regulatory Information

New Zealand:

This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval Code: Surface Coatings and Colourants (Flammable) – HSR002662

HSNO Classification: 3.1B, 6.1E(asp), 6.3B, 6.4A, 6.8B, 6.9B, 6.9N, 9.1B

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity
Certified Handler	Not required
Location Certificate	100L (>5L), 250L(<5L), 50L open
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	250L (3.1B)
Emergency Response Plan	1000L (3.1B, 9.1B)
Secondary Containment	1000L (3.1B, 9.1B)
Fire Extinguishers	250L - require 2X
Restriction of Use	Only use for the intended purpose.

Section 16 Other Information

Glossary

EC ₅₀	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC ₅₀	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD ₅₀	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

References:

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
2. Workplace Exposure Standards and Biological Exposure Indices Nov 2017 edition.
3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
4. Transport of Dangerous goods on land NZS 5433:2012
5. HSW (Hazardous Substances) Regulations 2017

Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact Auto Body Equipment, if further information is required.

Issue Date: 24 August 2018 Review Date: 24 August 2023