



## SAFETY DATA SHEET

### Section 1. Identification of the material and the supplier

Product: **Dekaseal 8936 Light Grey**  
Product Use: Sealant  
Restriction of Use: Refer to Section 15

New Zealand Supplier: **Auto Body Equipment**  
Address: 17 The Boulevard  
Te Rapa, Hamilton, 3200  
New Zealand

Telephone: +64 7 849 3514  
Email: office@abe.co.nz  
**Emergency No: 0800 764 766 (National Poison Centre)**

Date of SDS Preparation: 22 June 2018

### Section 2. Hazards Identification

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

**EPA Approval No: Surface Coatings and Colourants (Flammable) – HSR002662**

#### Pictograms



Flammable



Aspiration



Ecotoxic

Signal Word: **DANGER**

HSNO Classes	Hazard Code	Hazard Statement	GHS Category
3.1B	H225	Highly flammable liquid and vapour.	Flam. Liq. 2
6.1E (asp)	H304	May be fatal if swallowed and enters airways.	Asp. Tox. 1
9.1B	H411	Toxic to aquatic life with long lasting effects.	Aquatic Chronic 2

Prevention Code	Prevention Statement
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, sparks, open flames or hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating, lighting.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.

P273	Avoid release to the environment.
P280	Wear protective clothing.

Response Code	Response Statement
P101	If medical advice is needed, have product container or label at hand.
P331	Do NOT induce vomiting.
P391	Collect spillage.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303 + P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P370 + P378	In case of fire: Use CO2, sand, extinguishing powder for extinction.

Storage Code	Storage Statement
P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.

Disposal Code	Disposal Statement
P501	Dispose of according to Local Regulations or Authorities

### Section 3. Composition / Information on Hazardous Ingredients

Ingredients	Wt%	CAS NUMBER.
Naphtha (petroleum), hydrotreated light	10-<25	64742-49-0
Naphtha (petroleum), hydrodesulfurized heavy	<1	64742-82-1
Non hazardous	To bal	

### Section 4. First Aid Measures

Routes of Exposure:

If in Eyes	Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice.
If on Skin	Wash skin with water/shower. If skin irritation occurs: get medical advice/attention.
If Swallowed	Rinse mouth. Never give anything to the mouth of an unconscious person. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs. Call a POISON CENTER if unwell.
If Inhaled	Remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Apply artificial respiration if not breathing. Get medical advice if breathing becomes difficult.

#### Most important symptoms and effects, both acute and delayed

Symptoms:

<b>Ingestion:</b>	Not applicable.
<b>Inhalation:</b>	Not applicable.
<b>Skin:</b>	Not applicable.
<b>Eye:</b>	Not applicable.
<b>Chronic:</b>	May be fatal if swallowed and enters airways.

**Section 5. Fire Fighting Measures**

<b>Hazard Type</b>	Flammable.
<b>Hazards from products</b>	None known.
<b>Suitable Extinguishing media</b>	CO2, sand, extinguishing powder. Do not use water with full jet.
<b>Precautions for firefighters and special protective clothing</b>	Wear full protective clothing.
<b>HAZCHEM CODE</b>	<b>3YE</b>

**Section 6. Accidental Release Measures**

Wear protective gear as detailed in Section 8. Evacuate all unnecessary personnel.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Dispose of waste according to the applicable local and national regulations.

**Section 7. Handling and Storage****Precautions for Handling:**

- Keep out of reach of children.
- Read label before use.
- Keep away from heat, sparks, open flames or hot surfaces. No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical, ventilating, lighting.
- Use only non-sparking tools.
- Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Take precautionary measures against static discharge.
- Avoid release to the environment.
- Wear protective clothing.

**Precautions for Storage:**

- Store away from incompatible materials listed in Section 10.
- Store locked up.
- Store in a well-ventilated place. Keep cool.

**Section 8 Exposure Controls / Personal Protection****WORKPLACE EXPOSURE STANDARDS (provided for guidance only)**

Substance	TWA		STEL	
	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>

No ingredients have exposure limits

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the

## Engineering Controls

Ensure there is adequate ventilation available.

## Personal Protection Equipment

<b>Eyes</b>	Tightly sealed goggles.
<b>Skin</b>	Wear Nitrile gloves.
<b>Respiratory</b>	In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Filter A/P2 / Filter AX
<b>General</b>	Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols.

## Section 9 Physical and Chemical Properties

<b>Form</b>	Pasty
<b>Colour</b>	Light Grey
<b>Odour</b>	Characteristic
<b>Odour Threshold</b>	Not available
<b>pH @20°C</b>	Not available
<b>Boiling Point</b>	78°C
<b>Melting Point</b>	Not available
<b>Freezing Point</b>	Not available
<b>Flash Point</b>	-9 °C (DIN 53213)
<b>Flammability</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
<b>Upper and Lower Explosive Limits</b>	0.8 – 7.7% (vol)
<b>Vapour Pressure @20°C</b>	61 hPa
<b>Density@ 20°C</b>	1.34 g/cm <sup>3</sup> (DIN 51757)
<b>Specific Gravity</b>	Not available
<b>Water Solubility</b>	Not miscible or difficult to mix.
<b>Partition Coefficient:</b>	Not available
<b>Ignition Temperature</b>	200°C
<b>Decomposition Temperature</b>	Not available
<b>Dynatic Viscosity @20°C</b>	Not determined
<b>Particle Characteristics</b>	Not available
<b>Solvent content</b>	Organic Solvents: 12.6%
<b>Solids content</b>	87.4% (DIN 53216)
<b>VOC(EU)</b>	168.5 g/L 12.57%

## Section 10. Stability and Reactivity

<b>Stability of Substance</b>	This product is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reactions known.
<b>Conditions to Avoid</b>	None known.
<b>Incompatible Materials</b>	None known.
<b>Hazardous Decomposition Products</b>	No dangerous decomposition products known.

## Section 11 Toxicological Information

### Acute Effects:

<b>Swallowed</b>	Not applicable.
<b>Dermal</b>	Not applicable.
<b>Inhalation</b>	Not applicable.
<b>Eye</b>	Not applicable.
<b>Skin</b>	Not applicable.

**Chronic Effects:**

<b>Carcinogenicity</b>	Not applicable.
<b>Reproductive Toxicity</b>	Not applicable.
<b>Germ Cell Mutagenicity</b>	Not applicable.
<b>Aspiration</b>	May be fatal if swallowed and enters airways.
<b>STOT/SE</b>	Not applicable.
<b>STOT/RE</b>	Not applicable.

**Acute Toxicity -**

<b>Chemical Name</b>	<b>LD50 (Oral)</b>	<b>LD50 (Dermal)</b>	<b>LC50 (inhalation)</b>
<b>Product</b>			
Naphtha (petroleum), hydrotreated light (Cas No 64742-49-0)	5000mg/kg(Rat)	>2600mg/kg(Rat)	>193mg/l (Rat)

**Section 12. Ecotoxicological Information**

HSNO Classes: 9.1B = Toxic to aquatic life with long lasting effects.

<b>Persistence and degradability</b>	No data available
<b>Bioaccumulation</b>	No data available
<b>Mobility in Soil</b>	No data available
<b>Other adverse effects</b>	Slightly hazardous for water. Do not allow undiluted product to reach ground water, water course or sewage system.

Acquatic toxicity:

**64742-49-0 Naphtha (petroleum), hydrotreated light**  
EC50/48 h 10 mg/l (PHAEOPHYTA)

**Section 13. Disposal Considerations**

**Disposal Method:**

Spent media that has removed toxic chemicals should be examined for specific hazards. Spilled product may be recovered for use if it has not come in contact with liquids or been exposed to significant amounts of gaseous contaminants. Dispose of according to Local Regulations.

Ensure any container holding waste product or contaminated spill media is labelled "Hazardous Waste – "Spilled Flammable " and that the label also has the Flammable Pictogram, and the business name, address, and phone number.

**Precautions or methods to avoid:** Must not be disposed together with household garbage. Avoid release to the environment.

**Section 14 Transport Information**

**This product is classified as a Dangerous Good for transport in NZ ; NZS 5433:2012**

**Road and Rail Transport**

UN No: 1133

Product Name: Dekaseal 8936 - Lightgrey  
Date of SDS: 22 June 2018

Prepared by: Technical Compliance Consultants (NZ) Ltd  
Tel: 64 9 475 5240 www.techcomp.co.nz

Class-primary 3  
Packing Group II  
Proper Shipping Name: ADHESIVES CONTAINING FLAMMABLE LIQUID

**Air Transport**

UN No: 1133  
Class-primary 3  
Packing Group II  
Proper Shipping Name: ADHESIVES CONTAINING FLAMMABLE LIQUID

**Marine Transport**

UN No: 1133  
Class-primary 3  
Packing Group II  
Proper Shipping Name: ADHESIVES CONTAINING FLAMMABLE LIQUID

**Limited Quantities Statement:**

If the product's individual container is below 5L, it can be transported as a non-DG as long as the product packaging is still labelled as per DG requirements and the driver is given safety information in accordance with Chapter 3.4 of the UNRTDG.

**Section 15 Regulatory Information**

**New Zealand:**

This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval Code: Surface Coatings and Colourants (Flammable) – HSR002662

HSNO Classification: 3.1B, 6.1E(Asp), 9.1B

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity
Certified Handler	Not required
Location Certificate	100L (>5L), 250L(<5L), 50L open
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	250L (3.1B)
Emergency Response Plan	1,000L (3.1B)
Secondary Containment	1,000L (3.1B)
Fire Extinguishers	250L - require 2X
Restriction of Use	Only use for the intended purpose.

**Section 16 Other Information**

**Glossary**

EC <sub>50</sub>	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC <sub>50</sub>	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD <sub>50</sub>	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

References:

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
2. Workplace Exposure Standards and Biological Exposure Indices Nov 2017 edition.
3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
4. Transport of Dangerous goods on land NZS 5433:2012
5. HSW (Hazardous Substances) Regulations 2017

Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact Auto Body Equipment, if further information is required.

Issue Date: 22 June 2018 Review Date: 23 June 2023