

MATERIAL SAFETY DATA SHEET ADDENDUM

Page 0

N Z Specific Information addendum to Material Safety Data Sheet for Product No. **100420 Easy Sand** this must be read in conjunction with the MSDS from evercoat.com

Date Revised: 31/10/2019

SECTION 1	ADDITIONAL INFORMATION	
NZ Supplier:	Hindin Marquip Limited	
Head Office:	1012 Great South Road, Penrose 1061	
Phone:	09 579 9667	

EMERGENCY TELEPHONE 0800 POISON (0800 764 766)

SECTION 2

ADDITIONAL INFORMATION

This substance is hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001

HSNO CLASSIFICATION	HAZARD DESCRIPTION
3.1C	Flammable Liquid – medium hazard
6.1C	Substances that are acutely toxic -Toxic
6.3A	Substances that are irritating to the skin
6.4A	Substances that are irritating to the eye
6.6B	Substances that are suspected human mutagens
6.7B	Substances that are suspected human carcinogens
6.8B	Substances that are suspected or presumed human reproductive or developmental toxicants
6.9A	Substances that are toxic to human target organs or systems
9.1A	Substances that are very ecotoxic to the aquatic environment or are otherwise designed for biocidal
	action
9.3B	Substances that are ecotoxic to terrestrial vertebrates

PICTOGRAMS



SECTION 15

ADDITIONAL INFORMATION

EPA Approval: - HSR002665 – Surface Coatings and Colourants (Flammable, Toxic [6.1 + 6.7]) Group Standard 2006

SECTION 16

ADDITIONAL INFORMATION

Disclaimer

The modifications to this Safety Data Sheet made by M J Nankivell Haztec Ltd have been restricted to Adding New Zealand specific information only as required under the HSNO Act 1996 and associated regulations and no changes have been made to the Technical Content.

No Liability or responsibility shall be taken by M.J Nankivell Haztec Ltd for the technical content, or accidents or incidents arising from the use thereof.



Stock Number: 100420 Revision Date: 06-20-2017 Replaces: 01-20-2017

Easy Sand 24 ounce

1. Identification	
Product identifier used on the label: Stock Number:	Easy Sand 24 ounce 100420
Other means of identification: Synonyms:	None Known
Recommended use of the chemical and re Recommended use: Restrictions on use:	estrictions on use: Polyester Finishing and Blending Putty Premium Light weight body filler Uses other than recommended use.
Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party:	ITW Evercoat a division of Illinois Tool Works Inc. 6600 Cornell Road Cincinnati, OH 45242 513-489-7600
Telephone number:	CHEMTREC: 1-800-424-9300 CANUTEC: 1-613-996-6666
Emergency phone number:	CHEMTREC: 1-800-424-9300 CANUTEC: 1-613-996-6666

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Hazard Symbols:

GHS Classification:

Skin Sensitisation Category 1 Carcinogenicity Category 1A Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 1 Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 1 Aspiration Hazard Category 1 Skin Corrosion/Irritation Category 2 Serious Eye Damage/Eye Irritation Category 2A Germ Cell Mutagenicity Category 2 Reproductive Toxicity Category 2

	Product identifier used on the label: Easy Sand 24 ounce Stock Number: 100420 Revision Date: 06-20-2017 Replaces: 01-20-2017
	Hazardous to the aquatic environment - Acute Category 2
	Flammable Liquid Category 3
Signal Word:	Danger
Hazard Statements:	Flammable liquid and vapor.
	May be fatal if swallowed and enters airways.
	Causes skin irritation.
	May cause an allergic skin reaction.
	Causes serious eye irritation.
	Suspected of causing genetic defects.
	May cause cancer.
	Suspected of damaging fertility or the unborn child.
	Causes damage to organs.
	Causes damage to organs through prolonged or repeated exposure.
	Toxic to aquatic life.
Precautionary Statements: Prevention:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Keep container tightly closed.
	Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash with soap and water thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face
Response:	 Wear protective gloves/protective clothing/eye protection/race protection. If swallowed: Immediately call a poison center/doctor. IF ON SKIN: Wash with plenty of soap and water. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Specific treatment (see Sections 4 to 8 on the SDS and any additional information on the label). Do NOT induce vomiting.

Product identifier used on the label: Easy Sand 24 ounce

Stock Number: 100420 Revision Date: 06-20-2017 Replaces: 01-20-2017

	If skin irritation or rash occurs: Get medical advice/attention.		
	If eye irritation persists: Get medical advice/attention.		
	Take off contaminated clothing and wash it before reuse.		
	In case of fire: Use appropriate media to extinguish.		
Storage:	Keep container tightly closed. Store in a well-ventilated place. Keep cool.		
	Store locked up.		
Disposal:	Dispose of contents in accordance with your local disposal company along with national/international regulations.		
Hazards not otherwise classified:	Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.		

3. Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS #	%	
Silica, amorphous	None Known	7631-86-9	0.1 - 1	
Tetrahydrophthalic anhydride	None Known	85-43-8	1 - 5	
Titanium dioxide	None Known	13463-67-7	1 - 5	
Glass enamel	None Known	65997-17-3	5 - 10	
Talc	None Known	14807-96-6	10 - 30	
Styrene	None Known	100-42-5	10 - 30	

One or more hazardous ingredient(s) is claimed as a trade secret under the OSHA Hazard Communication Standard. The hazards of this (these) ingredient(s) are given on this SDS.

4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

Inhalation:	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately If the victim has stopped breathing open airway, loosen collar and belt, and administer artificial respiration. Keep the victim warm and quiet.
Eye Contact:	Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.
Skin Contact:	Wash with soap and water. Get medical attention if irritation develops or persists. Wash clothing before reuse. Remove contaminated clothing

Product identifier used on the label: Easy Sand 24 ounce Stock Number: 100420 Revision Date: 06-20-2017 Replaces: 01-20-2017				
	and continue flushing with water.			
Ingestion:	Do not induce vomiting and seek medical attention immediately. Drink two glasses of water or milk to dilute. Provide medical care provider with this SDS. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. If possible, do not leave individual unattended. If individual is drowsy or unconscious, do not give anything by mouth; place individual on left side with head down.			
Most important symptoms/effects, acute and delayed:	May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Causes damage to organs. Causes damage to organs through prolonged or repeated exposure			
Indication of immediate medical attention and special treatment needed, if necessary:	Specific treatment (see Sections 4 to 8 on the SDS and any additional information on this label).			

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media:	Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agents. Water may be ineffective but water spray can be used extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire. Regular foam
Unsuitable extinguishing media:	No data available
Specific hazards arising from the chemical:	Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back.
Hazardous combustion products:	Carbon dioxide, Carbon monoxide, Styrene oxide, Hydrocarbons, Phthalic anhydride
Special protective equipment and precautions for fire-fighters:	Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Wear a self contained breathing apparatus (NIOSH approved) with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Water may be used to cool closed containers to prevent pressure build-up and possible auto ignition or explosion when exposed to extreme heat.

Product identifier used on the label: Easy Sand 24 ounce Stock Number: 100420 Revision Date: 06-20-2017 Replaces: 01-20-2017

	•
6. Accidental release measures	
Personal precautions, protective equipment and emergency procedures:	No health affects expected from the clean-up of this material if contact can be avoided. Follow personal protective equipment recommendations found in Section 8 of this SDS
Methods and materials for containment and cleaning up:	No special spill clean-up considerations. Collect and discard in regular trash. Use an inert absorbent such as sand or vermiculite. Place in properly labeled closed container. Avoid breathing vapors. All personnel in the area should be protected as in Section 8. Activate available exhaust ventilation equipment in the immediate spill area. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.
7. Handling and storage	
Precautions for safe handling:	Mildly irritating material. Avoid unnecessary exposure. Keep out of the reach of children. Keep container closed when not in use. Do not take internally. Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Use with adequate ventilation Wash hands before eating Do not get in eyes, on skin and clothing All hazard precautions given in the data sheet must be observed.
Conditions for safe storage, including any	r incompatibilities:
Safe storage conditions:	Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Avoid contact with incompatible materials. Store in a tightly closed container Keep away from heat, sparks, and flame For maximum product quality, avoid prolonged storage at temperatures above 75 °F (25 °C).
Materials to Avoid/Chemical Incompatibility:	Peroxides, Strong acids, Strong oxidizing agents, Polymerization catalysts

8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Styrene	100 ppm	20 ppm	40 ppm STEL; 170	700 ppm IDLH
			mg/m3 STEL	
Talc	20 mppcf	2 mg/m3	No data available	1000 mg/m3 IDLH
				(containing no

Product identifier used on the label: Easy Sand 24 ounce

Stock Number: 100420

Revision Date: 06-20-2017

Replaces: 01-20-2017

				asbestos and <1% quartz)	
Glass enamel	5mg/m3	10mg/m3	No data available	No data available	
Titanium dioxide	15 mg/m3	10 mg/m3	No data available	5000 mg/m3 IDLH	
Appropriate engineering co	ntrols: No exp exhaus and ma	No exposure limits exist for the constituents of this product. Use local exhaust ventilation or other engineering controls to minimize exposures and maintain operator comfort.			
Individual protection measu	•	• • • •		vorovnoguro whon	
Respiratory Protection:		Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Use a NIOSH approved respirator designed to remove particulate matter and organic solvent vapors.			
Eye protection:		Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses. Splash proof chemical goggles are recommended to protect against the splash of product.			
Skin protection:		Not normally considered a skin hazard. Where use can result in skin contact, practice good personal hygiene and wear a barrier cream and/or impervious surgical style gloves. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. A barrier cream may be used for additional skin protection. To prevent repeated or prolonged skin contact, wear impervious clothing and boots Gloves should be made of neoprene or natural rubber. Protective gloves and proper clothing should be worn to prevent skin contact.			
Gloves:		Protective gloves are recommended when prolonged skin contact cannot be avoided.			
Other protective equipment:		A barrier cream may be used for additional skin protection. To prevent repeated or prolonged skin contact, wear impervious clothing and boots Gloves should be made of neoprene or natural rubber. Protective gloves and proper clothing should be worn to prevent skin contact. Splash proof chemical goggles are recommended to protect against the splash of product.			
General hygiene conditions:	Do not or fum ventila	p out of the reach of children. Keep container closed when not in use. not take internally. Avoid contact with material, avoid breathing dusts umes, use only in a well ventilated area. Use with adequate tilation Wash hands before eating Do not get in eyes, on skin and hing All hazard precautions given in the data sheet must be observed.			

Product identifier used on the label: Easy Sand 24 ounce Stock Number: 100420 Revision Date: 06-20-2017 Replaces: 01-20-2017

9. Physical and chemical properties

Appearance (physical state, color etc.):	
Physical state:	Paste
Color:	White
Odor:	Aromatic
Odor Threshold:	No data available
pH:	Neutral
Melting point/freezing point (°C):	
Melting Point (°C):	No data available
Freezing point (°C):	No data available
Initial boiling point and boiling range (°C):	145
Flash Point (°C):	35
Evaporation Rate:	No data available
Flammability (solid, gas):	No data available
Upper/lower flammability or explosive limits:	
Upper flammability or explosive limits:	6.1
Lower flammability or explosive limits:	1.1
Vapor pressure:	No data available
Vapor density:	Heavier than air. Vapors that evolve from this product will tend to settle and accumulate near the floor.
Relative density:	1.02
Solubility(ies):	Insoluble
Partition coefficient: n-octanol/water:	1.36
Auto-ignition temperature (°C):	No data available
Decomposition temperature (°C):	No data available
Viscosity:	27,200 - 32,000
Volatile Organic Chemicals:	20 - 25 %
	20 - 25%
	20%
VOC (as packaged-less exempts and water):	1.94 lbs/gal or 233 g/L

Product identifier used on the label: Easy Sand 24 ounce

Stock Number: 100420 **Revision Date:** 06-20-2017

Replaces: 01-20-2017

VOC (as applied*- 2% by wt hardener- less exempts and water):	0.26 lbs/gal or 31 g/L
Percent Solids by weight – as packaged (%):	77.2
Percent Solids by weight – as applied* - 2% by wt hardener (%):	96.8
VHAP Content by weight – as packaged (%):	22.8 %
VHAP Content by weight – as applied* - 2% by weight hardener (%):	3.2 %
Bulk density:	8.5
	8.86

10. Stability and reactivity

Reactivity:	Not expected to be reactive
Chemical stability:	Stable under normal handling conditions
Possibility of hazardous reactions:	None expected under standard conditions of storage
Conditions to avoid (e.g., static discharge, shock, or vibration):	Contamination
Incompatible materials:	Peroxides, Strong acids, Strong oxidizing agents, Polymerization catalysts
Hazardous decomposition products:	Carbon dioxide, Carbon monoxide, Styrene oxide, Hydrocarbons, Phthalic anhydride

11. Toxicological information Description of the various toxicological (health) effects and the available data used to identify those effects: Information on the likely routes of Absorption, Eye contact, Skin contact, Ingestion exposure (inhalation, ingestion, skin and eye contact): Symptoms related to the physical, May be fatal if swallowed and enters airways. Causes skin irritation. May chemical and toxicological cause an allergic skin reaction. Causes serious eye irritation. Causes characteristics: damage to organs. Causes damage to organs through prolonged or repeated exposure Delayed and immediate effects and also chronic effects from short- and long-term exposure: **Ingestion Toxicity:** Harmful if swallowed. May cause systemic poisoning. **Skin Contact:** Can cause minor skin irritation, defatting, and dermatitis. Symptoms may

include redness, burning, drying and cracking of skin, and skin burns No

Product identifier used on the label: Easy Sand 24 ounce

Stock Number: 100420 Revision Date: 06-20-2017 Replaces: 01-20-2017

Replaces: 01-20-2017				
	absorption hazard in normal industrial use.			
Inhalation Toxicity:	Upon prolonged and/or repeated exposure, can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache. Harmful! Can cause systemic damage (see "Target Organs)			
Eye Contact:	Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.			
Sensitization:	May cause an allergic skin reaction			
Mutagenicity:	No data			
Reproductive and Developmental Toxicity:	Classification has been based on toxicological information of the components in Section 3.			
Carcinogenicity:	The International Agency for Research on Cancer (IARC) has classified styrene as a group 2B carcinogen (possibly carcinogenic to humans).			
STOT-single exposure:	Classification has been based on toxicological information of the components in Section 3.			
STOT-repeated exposure:	Classification has been based on toxicological information of the components in Section 3.			
Aspiration hazard:	Classification has been based on toxicological information of the components in Section 3.			

Numerical measures of toxicity (such as acute toxicity estimates):

	<u> </u>	•	
Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Styrene	No data available	No data available	INHALATION LC50-4H Rat 11.7 MG/L
Titanium dioxide	ORAL LD50 Rat > 10000 mg/kg	No data available	No data available
Tetrahydrophthalic anhydride	ORAL LD50 Rat 5410 mg/kg	No data available	No data available
Silica, amorphous	No data available	DERMAL LD50 Rabbit > 2000 mg/kg	No data available

Is the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA:

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
Titanium dioxide	Y	Y	Ν
Talc	Ν	Y	Ν
Styrene	γ	Y	Y

12. Ecological information

Product identifier used on the label: Easy Sand 24 ounce

Stock Number: 100420 **Revision Date:** 06-20-2017

Replaces: 01-20-2017

Ecotoxicity (aquatic and terrestrial,
where available):Styrene is toxic to aquatic organisms and should not be released to
sewage, draining systems or any body of water exceeding concentrations
of approved limits under applicable regulations and permits.

Very toxic to aquatic life

Ecological Toxicity Data:

Chemical Name	CAS #	Aquatic EC50	Aquatic ERC50	Aquatic LC50 Fish
		Crustacea	Algae	
Styrene	100-42-5	48 HR EC50	96 HR EC50	96 HR LC50
		DAPHNIA MAGNA	PSEUDOKIRCHNERI	POECILIA
		3.3 - 7.4 MG/L	ELLA SUBCAPITATA	RETICULATA 58.75
			0.15 - 3.2 MG/L	- 95.32 MG/L
			[STATIC]	[STATIC]
			72 HR EC50	96 HR LC50
			PSEUDOKIRCHNERI	PIMEPHALES
			ELLA SUBCAPITATA	PROMELAS 6.75 -
			0.46 - 4.3 MG/L	14.5 MG/L [STATIC]
			[STATIC]	96 HR LC50
			96 HR EC50	LEPOMIS
			PSEUDOKIRCHNERI	MACROCHIRUS
			ELLA SUBCAPITATA	19.03 - 33.53 MG/L
			0.72 MG/L	[STATIC]
			72 HR EC50	96 HR LC50
			PSEUDOKIRCHNERI	PIMEPHALES
			ELLA SUBCAPITATA	PROMELAS 3.24 -
			1.4 MG/L	4.99 MG/L [FLOW-
				THROUGH]
Talc	14807-96-6	No data available	No data available	96 HR LC50
				BRACHYDANIO
				RERIO > 100 G/L
				[SEMI-STATIC]

Persistence and degradability: No

No data

Bioaccumulative potential: N

Mobility in soil:

No data available No data available No data available

Other adverse effects (such as hazardous to the ozone layer):

13. Disposal considerations

Description of waste residues and

Spent or discarded material is a hazardous waste.

Product identifier used on the label: Easy Sand 24 ounce Stock Number: 100420 Revision Date: 06-20-2017

Replaces: 01-20-2017

information on their safe handling and methods of disposal, including the disposal of any contaminated packaging:

Waste codes / waste designations: D001

14. Transport information

Carriage of dangerous goods by road (DO	T), rail or inland waterways:
UN number:	UN3269
UN Proper shipping name:	POLYESTER RESIN KIT
Transport hazard class(es):	3
Packing group, if applicable:	III
DOT Basic description:	No data available
International carriage of dangerous good	s by sea (IMDG/IMO):
UN number:	UN3269
UN Proper shipping name:	POLYESTER RESIN KIT
Transport hazard class(es):	3
Packing group, if applicable:	III
International carriage of dangerous good	s by air (IATA):
UN number:	UN3269
UN Proper shipping name:	POLYESTER RESIN KIT
Transport hazard class(es):	3
Packing group, if applicable:	III
Environmental hazards (e.g., Marine pollutant (Yes/No)):	Yes
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):	No data available
Special precautions which a user needs to be aware of or needs to comply with in connection with transport or conveyance either within or outside their premises:	No data available

15. Regulatory information

Safety, health and environmental regulations specific for the product in question:

Product identifier used on the label: Easy Sand 24 ounce

Stock Number: 100420 **Revision Date:** 06-20-2017

Replaces: 01-20-2017

TSCA Status:

The intentional ingredients of this product are listed. A component or components of this product are listed on the TSCA Inventory of Existing Chemical Substances.

Regulated Components:

Chemical Name	CAS #	CERCLA	Sara EHS	Sara 313	U.S. HAP
Polyester Resin	Proprietary	Ν	N	N	Ν
Styrene	100-42-5	Y	N	Y	Y
Talc	14807-96-6	Ν	N	N	Ν
Magnesite	546-93-0	Ν	N	N	Ν
Glass enamel	65997-17-3	Ν	Ν	N	N
Titanium dioxide	13463-67-7	Ν	N	N	Ν
Chlorite	1318-59-8	N	N	N	N
Dolomite	16389-88-1	N	N	N	Ν

Chemical Name	CAS #	California Prop 65 - Cancer	California Prop 65 - Dev. Toxicity	California Prop 65 - Reprod fem	California Prop 65 - Reprod male
Polyester Resin	Proprietary	N	N	N	Ν
Styrene	100-42-5	Y	N	N	Ν
Talc	14807-96-6	N	N	N	Ν
Magnesite	546-93-0	N	N	N	Ν
Glass enamel	65997-17-3	N	N	N	Ν
Titanium dioxide	13463-67-7	Y	N	N	Ν
Chlorite	1318-59-8	N	N	N	N
Dolomite	16389-88-1	N	N	N	Ν

Chemical Name	CAS #	Massachuset ts RTK List	New Jersey RTK List	Pennsylvani a RTK List	Rhode Island RTK List	Minnesota Hazardous Substance List
Polyester Resin	Proprietary	N	Ν	N	N	Ν
Styrene	100-42-5	N	Y	Y	N	Y
Talc	14807-96-6	N	Y	Y	N	Y
Magnesite	546-93-0	N	Ν	N	N	Y
Glass enamel	65997-17-3	N	Ν	N	N	Y
Titanium dioxide	13463-67-7	N	Y	Y	N	Y
Chlorite	1318-59-8	N	Ν	N	N	Ν
Dolomite	16389-88-1	N	Ν	N	N	Ν

Product identifier used on the label: Easy Sand 24 ounce Stock Number: 100420 Revision Date: 06-20-2017 Replaces: 01-20-2017

16. Other information, including da	te of preparation or last revision.
SDS Prepared by:	HAZOX
Revision Date:	06-20-2017
Revision Number:	15
Reason for revision: References:	Activated by Document Formulation Generation No data available
Disclaimer:	IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED, DATA OR INFORMATION SET FORTH. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DATA AND INFORMATION FURNISHED HEREUNDER ARE GIVEN GRATIS. NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DATA AND INFORMATION GIVEN ARE ASSUMED. ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.