1. Identification of the substance/mixture and of the company/undertaking

Product name	Centari® MasterTint® AM10 Fine Aluminium
Product code	1250091824

Intended use of the substance/preparation
Coating for professional use

Supplier	Axalta Coating Systems Australia Pty Limited
Street address	16 Darling Street, Marsden Park NSW 2765, Australia
Telephone	
Telefax	

Emergency Information

Emergency telephone number	+(64) 9801 0034 NZ Poisons Information Centre: 0800 764 766 or +(64) 3 479 7248
Importer	Resene Automotive & Light Industrial
Street/Box	4 Te Apunga Place, Mt Wellington, Auckland, NZ
Nat.-Code/Postal code/City	
Telephone	+64 (09) 259 2738
Date of preparation	2019-09-30

2. Hazards identification

Classified as a Dangerous Good according to NZS 5433
Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001

HSNO Classification

Flammable liquids	Category 3.1C
Acute inhalation toxicity	Category 6.1E
Skin corrosion/irritation	Category 6.3A
Serious eye damage/eye irritation	Category 6.4A
Skin sensitisation	Category 6.5B
Toxicity for reproduction	Category 6.8B
Target Organ Systemic Toxicant - Single exposure	Category 6.1E (respiratory tract irritant)
Target Organ Systemic Toxicant - Repeated exposure	Category 6.9B
Acute aquatic toxicity	Category 9.1D
Chronic aquatic toxicity	Category 9.1C
Ecotoxic to terrestrial invertebrates	Category 9.4C

Endpoints which are “not classified”, cannot be classified or are not applicable are not shown.

GHS-Labelling

Hazard symbols

Signal word: Warning

Hazard statements

Flammable liquid and vapour.
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May be harmful if inhaled.

© 2019 Axalta Coating Systems, LLC and all affiliates. All rights reserved.
Copies may be made only for those using Axalta Coating Systems products.

May cause respiratory irritation.
Suspected of damaging fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure.
Harmful to aquatic life.
Harmful to aquatic life with long lasting effects.

Precautionary statements

Obtain special instructions before use.
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Avoid release to the environment.
Wear protective gloves/protective clothing/eye protection/face protection.
IF exposed or concerned: Get medical advice/ attention.
If skin irritation or rash occurs: Get medical advice/ attention.
If eye irritation persists: Get medical advice/ attention.
Wash contaminated clothing before reuse.
Store in a well-ventilated place. Keep cool.

Other hazards which do not result in classification
Contains: methyl methacrylate; 2-hydroxyethyl acrylate. May produce an allergic reaction.

3. Composition/information on ingredients

Pure substance/mixture
Mixture

Hazardous components

CAS-No.	Chemical name	Concentration	GHS Hazardous
1330-20-7	xylene	20 - 30%	√
7429-90-5	aluminium powder (stabilized)	10 - 20%	√
123-86-4	n-butyl acetate	5 - 10%	√
100-41-4	ethylbenzene	5 - 10%	√
64742-95-6	solvent naphtha (petroleum), light arom. (<0,1% benzene)	3 - 5%	√
64742-48-9	Naphtha (petroleum), hydrotreated heavy (<0,1% benzene)	3 - 5%	√
123-92-2	isopentyl acetate	0.3 - 1.0%	√
80-62-6	methyl methacrylate	0.3 - 1.0%	√
107-21-1	ethanediol	0.1 - 0.3%	√
818-61-1	2-hydroxyethyl acrylate	0.1 - 0.3%	√
108-88-3	toluene	0.1 - 0.3%	√

Non-regulated ingredients 30 - 40%

4. First aid measures

Eye contact
Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

© 2019 Axalta Coating Systems, LLC and all affiliates. All rights reserved.
Copies may be made only for those using Axalta Coating Systems products.

Skin contact
Do NOT use solvents or thinners. Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

Inhalation
Avoid inhalation of vapour or mist. Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

Ingestion
If swallowed, seek medical advice immediately and show this safety data sheet (SDS) or product label. Do NOT induce vomiting. Keep at rest.

Most Important Symptoms/effects, acute and delayed

Inhalation
May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. If this product mixed with an isocyanate activator/hardener (see SDS for the activator), the following health effects may apply: Exposure to isocyanates may cause respiratory sensitization. This effect may be permanent. Symptoms include an asthma-like reaction with shortness of breath, wheezing, cough or permanent lung sensitization. This effect may be delayed for several hours after exposure. Repeated overexposure to isocyanates may cause a decrease in lung function, which may be permanent. Individuals with lung or breathing problems or prior reactions to isocyanates must not be exposed to vapors or spray mist of this product.

Ingestion
May result in gastrointestinal distress.

Skin or eye contact
May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis. If this product is mixed with an isocyanate, skin contact may cause sensitization.

Notes to physician
No data available on the product. See section 3 and 11 for hazardous ingredients found in the product.

5. Firefighting measures

Suitable extinguishing media
Universal aqueous film-forming foam, Carbon dioxide (CO2), Dry chemical, Water spray.

Extinguishing media which shall not be used for safety reasons
High volume water jet Water spray

Specific hazards
Flammable liquid and vapour. Vapours may form explosive mixtures with air. Remove all sources of ignition. Solvent vapours are heavier than air and may spread along floors. Do not allow run-off from fire fighting to enter drains or water courses. Never use pressure to empty container: container is not a pressure vessel. Always keep in containers of same material as the original one.

Special Protective Equipment and Fire Fighting Procedures
Wear as appropriate: Full protective flameproof clothing. Wear self-contained breathing apparatus for firefighting if necessary. In the event of fire, cool tanks with water spray.

6. Accidental release measures

Personal precautions
Keep in a well-ventilated place. Keep away from sources of ignition. Comply with safety directives (see chapters 7 and 8). Do not inhale vapours.

Environmental precautions
Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.

Methods for cleaning up

© 2019 Axalta Coating Systems, LLC and all affiliates. All rights reserved.
Copies may be made only for those using Axalta Coating Systems products.

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations. Clean preferably with a detergent; avoid use of solvents.

7. Handling and storage

Handling
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Safe handling advice
Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use grounded leads when transferring from one container to another.
Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid skin and eye contact. Do not breathe vapours or spray mist. Smoking, eating and drinking should be prohibited in the application area.

Storage

Suitable storage conditions
Observe label precautions. Refer to Technical Data Sheet (TDS) for further information about storage temperature. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Suitable container and packaging materials for safe storage
Always keep in containers made of the same material as the supply container.

8. Exposure controls/personal protection

National occupational exposure limits

Chemical name		
xylene	TWA	50 ppm
	TWA	217 mg/m3
aluminium powder (stabilized)	TWA	5 mg/m3
n-butyl acetate	TWA	150 ppm
	TWA	713 mg/m3
	STEL	200 ppm
	STEL	950 mg/m3
ethylbenzene	TWA	100 ppm
	TWA	434 mg/m3
	STEL	125 ppm
	STEL	543 mg/m3
isopentyl acetate	TWA	100 ppm
	TWA	532 mg/m3
methyl methacrylate	TWA	50 ppm
	TWA	208 mg/m3
	STEL	100 ppm
	STEL	416 mg/m3
ethanediol	CEIL	50 ppm
	CEIL	127 mg/m3
toluene	TWA	50 ppm
	TWA	188 mg/m3

© 2019 Axalta Coating Systems, LLC and all affiliates. All rights reserved.
Copies may be made only for those using Axalta Coating Systems products.

Engineering measures
Provide adequate ventilation.This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation.If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Glossary

CEIL	Ceiling exposure limit
STEL	Short term exposure limit
TWA	Time weighted average

Protective equipment
Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

Respiratory protection
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Eye protection
Use safety eyewear designed to protect against splash of products.

Hand protection
The breakthrough time of gloves is unknown for the product itself. The glove material given is recommended on basis of the substances in the preparation.

Chemical name	Glove material	Glove thickness	Break through time
xylene	Nitrile rubber	0.33 mm	30 MIN
	Viton (R) ®	0.7 mm	480 MIN
n-butyl acetate	Viton (R) ®	0.7 mm	10 MIN
	Nitrile rubber	0.33 mm	30 MIN
solvent naphtha (petroleum), light arom. (<0,1% benzene)	Viton (R) ®	0.7 mm	30 MIN

The protective glove should be checked in each case for their work specific suitability (e.g. mechanical stability, product compatibility, and anti-static properties). When the intended use is for spray application a nitrile glove of the chemical resistance group 3 (e.g. Dermatril® glove) is to be used. After contamination, the glove has to be changed. If immersing the hands into the product is not avoidable (e.g. maintenance work) a butyl or fluorocarbon rubber glove should be used. When skin exposure may occur to materials specified in section 3 of this SDS, advice should be sought from the glove supplier as to appropriate type to use with this product and the permeation breakthrough times. Care should be taken when working with sharp edged articles as these can easily damage the gloves and make them ineffective. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed. Damaged gloves or those showing signs of wear should be replaced immediately.

Skin and body protection
Wear suitable protective clothing. Personnel should wear antistatic clothing made of natural fiber or of high temperature resistant synthetic fiber.

Hygiene measures
Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use organic solvents!

9. Physical and chemical properties

Appearance

Form : liquid **Colour:** silver **Odour:** Characteristic Paint Odor **Odor Threshold :** No data available

pH	Not applicable	
Freezing point	-74 – 650 °C	
Boiling point	125 °C	
Flash point	29 °C	EN ISO 3679
Evaporation rate	Slower than Ether	
Flammability		
Upper explosion limit	7.5 %	
Lower explosion limit	1 %	

© 2019 Axalta Coating Systems, LLC and all affiliates. All rights reserved.
Copies may be made only for those using Axalta Coating Systems products.

Vapour pressure	5.0 hPa	
Solubility(ies)	partly miscible	
Vapour density	No data available	
Density	1.04 g/cm^3	DIN 53217/ISO 2811
Partition coefficient: n-octanol/water	No data available	
Ignition temperature	355 °C	DIN 51794
Decomposition temperature		
Viscosity (23 °C)	23 s	ISO 2431-1993 6 mm

10. Stability and reactivity

Stability

Stable

Hazardous polymerisation

Will not occur.

Conditions to avoid

Stable under recommended storage and handling conditions (see section 7).

Materials to avoid

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

11. Toxicological information

Information on likely routes of exposure

Inhalation
May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. If this product mixed with an isocyanate activator/hardener (see SDS for the activator), the following health effects may apply: Exposure to isocyanates may cause respiratory sensitization. This effect may be permanent. Symptoms include an asthma-like reaction with shortness of breath, wheezing, cough or permanent lung sensitization. This effect may be delayed for several hours after exposure. Repeated overexposure to isocyanates may cause a decrease in lung function, which may be permanent. Individuals with lung or breathing problems or prior reactions to isocyanates must not be exposed to vapors or spray mist of this product.

Ingestion
May result in gastrointestinal distress.

Skin or eye contact
May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

Delayed and immediate effects and also chronic effects from short and long term exposure:

Acute oral toxicity
not hazardous

Acute dermal toxicity
not hazardous

Acute inhalation toxicity

xylene	Category 4

© 2019 Axalta Coating Systems, LLC and all affiliates. All rights reserved.
Copies may be made only for those using Axalta Coating Systems products.

ethylbenzene Category 4

% of unknown composition: 0 %

Skin corrosion/irritation

xylene	Category 2
n-butyl acetate	Category 3
solvent naphtha (petroleum), light arom. (<0,1% benzene)	Category 3
Naphtha (petroleum), hydrotreated heavy (<0,1% benzene)	Category 3
isopentyl acetate	Category 3
methyl methacrylate	Category 2
2-hydroxyethyl acrylate	Category 1B
toluene	Category 2

Serious eye damage/eye irritation

xylene Category 2A

Respiratory sensitisation
Not classified according to GHS criteria

Skin sensitisation

methyl methacrylate	Category 1
2-hydroxyethyl acrylate	Category 1

Germ cell mutagenicity
Not classified according to GHS criteria

Carcinogenicity
Not classified according to GHS criteria

Toxicity for reproduction

toluene Category 2

Target Organ Systemic Toxicant - Single exposure

- **Inhalation**

  Narcotic effects toluene

Target Organ Systemic Toxicant - Repeated exposure
No data available.

Aspiration toxicity
Not classified according to GHS criteria

Numerical measures of toxicity (acute toxicity estimation (ATE),etc.)
No information available.

Symptoms related to the physical, chemical and toxicological characteristics
Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Through skin resorbtion, solvents can cause some of the effects described here. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

12. Ecological information

Product contains environmentally hazardous substances and product is not classified per GHS.

© 2019 Axalta Coating Systems, LLC and all affiliates. All rights reserved.
Copies may be made only for those using Axalta Coating Systems products.

Ecotoxicity effects
There are no data available on the product itself. The product should not be allowed to enter drains or watercourses.

Acute aquatic toxicity

n-butyl acetate	Category 3
ethylbenzene	Category 2
2-hydroxyethyl acrylate	Category 1

Chronic aquatic toxicity

ethylbenzene	Category 3
solvent naphtha (petroleum), light arom. (<0,1% benzene)	Category 2
2-hydroxyethyl acrylate	Category 3

% of unknown composition 0%

Persistence and degradability
No information available.

Bioaccumulation
No information available.

Mobility in soil
No information available.

Other adverse effects
No information available.

13. DISPOSAL CONSIDERATIONS

Waste disposal methods
Dispose of in accordance with local regulations.

Disposal considerations
A disposal process that converts the waste into energy is recommended. If this is not possible the hazardous waste must be disposed of by incineration.

14. Transport information

NZS5433

Proper shipping name:	PAINT
UN number:	1263
Hazard Class:	3
Packing group:	III
Hazchem Code:	3Y

IMDG (Sea transport)

Proper shipping name:	PAINT
UN number:	1263
Hazard Class:	3
Subsidiary Hazard Class:	Not applicable.
Packing group:	III
Marine Pollutant:	no
EmS:	F-E,S-E

ICAO/IATA (Air transport)

© 2019 Axalta Coating Systems, LLC and all affiliates. All rights reserved.
Copies may be made only for those using Axalta Coating Systems products.

Proper shipping name:	PAINT
UN number:	1263
Hazard Class:	3
Subsidiary Hazard Class:	Not applicable.
Packing group:	III

Matters needing attention for transportation
Confirm that there is no breakage, corrosion, or leakage from the container before shipping. Be sure to prevent damage to cargo by loading so as to avoid falling, dropping, or collapse. Ship in appropriate containers with denotation of the content in accordance with the relevant statutes and rules.

15. Regulatory information

National regulatory information

HSNO Approval Code	HSR002662
HSNO Classification	
Acute inhalation toxicity	Category 6.1E
Skin corrosion/irritation	Category 6.3A
Serious eye damage/eye irritation	Category 6.4A
Skin sensitisation	Category 6.5B
Toxicity for reproduction	Category 6.8B
Target Organ Systemic Toxicant - Single exposure	Category 6.1E (respiratory tract irritant)
Target Organ Systemic Toxicant - Repeated exposure	Category 6.9B
Flammable liquids	Category 3.1C
Acute aquatic toxicity	Category 9.1D
Chronic aquatic toxicity	Category 9.1C
Ecotoxic to terrestrial invertebrates	Category 9.4C

16. Other information

Revision Note

Version	Changes
14.0	8

Revision Date: 2019-08-03
B11935413

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The above information relates only to the specific material(s) designated herein and may not be valid for such material(s) used in combination with any other materials or in any process or if the material is altered or processed, unless specified in the text.

End of Safety Data Sheet

© 2019 Axalta Coating Systems, LLC and all affiliates. All rights reserved.
Copies may be made only for those using Axalta Coating Systems products.