

SAFETY DATA SHEET



Product name: 861-63 A5LT NI EPOXY PLUS ACCELERATOR

Product code: 9314042015368

Print Date: 2019-05-15

v8.0

Revision Date: 2019-05-15

NZ/en Page 1- 9

1. Identification of the substance/mixture and of the company/undertaking

Product name 861-63 A5LT NI EPOXY PLUS ACCELERATOR

Product code 9314042015368

Intended use of the substance/preparation

Thinner for professional use

Supplier

Street address

Telephone

Telefax

Axalta Coating Systems Australia Pty Limited

16 Darling Street, Marsden Park NSW 2765, Australia

Emergency Information

Emergency telephone number

+(64) 9801 0034

NZ Poisons Information Centre: 0800 764 766 or +(64) 3 479 7248

Importer

Resene Automotive & Light Industrial

Street/Box

4 Te Apunga Place, Mt Wellington, Auckland, NZ

Nat.-Code/Postal code/City

Telephone

+64 (09) 259 2738

Date of preparation

2019-05-15

2. Hazards identification

Classified as a Dangerous Good according to NZS 5433

Classified as hazardous according to criteria in the HS (Minimum Degrees of Hazard) Regulations 2001

HSNO Classification

Flammable liquids

Category 3.1C

Acute oral toxicity

Category 6.1E

Skin corrosion/irritation

Category 6.3A

Serious eye damage/eye irritation

Category 6.4A

Carcinogenicity

Category 6.7B

Target Organ Systemic Toxicant - Single exposure

Category 6.1E (respiratory tract irritant) + Category 6.9B (narcotic effects)

Aspiration toxicity

Category 6.1E

Acute aquatic toxicity

Category 9.1D

Chronic aquatic toxicity

Category 9.1B

Endpoints which are "not classified", cannot be classified or are not applicable are not shown.

GHS-Labeling

Hazard symbols



Signal word: Danger

Hazard statements

Flammable liquid and vapour.

May be harmful if swallowed.

May be fatal if swallowed and enters airways.

Causes skin irritation.

Causes serious eye irritation.

May cause respiratory irritation.

May cause drowsiness or dizziness.

Suspected of causing cancer.

Harmful to aquatic life.

SAFETY DATA SHEET



Product name: 861-63 A5LT NI EPOXY PLUS ACCELERATOR

Product code: 9314042015368

Print Date: 2019-05-15

v8.0

Revision Date: 2019-05-15

NZ/en Page 2- 9

Toxic to aquatic life with long lasting effects.

Precautionary statements

Obtain special instructions before use.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face protection.

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

Do NOT induce vomiting.

If eye irritation persists: Get medical advice/ attention.

Collect spillage.

Store in a well-ventilated place. Keep cool.

Other hazards which do not result in classification

None known.

3. Composition/information on ingredients

Pure substance/mixture

Mixture

Hazardous components

CAS-No.	Chemical name	Concentration	GHS Hazardous
108-65-6	2-methoxy-1-methylethyl acetate	20 - 30%	✓
95-63-6	1,2,4-trimethylbenzene	10 - 20%	✓
64742-95-6	solvent naphtha (petroleum), light arom. (<0,1% benzene)	10 - 20%	✓
763-69-9	ethyl 3-ethoxypropionate	10 - 20%	✓
112-07-2	2-butoxyethyl acetate	5 - 10%	✓
64742-94-5	Solvent naphtha (petroleum), heavy arom.	5 - 10%	✓
123-86-4	n-butyl acetate	5 - 10%	✓
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	3 - 5%	✓
108-67-8	mesitylene	1 - 3%	✓
103-65-1	n-propylbenzene	1 - 3%	✓
98-82-8	cumene	0.3 - 1.0%	✓
91-20-3	Naphthalene	0.3 - 1.0%	✓
1330-20-7	xylene	0.3 - 1.0%	✓

Non-regulated ingredients 0.1 - 1.0%

4. First aid measures

Eye contact

Remove contact lenses. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart. Seek medical advice.

Skin contact

SAFETY DATA SHEET



Product name: 861-63 A5LT NI EPOXY PLUS ACCELERATOR

Product code: 9314042015368

Print Date: 2019-05-15

v8.0

Revision Date: 2019-05-15

NZ/en Page 3- 9

Do NOT use solvents or thinners. Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. If skin irritation persists, call a physician.

Inhalation

Avoid inhalation of vapour or mist. Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.

Ingestion

If swallowed, seek medical advice immediately and show this safety data sheet (SDS) or product label. Do NOT induce vomiting. Keep at rest.

Most Important Symptoms/effects, acute and delayed

Inhalation

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Ingestion

May result in gastrointestinal distress.

Skin or eye contact

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

Notes to physician

No data available on the product. See section 3 and 11 for hazardous ingredients found in the product.

5. Firefighting measures

Suitable extinguishing media

Universal aqueous film-forming foam, Carbon dioxide (CO₂), Dry chemical, Water spray.

Extinguishing media which shall not be used for safety reasons

High volume water jet

Specific hazards

Flammable liquid and vapour. Vapours may form explosive mixtures with air. Remove all sources of ignition. Solvent vapours are heavier than air and may spread along floors. Do not allow run-off from fire fighting to enter drains or water courses. Never use pressure to empty container: container is not a pressure vessel. Always keep in containers of same material as the original one.

Special Protective Equipment and Fire Fighting Procedures

Wear as appropriate: Full protective flameproof clothing. Wear self-contained breathing apparatus for firefighting if necessary. In the event of fire, cool tanks with water spray.

6. Accidental release measures

Personal precautions

Keep in a well-ventilated place. Keep away from sources of ignition. Comply with safety directives (see chapters 7 and 8). Do not inhale vapours.

Environmental precautions

Do not let product enter drains. Notify the respective authorities in accordance with local law in the case of contamination of rivers, lakes or waste water systems.

Methods for cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations. Clean preferably with a detergent; avoid use of solvents.

7. Handling and storage

SAFETY DATA SHEET



Product name: 861-63 A5LT NI EPOXY PLUS ACCELERATOR

Product code: 9314042015368

Print Date: 2019-05-15

v8.0

Revision Date: 2019-05-15

NZ/en Page 4- 9

Safe handling advice

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Preparation may charge electrostatically: always use grounded leads when transferring from one container to another.

Operators should wear antistatic footwear and clothing. No sparking tools should be used. Avoid skin and eye contact. Do not breathe vapours or spray mist. Smoking, eating and drinking should be prohibited in the application area.

Storage

Suitable storage conditions

Observe label precautions. Refer to Technical Data Sheet (TDS) for further information about storage temperature. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Suitable container and packaging materials for safe storage

Always keep in containers made of the same material as the supply container.

8. Exposure controls/personal protection

National occupational exposure limits

Chemical name		
1,2,4-trimethylbenzene	TWA	25 ppm
	TWA	123 mg/m3
n-butyl acetate	TWA	150 ppm
	STEL	200 ppm
	STEL	950 mg/m3
	TWA	713 mg/m3
mesitylene	TWA	25 ppm
	TWA	25 ppm
	TWA	123 mg/m3
	TWA	123 mg/m3
cumene	TWA	25 ppm
	STEL	75 ppm
	STEL	375 mg/m3
	TWA	125 mg/m3
Naphthalene	TWA	10 ppm
	STEL	15 ppm
	STEL	79 mg/m3
	TWA	52 mg/m3
xylene	TWA	50 ppm
	TWA	217 mg/m3

Engineering measures

Provide adequate ventilation. This should be achieved by a good general extraction and -if practically feasible- by the use of a local exhaust ventilation. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

Glossary

CEIL Ceiling exposure limit

STEL Short term exposure limit

TWA Time weighted average

Protective equipment

Personal protective equipment should be worn to prevent contact with eyes, skin or clothing.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

SAFETY DATA SHEET



Product name: 861-63 A5LT NI EPOXY PLUS ACCELERATOR

Product code: 9314042015368

Print Date: 2019-05-15

v8.0

Revision Date: 2019-05-15

NZ/en Page 5- 9

Eye protection

Use safety eyewear designed to protect against splash of products.

Hand protection

The breakthrough time of gloves is unknown for the product itself. The glove material given is recommended on basis of the substances in the preparation.

Chemical name	Glove material	Glove thickness	Break through time
solvent naphtha (petroleum), light arom. (<0,1% benzene)	Viton (R) ®	0.7 mm	30 MIN
2-butoxyethyl acetate	Viton (R) ®	0.7 mm	480 m
	Nitrile rubber	0.33 mm	480 m
n-butyl acetate	Viton (R) ®	0.7 mm	10 MIN
	Nitrile rubber	0.33 mm	30 MIN
xylene	Nitrile rubber	0.33 mm	30 MIN
	Viton (R) ®	0.7 mm	480 MIN

The protective glove should be checked in each case for their work specific suitability (e.g. mechanical stability, product compatibility, and anti-static properties). When the intended use is for spray application a nitrile glove of the chemical resistance group 3 (e.g. Dermatrill® glove) is to be used. After contamination, the glove has to be changed. If immersing the hands into the product is not avoidable (e.g. maintenance work) a butyl or fluorocarbon rubber glove should be used. When skin exposure may occur to materials specified in section 3 of this SDS, advice should be sought from the glove supplier as to appropriate type to use with this product and the permeation breakthrough times. Care should be taken when working with sharp edged articles as these can easily damage the gloves and make them ineffective. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed. Damaged gloves or those showing signs of wear should be replaced immediately.

Skin and body protection

Wear suitable protective clothing. Personnel should wear antistatic clothing made of natural fiber or of high temperature resistant synthetic fiber.

Hygiene measures

Wash skin thoroughly with soap and water or use recognized skin cleanser. Do not use organic solvents!

9. Physical and chemical properties

Appearance

Form : liquid **Colour:** clear **Odor Threshold :** No data available

pH	No data available.	
Freezing point	-74 – -20 °C	
Boiling point	125 °C	
Flash point	24 °C	
Evaporation rate	Slower than Ether	
Flammability		
Upper explosion limit	9.8 %	
Lower explosion limit	0.6 %	
Vapour pressure	4.5 hPa	
Solubility(ies)	appreciable	
Vapour density	No data available	
Density	0.91 g/cm ³	DIN 53217/ISO 2811
Partition coefficient: n-octanol/water	No data available	
Ignition temperature	272 °C	DIN 51794
Decomposition temperature		
Viscosity (23 °C)	<20 s	ISO 2431-1993 6 mm

Product name: 861-63 A5LT NI EPOXY PLUS ACCELERATOR

Product code: 9314042015368

Print Date: 2019-05-15

v8.0

Revision Date: 2019-05-15

NZ/en Page 6- 9

10. Stability and reactivity

Stability

Stable

Hazardous polymerisation

Will not occur.

Conditions to avoid

Stable under recommended storage and handling conditions (see section 7).

Materials to avoid

Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

11. Toxicological information

Information on likely routes of exposure

Inhalation

May cause nose and throat irritation. May cause nervous system depression characterized by the following progressive steps: headache, dizziness, nausea, staggering gait, confusion, unconsciousness. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Ingestion

May result in gastrointestinal distress.

Skin or eye contact

May cause irritation or burning of the eyes. Repeated or prolonged liquid contact may cause skin irritation with discomfort and dermatitis.

Delayed and immediate effects and also chronic effects from short and long term exposure:

Acute oral toxicity

1,2,4-trimethylbenzene	Category 5
2-butoxyethyl acetate	Category 4
2,4,6-tris(dimethylaminomethyl)phenol	Category 4
cumene	Category 5
Naphthalene	Category 4
xylene	Category 5

Acute dermal toxicity

not hazardous

Acute inhalation toxicity

not hazardous

% of unknown composition: 0 %

Skin corrosion/irritation

1,2,4-trimethylbenzene	Category 2
solvent naphtha (petroleum), light arom. (<0,1% benzene)	Category 3
ethyl 3-ethoxypropionate	Category 3
Solvent naphtha (petroleum), heavy arom.	Category 3
n-butyl acetate	Category 3
2,4,6-tris(dimethylaminomethyl)phenol	Category 2
mesitylene	Category 2

SAFETY DATA SHEET



Product name: 861-63 A5LT NI EPOXY PLUS ACCELERATOR

Product code: 9314042015368

Print Date: 2019-05-15

v8.0

Revision Date: 2019-05-15

NZ/en Page 7- 9

xylene

Category 2

Serious eye damage/eye irritation

1,2,4-trimethylbenzene	Category 2A
2,4,6-tris(dimethylaminomethyl)phenol	Category 2A
mesitylene	Category 2A
xylene	Category 2A

Respiratory sensitisation

Not classified according to GHS criteria

Skin sensitisation

Not classified according to GHS criteria

Germ cell mutagenicity

Not classified according to GHS criteria

Carcinogenicity

Naphthalene Category 2

Toxicity for reproduction

Not classified according to GHS criteria

Target Organ Systemic Toxicant - Single exposure

• Inhalation

Narcotic effects Solvent naphtha (petroleum), heavy arom.

Respiratory system mesitylene

Target Organ Systemic Toxicant - Repeated exposure

Not classified according to GHS criteria

Aspiration toxicity

1,2,4-trimethylbenzene	Category 1
solvent naphtha (petroleum), light arom. (<0,1% benzene)	Category 1
Solvent naphtha (petroleum), heavy arom.	Category 1
mesitylene	Category 1
n-propylbenzene	Category 1
cumene	Category 1
xylene	Category 1

Numerical measures of toxicity (acute toxicity estimation (ATE),etc.)

No information available.

Symptoms related to the physical, chemical and toxicological characteristics

Exposure to component solvents vapours concentration in excess of the stated occupational exposure limit may result in adverse health effect such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Through skin resorbtion, solvents can cause some of the effects described here. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

12. Ecological information

Product contains environmentally hazardous substances and product is not classified per GHS.

Ecotoxicity effects

There are no data available on the product itself. The product should not be allowed to enter drains or watercourses.

SAFETY DATA SHEET



Product name: 861-63 A5LT NI EPOXY PLUS ACCELERATOR

Product code: 9314042015368

Print Date: 2019-05-15

v8.0

Revision Date: 2019-05-15

NZ/en Page 8- 9

Acute aquatic toxicity

1,2,4-trimethylbenzene	Category 2
ethyl 3-ethoxypropionate	Category 3
n-butyl acetate	Category 3
n-propylbenzene	Category 2
cumene	Category 2
Naphthalene	Category 1

Chronic aquatic toxicity

1,2,4-trimethylbenzene	Category 2
solvent naphtha (petroleum), light arom. (<0,1% benzene)	Category 2
Solvent naphtha (petroleum), heavy arom.	Category 2
mesitylene	Category 2
n-propylbenzene	Category 2
cumene	Category 2
Naphthalene	Category 1

% of unknown composition 0%

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility in soil

No information available.

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with local regulations.

Disposal considerations

A disposal process that converts the waste into energy is recommended. If this is not possible the hazardous waste must be disposed of by incineration.

14. Transport information

NZS5433

Proper shipping name: PAINT RELATED MATERIAL

UN number: 1263

Hazard Class: 3

Packing group: III

Hazchem Code: 3Y

IMDG (Sea transport)

Proper shipping name: PAINT RELATED MATERIAL

UN number: 1263

Hazard Class: 3

Subsidiary Hazard Class: Not applicable.

Packing group: III

SAFETY DATA SHEET



Product name: 861-63 A5LT NI EPOXY PLUS ACCELERATOR

Product code: 9314042015368

Print Date: 2019-05-15

v8.0

Revision Date: 2019-05-15

NZ/en Page 9- 9

Marine Pollutant: yes [solvent naphtha (petroleum), light arom. (<0,1% benzene)]
EmS: F-E,S-E

ICAO/IATA (Air transport)

Proper shipping name: PAINT RELATED MATERIAL

UN number: 1263
Hazard Class: 3
Subsidiary Hazard Class: Not applicable.
Packing group: III

Matters needing attention for transportation

Confirm that there is no breakage, corrosion, or leakage from the container before shipping. Be sure to prevent damage to cargo by loading so as to avoid falling, dropping, or collapse. Ship in appropriate containers with denotation of the content in accordance with the relevant statutes and rules.

15. Regulatory information

National regulatory information

HSNO Approval Code	HSR002669
HSNO Classification	
Acute oral toxicity	Category 6.1E
Skin corrosion/irritation	Category 6.3A
Serious eye damage/eye irritation	Category 6.4A
Carcinogenicity	Category 6.7B
Target Organ Systemic Toxicant - Single exposure	Category 6.1E (respiratory tract irritant) + Category 6.9B (narcotic effects)
Aspiration toxicity	Category 6.1E
Flammable liquids	Category 3.1C
Acute aquatic toxicity	Category 9.1D
Chronic aquatic toxicity	Category 9.1B

16. Other information

Revision Note

Version	Changes
8.0	2, 9, 11, 15

Revision Date: 2019-05-15
B12914812

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The above information relates only to the specific material(s) designated herein and may not be valid for such material(s) used in combination with any other materials or in any process or if the material is altered or processed, unless specified in the text.

End of Safety Data Sheet