

MATERIAL SAFETY DATA SHEET ADDENDUM

Page 0

N Z Specific Information addendum to Material Safety Data Sheet for Product No. **101156, 101156 Lite Weight** this must be read in conjunction with the MSDS from evercoat.com

Date Revised: 31/10/2019

SECTION 1 ADDITIONAL INFORMATION

NZ Supplier: Hindin Marquip Limited

Head Office: 1012 Great South Road, Penrose 1061

Phone: **09 579 9667**

EMERGENCY TELEPHONE 0800 POISON (0800 764 766)

SECTION 2 ADDITIONAL INFORMATION

This substance is hazardous according to the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001

HSNO CLASSIFICATION	HAZARD DESCRIPTION
3.1C	Flammable Liquid – medium hazard
6.1C	Substances that are acutely toxic -Toxic
6.3A	Substances that are irritating to the skin
6.4A	Substances that are irritating to the eye
6.6B	Substances that are suspected human mutagens
6.7B	Substances that are suspected human carcinogens
6.8B	Substances that are suspected or presumed human reproductive or developmental toxicants
6.9A	Substances that are toxic to human target organs or systems
9.1A	Substances that are very ecotoxic to the aquatic environment or are otherwise designed for biocidal
	action
9.3B	Substances that are ecotoxic to terrestrial vertebrates

PICTOGRAMS











SECTION 15

ADDITIONAL INFORMATION

EPA Approval: - HSR002665 - Surface Coatings and Colourants (Flammable, Toxic [6.1 + 6.7]) Group Standard 2006

SECTION 16

ADDITIONAL INFORMATION

Disclaimer

The modifications to this Safety Data Sheet made by M J Nankivell Haztec Ltd have been restricted to Adding New Zealand specific information only as required under the HSNO Act 1996 and associated regulations and no changes have been made to the Technical Content.

No Liability or responsibility shall be taken by M.J Nankivell Haztec Ltd for the technical content, or accidents or incidents arising from the use thereof.



 Stock Number:
 100156

 Revision Date:
 06-20-2017

 Replaces:
 10-12-2016

Replaces. 10-12-2

Light Weight

1. Identification

Product identifier used on the label: Light Weight Stock Number: 100156

Other means of identification:

Synonyms: None Known

Recommended use of the chemical and restrictions on use:

Recommended use: Lightweight body filler

Restrictions on use: Uses other than recommended use.

Name, address, and telephone number

of the chemical manufacturer,

ITW Evercoat

a division of Illinois Tool Works Inc.

importer, or other responsible party:

6600 Cornell Road Cincinnati, OH 45242

513-489-7600

Telephone number: CHEMTREC: 1-800-424-9300

CANUTEC: 1-613-996-6666

Emergency phone number: CHEMTREC: 1-800-424-9300 CANUTEC: 1-613-996-6666

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Hazard Symbols:





GHS Classification: Skin Sensitisation Category 1

Carcinogenicity Category 1B

Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category

1

Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure

Category 1

Aspiration Hazard Category 1

Skin Corrosion/Irritation Category 2

Serious Eye Damage/Eye Irritation Category 2A

Germ Cell Mutagenicity Category 2 Reproductive Toxicity Category 2

Hazardous to the aquatic environment - Acute Category 2

Product identifier used on the label: Light Weight

Stock Number: 100156 Revision Date: 06-20-2017 Replaces: 10-12-2016

Flammable Liquid Category 3

Signal Word: Danger

Hazard Statements: Flammable liquid and vapor.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye irritation.

Suspected of causing genetic defects.

May cause cancer.

Suspected of damaging fertility or the unborn child.

Causes damage to organs.

Causes damage to organs through prolonged or repeated exposure.

Toxic to aquatic life.

Precautionary Statements:

Prevention: Obtain special instructions before use.

Do not handle until all safety precautions have been read and

understood.

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash with soap and water thoroughly after handling. Do not eat, drink or smoke when using this product.

Contaminated work clothing must not be allowed out of the workplace.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face

protection.

Response: If swallowed: Immediately call a poison center/doctor.

IF ON SKIN: Wash with plenty of soap and water.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see Sections 4 to 8 on the SDS and any additional

information on the label). Do NOT induce vomiting.

If skin irritation or rash occurs: Get medical advice/attention.

Product identifier used on the label: Light Weight

Stock Number: 100156 **Revision Date:** 06-20-2017 **Replaces:** 10-12-2016

If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish.

Storage: Keep container tightly closed. Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal: Dispose of contents in accordance with your local disposal company

along with national/international regulations.

Hazards not otherwise classified: Reports have associated repeated and prolonged occupational

overexposure to solvents with permanent brain and nervous system

damage.

3. Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS#	%
Ethylene Glycol phenyl ether	None Known	122-99-6	0.1 - 1
Titanium dioxide	None Known	13463-67-7	0.1 - 1
Tetrahydrophthalic anhydride	None Known	85-43-8	0.1 - 1
Glass enamel	None Known	65997-17-3	1 - 5
Calcium carbonate	None Known	471-34-1	3 - 7
Styrene	None Known	100-42-5	10 - 30
Talc	None Known	14807-96-6	10 - 30

One or more hazardous ingredient(s) is claimed as a trade secret under the OSHA Hazard Communication Standard. The hazards of this (these) ingredient(s) are given on this SDS.

4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual

administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen. Get medical attention immediately If the victim has stopped breathing open airway, loosen collar and belt, and administer artificial respiration. Keep the victim warm and quiet.

Eye Contact: Flush eyes with plenty of water for at least 20 minutes retracting eyelids

often. Tilt the head to prevent chemical from transferring to the

uncontaminated eye. Get immediate medical attention.

Skin Contact: Wash with soap and water. Get medical attention if irritation develops or

persists. Wash clothing before reuse. Remove contaminated clothing

Product identifier used on the label: Light Weight

Stock Number: 100156 **Revision Date:** 06-20-2017 **Replaces:** 10-12-2016

and continue flushing with water.

Ingestion: Do not induce vomiting and seek medical attention immediately. Drink

two glasses of water or milk to dilute. Provide medical care provider with this SDS. If possible, do not leave individual unattended. If individual is drowsy or unconscious, do not give anything by mouth; place individual

on left side with head down.

Most important symptoms/effects, acute and delayed:

May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Causes damage to organs. Causes damage to organs through prolonged or

repeated exposure

Indication of immediate medical attention and special treatment needed, if necessary:

Specific treatment (see Sections 4 to 8 on the SDS and any additional

information on this label).

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing

agents. Water may be ineffective but water spray can be used extinguish a fire if swept across the base of the flames. Water can absorb heat and keep exposed material from being damaged by fire. Regular foam

Unsuitable extinguishing media: No data available

Specific hazards arising from the

chemical:

Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back.

Hazardous combustion products: Carbon dioxide, Carbon monoxide, Styrene oxide, Hydrocarbons

Special protective equipment and precautions for fire-fighters:

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Wear a self contained breathing apparatus (NIOSH approved) with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment. Water may be used to cool closed containers to prevent pressure build-up and possible auto

ignition or explosion when exposed to extreme heat.

6. Accidental release measures

Product identifier used on the label: Light Weight

Stock Number: 100156 Revision Date: 06-20-2017 Replaces: 10-12-2016

Personal precautions, protective equipment and emergency procedures:

No health affects expected from the clean-up of this material if contact can be avoided. Follow personal protective equipment recommendations

found in Section 8 of this SDS

Methods and materials for containment and cleaning up:

No special spill clean-up considerations. Collect and discard in regular trash. Use an inert absorbent such as sand or vermiculite. Place in properly labeled closed container. Avoid breathing vapors. All personnel in the area should be protected as in Section 8. Activate available exhaust ventilation equipment in the immediate spill area. Shut off ignition sources; including electrical equipment and flames. Do not allow smoking in the area.

7. Handling and storage

Precautions for safe handling:

Mildly irritating material. Avoid unnecessary exposure. Keep out of the reach of children. Keep container closed when not in use. Do not take internally. Avoid contact with material, avoid breathing dusts or fumes, use only in a well ventilated area. Use with adequate ventilation Wash hands before eating Do not get in eyes, on skin and clothing All hazard precautions given in the data sheet must be observed.

Conditions for safe storage, including any incompatibilities:

Safe storage conditions:

Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Avoid contact with incompatible materials. Store in a tightly closed container Keep away from heat, sparks, and flame For maximum product quality, avoid prolonged storage at temperatures above 75 °F (25 °C).

Materials to Avoid/Chemical Incompatibility:

Peroxides, Strong acids, Strong oxidizing agents, Polymerization catalysts

8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Talc	20 mppcf	2 mg/m3	No data available	1000 mg/m3 IDLH (containing no asbestos and <1% quartz)
Styrene	100 ppm	20 ppm	40 ppm STEL; 170 mg/m3 STEL	700 ppm IDLH

Product identifier used on the label: Light Weight

Stock Number: 100156 Revision Date: 06-20-2017 Replaces: 10-12-2016

Calcium carbonate	15 mg/m3 (total), 5 mg/m3 (respirable)	10 mg/m3	No data available	No data available
Glass enamel	5mg/m3	10mg/m3	No data available	No data available

Appropriate engineering controls: No exposure limits exist for the constituents of this product. Use local

exhaust ventilation or other engineering controls to minimize exposures

and maintain operator comfort.

Individual protection measures, such as personal protective equipment:

Respiratory Protection: Respiratory protection may be required to avoid overexposure when

handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in section 2.

Eye protection: Wear chemically resistant safety glasses with side shields when handling

this product. Do not wear contact lenses. Splash proof chemical goggles

are recommended to protect against the splash of product.

Skin protection: Not normally considered a skin hazard. Where use can result in skin

contact, practice good personal hygiene and wear a barrier cream and/or impervious surgical style gloves. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. To prevent repeated or prolonged skin contact, wear impervious clothing

and boots Gloves should be made of neoprene or natural rubber. Protective gloves and proper clothing should be worn to prevent skin

contact.

Gloves: Protective gloves are recommended when prolonged skin contact cannot

be avoided.

Other protective equipment: To prevent repeated or prolonged skin contact, wear impervious clothing

and boots Gloves should be made of neoprene or natural rubber. Protective gloves and proper clothing should be worn to prevent skin contact. Splash proof chemical goggles are recommended to protect

against the splash of product.

General hygiene conditions: Keep out of the reach of children. Keep container closed when not in use.

Do not take internally. Avoid contact with material, avoid breathing dusts

or fumes, use only in a well ventilated area. Use with adequate ventilation Wash hands before eating Do not get in eyes, on skin and clothing All hazard precautions given in the data sheet must be observed.

Page 6 of 13

Product identifier used on the label: Light Weight

Stock Number: 100156 Revision Date: 06-20-2017 Replaces: 10-12-2016

9. Physical and chemical properties

Appearance (physical state, color etc.):

Physical state: Paste
Color: Grey
Odor: Aromatic

Odor Threshold: No data available

pH: Neutral

Melting point/freezing point (°C):

Melting Point (°C):

No data available

Freezing point (°C):

No data available

145

6.1

1.1

Initial boiling point and boiling range

(°C):

Flash Point (°C): 35

Evaporation Rate: No data available Flammability (solid, gas): No data available

Upper/lower flammability or explosive

limits:

Upper flammability or explosive

limits:

i i

Lower flammability or explosive

limits:

Vapor pressure:No data available

Vapor density: Heavier than air. Vapors that evolve from this product will tend to settle

and accumulate near the floor.

Relative density: 1.25

Solubility(ies): Insoluble Partition coefficient: n-octanol/water: 1.36

Auto-ignition temperature (°C):No data availableDecomposition temperature (°C):No data availableViscosity:138,000 - 156,000

Volatile Organic Chemicals: 15 - 20%

VOC (as packaged-less exempts and

water):

1.46 lbs/gal or 175 g/L

VOC (as applied*- 2% by wt hardener-

less exempts and water):

0.4 lbs/gal or 48 g/L

Product identifier used on the label: Light Weight

Stock Number: 100156 Revision Date: 06-20-2017 Replaces: 10-12-2016

Percent Solids by weight – as packaged

(%):

Percent Solids by weight - as applied* -

2% by wt hardener (%):

VHAP Content by weight - as packaged

(%):

VHAP Content by weight – as applied* -

2% by weight hardener (%):

Bulk density: 10.4

10. Stability and reactivity

Reactivity:Not expected to be reactive

Chemical stability: Stable under normal handling conditions

85

96

15

4

Possibility of hazardous reactions: None expected under standard conditions of storage

Conditions to avoid (e.g., static

discharge, shock, or vibration):

Contamination

Incompatible materials: Peroxides, Strong acids, Strong oxidizing agents, Polymerization catalysts

Hazardous decomposition products: Carbon dioxide, Carbon monoxide, Styrene oxide, Hydrocarbons

11. Toxicological information

Description of the various toxicological (health) effects and the available data used to identify those effects:

Information on the likely routes of exposure (inhalation, ingestion, skin

and eye contact):

Absorption, Eye contact, Skin contact, Ingestion

Symptoms related to the physical,

chemical and toxicological

characteristics:

May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Causes damage to organs. Causes damage to organs through prolonged or

repeated exposure

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Ingestion Toxicity: Harmful if swallowed. May cause systemic poisoning.

Skin Contact: Can cause minor skin irritation, defatting, and dermatitis. Symptoms may

include redness, burning, drying and cracking of skin, and skin burns No

absorption hazard in normal industrial use.

Inhalation Toxicity: Upon prolonged and/or repeated exposure, can cause moderate

respiratory irritation, dizziness, weakness, fatigue, nausea and headache.

Product identifier used on the label: Light Weight

Stock Number: 100156 Revision Date: 06-20-2017 Replaces: 10-12-2016

Eye Contact: Can cause moderate irritation, tearing and reddening, but not likely to

permanently injure eye tissue.

Sensitization: May cause an allergic skin reaction

Mutagenicity: No data

Reproductive and Developmental

Toxicity:

Classification has been based on toxicological information of the

components in Section 3.

Carcinogenicity: The International Agency for Research on Cancer (IARC) has classified

styrene as a group 2B carcinogen (possibly carcinogenic to humans).

STOT-single exposure: Classification has been based on toxicological information of the

components in Section 3.

STOT-repeated exposure: Classification has been based on toxicological information of the

components in Section 3.

Aspiration hazard: Classification has been based on toxicological information of the

components in Section 3.

Numerical measures of toxicity (such as acute toxicity estimates):

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Styrene	No data available	No data available	INHALATION LC50-4H Rat 11.7 MG/L
Calcium carbonate	No data available	No data available	No data available
Tetrahydrophthalic anhydride	ORAL LD50 Rat 5410 mg/kg	No data available	No data available
Titanium dioxide	ORAL LD50 Rat > 10000 mg/kg	No data available	No data available
Ethylene Glycol phenyl ether	No data available	DERMAL LD50 Rabbit 5 ml/kg	No data available

Is the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA:

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
Styrene	Υ	Υ	Υ
Talc	N	Υ	N

12. Ecological information

Ecotoxicity (aquatic and terrestrial, where available):

Styrene is toxic to aquatic organisms and should not be released to sewage, draining systems or any body of water exceeding concentrations of approved limits under applicable regulations and permits.

of approved littles under applicable regulations and

Very toxic to aquatic life

Product identifier used on the label: Light Weight
Stock Number: 100156
Revision Date: 06-20-2017

Replaces: 10-12-2016

Ecological Toxicity Data:

Chemical Name	CAS#	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
Talc	14807-96-6	No data available	No data available	96 HR LC50
				BRACHYDANIO
				RERIO > 100 G/L
				[SEMI-STATIC]
Styrene	100-42-5	48 HR EC50	96 HR EC50	96 HR LC50
, and the second		DAPHNIA MAGNA	PSEUDOKIRCHNERI	POECILIA
		3.3 - 7.4 MG/L	ELLA SUBCAPITATA	RETICULATA 58.75
			0.15 - 3.2 MG/L	- 95.32 MG/L
			[STATIC]	[STATIC]
			72 HR EC50	96 HR LC50
			PSEUDOKIRCHNERI	PIMEPHALES
			ELLA SUBCAPITATA	PROMELAS 6.75 -
			0.46 - 4.3 MG/L	14.5 MG/L [STATIC]
			[STATIC]	96 HR LC50
			96 HR EC50	LEPOMIS
			PSEUDOKIRCHNERI	MACROCHIRUS
			ELLA SUBCAPITATA	19.03 - 33.53 MG/L
			0.72 MG/L	[STATIC]
			72 HR EC50	96 HR LC50
			PSEUDOKIRCHNERI	PIMEPHALES
			ELLA SUBCAPITATA	PROMELAS 3.24 -
			1.4 MG/L	4.99 MG/L [FLOW-
				THROUGH]

Persistence and degradability: No data

Bioaccumulative potential:No data availableMobility in soil:No data availableOther adverse effects (such asNo data available

hazardous to the ozone layer):

13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging:

Spent or discarded material is a hazardous waste.

Product identifier used on the label: Light Weight

Stock Number: 100156 **Revision Date:** 06-20-2017 **Replaces:** 10-12-2016

Waste codes / waste designations: D001

14. Transport information

Carriage of dangerous goods by road (DOT), rail or inland waterways:

UN number: UN3269

UN Proper shipping name: POLYESTER RESIN KIT

Transport hazard class(es): 3
Packing group, if applicable: |||

DOT Basic description:No data available

International carriage of dangerous goods by sea (IMDG/IMO):

UN number: UN3269

UN Proper shipping name: POLYESTER RESIN KIT

Transport hazard class(es): 3
Packing group, if applicable: |||

International carriage of dangerous goods by air (IATA):

UN number: UN3269

UN Proper shipping name: POLYESTER RESIN KIT

Transport hazard class(es): 3
Packing group, if applicable: |||

Environmental hazards (e.g., Marine

pollutant (Yes/No)):

Yes

Transport in bulk (according to Annex II

of MARPOL 73/78 and the IBC Code):

No data available

Special precautions which a user needs to be aware of or needs to comply with

to be aware of or needs to comply with in connection with transport or conveyance either within or outside

their premises:

No data available

15. Regulatory information

Safety, health and environmental regulations specific for the product in question:

TSCA Status: The intentional ingredients of this product are listed.

Regulated Components:

Product identifier used on the label: Light Weight

Stock Number: 100156 Revision Date: 06-20-2017 Replaces: 10-12-2016

Chemical Name	CAS#	CERCLA	Sara EHS	Sara 313	U.S. HAP
Polyester Resin	Proprietary	N	N	N	N
Talc	14807-96-6	N	N	N	N
Styrene	100-42-5	Υ	N	Υ	Υ
Magnesite	546-93-0	N	N	N	N
Calcium carbonate	471-34-1	N	N	N	N
Glass enamel	65997-17-3	N	N	N	N
Chlorite	1318-59-8	N	N	N	N
Dolomite	16389-88-1	N	N	N	N

Chemical Name	CAS#	California Prop 65 - Cancer	California Prop 65 - Dev. Toxicity	California Prop 65 - Reprod fem	California Prop 65 - Reprod male
Polyester Resin	Proprietary	N	N	N	N
Talc	14807-96-6	N	N	N	N
Styrene	100-42-5	Υ	N	N	N
Magnesite	546-93-0	N	N	N	N
Calcium carbonate	471-34-1	N	N	N	N
Glass enamel	65997-17-3	N	N	N	N
Chlorite	1318-59-8	N	N	N	N
Dolomite	16389-88-1	N	N	N	N

Chemical Name	CAS#	Massachuset ts RTK List	New Jersey RTK List	Pennsylvani a RTK List	Rhode Island RTK List	Minnesota Hazardous Substance List
Polyester Resin	Proprietary	N	N	N	N	N
Talc	14807-96-6	N	Υ	Υ	N	Υ
Styrene	100-42-5	N	Υ	Υ	N	Υ
Magnesite	546-93-0	N	N	N	N	Υ
Calcium carbonate	471-34-1	N	Υ	Υ	N	Υ
Glass enamel	65997-17-3	N	N	N	N	Y
Chlorite	1318-59-8	N	N	N	N	N
Dolomite	16389-88-1	N	N	N	N	N

16. Other information, including date of preparation or last revision.

SDS Prepared by: HAZOX

Product identifier used on the label: Light Weight

Stock Number: 100156 Revision Date: 06-20-2017 Replaces: 10-12-2016

Revision Date: 06-20-2017

Revision Number: 2

Reason for revision: Activated by Document Formulation Generation

References: No data available

Disclaimer: IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION

CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED,

INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE

REGARDING PRODUCTS DESCRIBED, DATA OR INFORMATION SET FORTH.

IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA

PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF

SALE. FURTHER, THE DESCRIPTIONS, DATA AND INFORMATION FURNISHED HEREUNDER ARE GIVEN GRATIS. NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DATA AND INFORMATION GIVEN ARE ASSUMED. ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.