

# **SAFETY DATA SHEET**

# Section 1. Identification of the material and the supplier

Product: Dinitrol 3650

Product Use: Anticorrosion additive Restriction of Use: Refer to Section 15

New Zealand Supplier: Auto Body Equipment

Address: 17 The Boulevard

Te Rapa, Hamilton, 3200

New Zealand

Telephone: +64 7 849 3514 Email: office@abe.co.nz

Emergency No: 0800 764 766 (National Poison Centre)

Date of SDS Preparation: 22 July 2019

### Section 2. Hazards Identification

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval No: Corrosive Inhibitor (Flammable) - HSR002548

## **Pictograms:**









Flammable

Irritant

Asp/ Chronic

Ecotoxic

Signal Word: DANGER

HSNO Classes	Hazard Code	Hazard Statement	GHS Category
3.1C	H226	Flammable liquid and vapour.	Flam. Liq. 3
6.1E (asp)	H304	May be fatal if swallowed and enters airways.	Asp. Tox. 1
6.3A	H315	Causes skin irritation.	Skin Irrit. 2
6.8B	H361	Suspected of damaging fertility or the unborn child.	Repr. 2
6.9N	H336	May cause drowsiness or dizziness.	STOT SE 3
9.1B	H411	Toxic to aquatic life with long lasting effects.	Aquatic Chronic 2

<b>Prevention Code</b>	Prevention Statement
P102	Keep out of reach of children.
P103	Read label before use.
P201	Obtain special instructions before use.
P210	Keep away from heat, sparks, open flames or hot surfaces. No smoking.

Product Name: Dinitrol 3650

Prepared by: Technical Compliance Consultants (NZ) Ltd
Date of SDS: 22 July 2019

Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: 64 9 475 5240 www.techcomp.co.nz

Page 1

P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating, lighting.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing fumes, vapours or spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective clothing as detailed in Section 8.
P281	Use personal protective equipment as required.

Response Code	Response Statement
P101	If medical advice is needed, have product container or label at hand.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P331	Do NOT induce vomiting.
P362	Take off contaminated clothing and wash before re-use.
P391	Collect spillage.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303 +	IF ON SKIN (or hair): Remove/Take off immediately all contaminated
P361+P353	clothing. Rinse skin with water/shower.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P332+ P313	If skin irritation occurs: Get medical advice/attention.
P370 + P378	In case of fire: Use CO2, powder or water spray for extinction.

Storage Code	Storage Statement
P405	Store locked up.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.

Disposal Code	Disposal Statement
P501	Dispose of according to Local Regulations or Authorities

# Section 3. Composition / Information on Hazardous Ingredients

Ingredients	Wt%	CAS NUMBER.
Naphtha (petroleum), hydrotreated heavy	50-<100	64742-48-9

C L! 4	
Section 4.	First Aid Measures

## Routes of Exposure:

If in Eyes Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get

medical advice.

If on Skin Remove/Take off immediately all contaminated clothing and wash before

re-use. Rinse skin with water/shower. If skin irritation or rash occurs: get

medical advice/attention.

If Swallowed Do NOT induce vomiting. Rinse mouth. Never give anything to the mouth

of an unconscious person. If vomiting occurs, place victim face

downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs. Call a POISON CENTER if unwell.

If Inhaled Remove person to fresh air. Remove contaminated clothing and loosen

remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Apply artificial

Product Name: Dinitrol 3650

Date of SDS: 22 July 2019

Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: 64 9 475 5240 www.techcomp.co.nz

respiration if not breathing. Get medical advice if breathing becomes difficult.

### Most important symptoms and effects, both acute and delayed

Symptoms: May cause drowsiness or dizziness.

Ingestion: Not applicable. Inhalation: Not applicable. Causes skin irritation. Skin:

Eve: Not applicable.

Chronic: Suspected of damaging fertility or the unborn child. May be fatal if

swallowed and enters airways.

#### Section 5. **Fire Fighting Measures**

Hazard Type	Flammable Liquid
Hazards from products	None known.
Suitable Extinguishing media	CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Do not use water with full jet.
Precautions for firefighters and special protective clothing	Wear a respiratory protective device. Cool containers with water spray.
HAZCHEM CODE	3Y

#### Section 6. **Accidental Release Measures**

Wear protective gear as detailed in Section 8. Evacuate all unnecessary personnel. Avoid contact with skin, eyes and clothes.

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Dispose of waste according to the applicable local regulations detailed in Section 13.

#### Section 7. **Handling and Storage**

# **Precautions for Handling:**

- Read label before use.
- Obtain special instructions before use.
- Prevent formation of aerosols
- Keep away from heat, sparks, open flames or hot surfaces. No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical, ventilating, lighting.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Avoid breathing fumes, vapours or spray.
- Wash hands thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Use only outdoors or in a well-ventilated area.
- Contaminated work clothing should not be allowed out of the workplace.
- · Avoid release to the environment.
- Wear protective clothing as detailed in Section 8.
- Use personal protective equipment as required.

### **Precautions for Storage:**

Product Name: Dinitrol 3650 Prepared by: Technical Compliance Consultants (NZ) Ltd Date of SDS: 22 July 2019

Tel: 64 9 475 5240 www.techcomp.co.nz

- Store away from incompatible materials listed in Section 10.
- Keep out of reach of children.
- Store locked up.
- Store in a well-ventilated place. Keep container tightly closed.
- Store in cool, dry conditions in well-sealed receptacles.

## Section 8 Exposure Controls / Personal Protection

# **WORKPLACE EXPOSURE STANDARDS (provided for guidance only)**

TWA STEL Substance ppm mg/m³ ppm mg/m³

No ingredients have exposure limits

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices NOV 2017 9TH EDITION.

$\cdot$ DNELs		
CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy		
Oral	Long-term - systemic effects, general population	125 mg/kg bw/day (General Population)
Dermal	Long-term - systemic effects, worker	208 mg/kg bw/day (Worker)
	Long-term - systemic effects, general population	125 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects, worker	871 mg/m3 (Worker)
	Long-term - systemic effects, general population	185 mg/m3 (General Population)

### **Engineering Controls**

Ensure there is adequate ventilation available.

### **Personal Protection Equipment**







Eyes	Tightly sealed goggles.
Skin	Wear solvent resistant gloves.
Respiratory	In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
General	Wash hands before breaks and at the end of work.

# Section 9 Physical and Chemical Properties

Form	Liquid
Colour	Transparent
Odour	Characteristic
Odour Threshold	Not available
pH @20°C	Not available
<b>Boiling Point</b>	145°C
Melting Point	Not available
Freezing Point	Not available
Flash Point	36 °C (DIN 53213)
Flammability	Flammable . Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
Upper and Lower	0.6 Vol% - 7.0 Vol %

Product Name: Dinitrol 3650

Prepared by: Technical Compliance Consultants (NZ) Ltd

Date of SDS: 22 July 2019 Tel: 64 9 475 5240 www.techcomp.co.nz

<b>Explosive Limits</b>	
Vapour Pressure @20°C	2.1 hPa
Density@ 20°C	0.82 g/cm <sup>3</sup> (DIN 51757)
Specific Gravity	Not available
Water Solubility	Not miscible or difficult to mix.
Partition Coefficient:	Not available
Ignition Temperature	>200°C
Decomposition	Not available
Temperature	
Kinematic Viscosity	15 s (DIN 53211/4)
@20°C	
<b>Particle Characteristics</b>	Not available
Solvent content	Organic Solvents: 57.0%
Solids content	43.0% (DIN 53216)

# Section 10. Stability and Reactivity

Stability of Substance	This product is stable under normal conditions.	
Possibility of hazardous	No dangerous reactions known.	
reactions		
Conditions to Avoid	Keep away from heat, sparks, open flames or hot surfaces. No smoking.	
Incompatible Materials	None known.	
Hazardous Decomposition Products	No dangerous decomposition products known.	

# Section 11 Toxicological Information

## **Acute Effects:**

Swallowed	Not applicable.
Dermal	Not applicable.
Inhalation	Not applicable.
Eye	Not applicable.
Skin	Causes skin irritation.

## **Chronic Effects:**

Carcinogenicity	Not applicable.	
Reproductive Toxicity	Suspected of damaging fertility or the unborn child.	
Germ Cell	Not applicable.	
Mutagenicity		
Aspiration	May be fatal if swallowed and enters airways.	
STOT/SE	Not applicable.	
STOT/RE	May cause drowsiness or dizziness.	

# **Acute Toxicity -**

Chemical Name	LD50 (Oral)	LD50 (Dermal)	LC50 (inhalation)
Product			
Naphtha (petroleum), hydrotreated heavy (Cas No 64742-48-9)	>5000mg/kg(Rat)	>5000mg/kg(Rabbit)	>4591 mg/l (Rat)- 4hrs

# Section 12. Ecotoxicological Information

Product Name: Dinitrol 3650

Prepared by: Technical Compliance Consultants (NZ) Ltd
Date of SDS: 22 July 2019

Prepared by: Technical Compliance Consultants (NZ) Ltd
Tel: 64 9 475 5240 www.techcomp.co.nz

HSNO Classes: 9.1B = Toxic to aquatic life with long lasting effects.

Persistence and degradability	No data available	
Bioaccumulation	No data available	
Mobility in Soil	No data available	
Other adverse effects	Hazardous for water. Do not allow undiluted product to	
	reach ground water, water course or sewage system.	

## **Section 13. Disposal Considerations**

### **Disposal Method:**

Spent media that has removed toxic chemicals should be examined for specific hazards. Spilled product may be recovered for use if it has not come in contact with liquids or been exposed to significant amounts of gaseous contaminants. Dispose of according to Local Regulations.

Ensure any container holding waste product or contaminated spill media is labelled "Hazardous Waste – "Spilled Flammable Liquid" and that the label also has the Flammable Pictogram, and the business name, address, and phone number.

**Precautions or methods to avoid:** Must not be disposed together with household garbage. Avoid release to the environment.

# Section 14 Transport Information

# This product is classified as a Dangerous Good for transport in NZ; NZS 5433:2012



### **Road and Rail Transport**

UN No: 1993 Class-primary 3 Packing Group III

Proper Shipping Name: FLAMMABLE LIQUIDS, N.O.S(Naphtha (petroleum),

hydrotreated heavy)

**Air Transport** 

UN No: 1993 Class-primary 3 Packing Group III

Proper Shipping Name: FLAMMABLE LIQUIDS, N.O.S(Naphtha (petroleum),

hydrotreated heavy)

**Marine Transport** 

UN No: 1993 Class-primary 3 Packing Group III

Proper Shipping Name: FLAMMABLE LIQUIDS, N.O.S(Naphtha (petroleum),

hydrotreated heavy)

#### **Limited Quantities Statement:**

If the product's individual container is below 5L, it can be transported as a non-DG as long as the product packaging is still labelled as per DG requirements and the driver is given safety information in accordance with Chapter 3.4 of the UNRTDG.

# Section 15 Regulatory Information

### **New Zealand:**

This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval Code: Corrosion Inhibitor (Flammable) - HSR002548

Product Name: Dinitrol 3650 Prepared by: Technical Compliance Consultants (NZ) Ltd

Date of SDS: 22 July 2019 Tel: 64 9 475 5240 www.techcomp.co.nz

HSNO Classification: 3.1C, 6.1E(Asp), 6.3A, 6.8B, 6.9N, 9.1B

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity
Certified Handler	Not required
Location Certificate	500L (>5L), 1500L(<5L), 250L open
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	1000L (3.1C, 9.1B)
Emergency Response Plan	1000L (9.1B)
Secondary Containment	1000L (9.1B)
Fire Extinguishers	500L - require 2X
Restriction of Use	Only use for the intended purpose.

#### Section 16 Other Information

Glossary

Median effective concentration.  $EC_{50}$ EEL Environmental Exposure Limit. **FPA Environmental Protection Authority** 

Hazardous Substances and New Organisms. **HSNO** 

**HSW** Health and Safety at Work.

Lethal concentration that will kill 50% of the test organisms  $LC_{50}$ 

inhaling or ingesting it.

 $LD_{50}$ Lethal dose to kill 50% of test animals/organisms.

LEL Lower explosive level.

American Occupational Safety and Health Administration. **OSHA** 

TEL Tolerable Exposure Limit.

**TLV** Threshold Limit Value-an exposure limit set by responsible

authority.

UEL Upper Explosive Level Workplace Exposure Limit WES

### References:

- EPA Hazardous Substances (Safety Data Sheets) Notice 2017 1.
- Workplace Exposure Standards and Biological Exposure Indices Nov 2017 edition. 2.
- 3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
- Transport of Dangerous goods on land NZS 5433:2012 4.
- 5. HSW (Hazardous Substances) Regulations 2017

#### Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-todate information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact Auto Body Equipment, if further information is required.

Issue Date: 22 July 2019 Review Date: 22 July 2024

Prepared by: Technical Compliance Consultants (NZ) Ltd Product Name: Dinitrol 3650 Date of SDS: 22 July 2019