

## SAFETY DATA SHEET

Section 1. Identification			
Product identifier	: 1250005333		
Product name	: 389S Imron Accelerator		
Other means of identification	: Not available.		
Date of issue	: 8/9/2022		
Version	: 1		
Relevant identified uses o	f the substance or mixture and uses advised against		
Identified uses	: Coating component.		
Uses advised against	: Not for sale to or use by consumers.		
Supplier's details: Axalta Coating Systems Australia Pty Limited 16 Darling Street, Marsden Park NSW 2765, Australia Importer: Resene Automotive & Light Industrial 4 Te Apunga Place, Mt Wellington, Auckland, New Zealand 			
Product information	: +61 (0)2 8818 4300		
Emergency telephone number	: +(64) 9801 0034 NZ Poisons Information Center: 0800 764 766 or +(64) 3 479 7248		

## Section 2. Hazards identification

This material is classified as hazardous according to criteria in the Hazardous Substances (Hazard Classification) Notice 2020.

This material is classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

HSNO Classification	<ul> <li>FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 EYE IRRITATION - Category 2 SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2 LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3</li> </ul>
GHS label elements	
Symbol	
Signal word	: Danger

### Section 2. Hazards identification

Hazard statements	<ul> <li>Flammable liquid and vapour.</li> <li>Toxic if swallowed, in contact with skin or if inhaled.</li> <li>Causes serious eye irritation.</li> <li>May cause damage to organs through prolonged or repeated exposure.</li> <li>Harmful to aquatic life with long lasting effects.</li> </ul>
Precautionary statements	
Prevention	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Do not breathe vapour. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wear protective gloves, protective clothing and eye or face protection.
Response	: IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF ON SKIN: Call a POISON CENTER or doctor if you feel unwell. Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not result in classification	: None known.

## Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	% (w/w)	CAS number
pentane-2,4-dione	>60	123-54-6
dibutyltin dilaurate	0.3 - <1	77-58-7

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### Description of necessary first aid measures

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

# Section 4. First aid measures

mouth with water. Remove dentures if any. If material has been exposed person is conscious, give small quantities of water to of exposed person feels sick as vomiting may be dangerous. Do unless directed to do so by medical personnel. If vomiting occu be kept low so that vomit does not enter the lungs. Never give an unconscious person. If unconscious, place in recovery positi		Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.			
Skin contact	:	Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. If necessary, call a poison center or physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.			
Most important symptoms/ef	fec	ts, acute and delayed			
Potential acute health effect	<u>ts</u>				
Inhalation	:	Toxic if inhaled.			
Ingestion	:	Toxic if swallowed.			
Skin contact	:	Toxic in contact with skin.			
Eye contact		Causes serious eye irritation.			
Over-exposure signs/sympt	ton	<u>15</u>			
Inhalation : No specific data.					
Ingestion : No specific data.		No specific data.			
Skin	:	No specific data.			
Eyes : Adverse symptoms may include the following: pain or irritation watering redness		pain or irritation watering			
Indication of immediate med	ica	l attention and special treatment needed, if necessary			
Specific treatments	:	Not available.			
Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.			
Protection of first-aiders	<ul> <li>Protection of first-aiders</li> <li>No action shall be taken involving any personal risk or without suitable training is suspected that fumes are still present, the rescuer should wear an approprimask or self-contained breathing apparatus. It may be dangerous to the persproviding aid to give mouth-to-mouth resuscitation. Wash contaminated cloth thoroughly with water before removing it, or wear gloves.</li> </ul>				
See toxicological information	า (ร	See toxicological information (Section 11)			

## Section 5. Firefighting measures

Extinguishing media			
Suitable	: Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.		
Not suitable	o not use water jet.		
Specific hazards arising from the chemical	: Flammable liquid and vapour. Runoff to sewer may create fire or explosion has In a fire or if heated, a pressure increase will occur and the container may burst the risk of a subsequent explosion. This material is harmful to aquatic life with lasting effects. Fire water contaminated with this material must be contained an prevented from being discharged to any waterway, sewer or drain.		
Hazardous thermal decomposition products	ecomposition products may include the following materials: arbon dioxide arbon monoxide		
Hazchem code	: 2Y		
Special precautions for fire- fighters	romptly isolate the scene by removing all persons from the vicinity of the inc nere is a fire. No action shall be taken involving any personal risk or without uitable training. Move containers from fire area if this can be done without ri lse water spray to keep fire-exposed containers cool.		
Special protective equipment for fire-fighters	ire-fighters should wear appropriate protective equipment and self-contained reathing apparatus (SCBA) with a full face-piece operated in positive pressu node.		
Remark	ot available.		

## Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	<ul> <li>If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".</li> </ul>		
Environmental precautions	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.		
Methods and material for co	ntainment and cleaning up		
Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.		
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.		

## Section 7. Handling and storage

Precautions for safe handling	Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

### **Control parameters**

### **Occupational exposure limits**

Ingredient name			Exposure limits	
pentane-2,4-dione dibutyltin dilaurate			ACGIH TLV (United States, 1/2021). Absorbed through skin. TWA: 25 ppm 8 hours. NZ HSWA 2015 - GRWM 2016 (New Zealand, 11/2020). Absorbed through skin. WES-TWA: 0.1 mg/m <sup>3</sup> , (as Sn) 8 hours. WES-STEL: 0.2 mg/m <sup>3</sup> , (as Sn) 15 minutes.	
Appropriate engineering controls	:	: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.		
Environmental exposure controls		Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.		
ndividual protection measures				
Hygiene measures	:	eating, smoking and using Appropriate techniques sh Wash contaminated cloth	nd face thoroughly after handling chemical products, before g the lavatory and at the end of the working period. hould be used to remove potentially contaminated clothing. ing before reusing. Ensure that eyewash stations and to the workstation location.	

# Section 8. Exposure controls/personal protection

Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Eye protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.
Skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## Section 9. Physical and chemical properties

### **Appearance**

Appearance		
Physical state	:	Liquid.
Colour	:	Clear.
Odour	:	Not available.
Odour threshold	:	Not available.
рН	:	Not applicable.
Melting point	:	Not applicable.
Boiling point	:	135 to 140°C (275 to 284°F)
Flash point	:	Closed cup: 24°C (75.2°F)
Fire point	:	Not available.
Evaporation rate	:	Not available.
Flammability (solid, gas)	:	Not available.
Lower and upper explosive (flammable) limits	:	Lower: 1.7% Upper: 11.6%
Vapour pressure	:	0.92 kPa (6.9 mm Hg)
Vapour density	:	Not available.
Density	:	0.976 g/cm³
Solubility	:	Soluble in the following materials: cold water.
Partition coefficient: n- octanol/water	:	Not applicable.
Auto-ignition temperature	:	340°C (644°F)
Decomposition temperature	:	Not applicable.

## Section 9. Physical and chemical properties

SADT	: Not available.
SAPT	: Not available.
Viscosity	: Not available.
Flow time (ISO 2431)	: Not available.

## Section 10. Stability and reactivity

Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: Reactive or incompatible with the following materials: oxidising materials
Hazardous decomposition products	<ul> <li>Under normal conditions of storage and use, hazardous decomposition products should not be produced.</li> </ul>

## Section 11. Toxicological information

### Information on likely routes of exposure

: Toxic if inhaled.
: Toxic if swallowed.
: Toxic in contact with skin.
: Causes serious eye irritation.
physical, chemical and toxicological characteristics
: No specific data.
: No specific data.
: No specific data.
: Adverse symptoms may include the following: pain or irritation watering redness

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
pentane-2,4-dione	LC50 Inhalation Vapour	Rat	5.1 mg/l	4 hours
	LD50 Dermal	Rabbit - Male	790 mg/kg	-
	LD50 Oral	Rat - Female	570 mg/kg	-
dibutyltin dilaurate	LD50 Oral	Rat - Male,	2071 mg/kg	-
-		Female		

Conclusion/Summary

: Not available.

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
pentane-2,4-dione	Skin - Mild irritant	Rabbit	-	488 mg	-
dibutyltin dilaurate	Eyes - Moderate irritant	Rabbit	-	24 hours 100	-
	Skin - Severe irritant	Rabbit	-	mg 500 mg	-
Skin	: Not available.				•
Eyes	: Not available.				
Respiratory	: Not available.				
Sensitisation					
Not available.					
Skin	: Not available.				
Respiratory	: Not available.				
Potential chronic health eff	fects				
General	: May cause damage to	organs through	prolonged o	r repeated expos	ure.
Inhalation	: No known significant e	ffects or critical	hazards.		
Ingestion	: No known significant e	ffects or critical	hazards.		
Skin contact	: No known significant e	ffects or critical	hazards.		
Eye contact	: No known significant e	ffects or critical	hazards.		
Carcinogenicity	: No known significant e	ffects or critical	hazards.		
Mutagenicity	: No known significant e	ffects or critical	hazards.		
Teratogenicity	: No known significant e	ffects or critical	hazards.		
Developmental effects	: No known significant e	ffects or critical	hazards.		
Fertility effects	: No known significant e	ffects or critical	hazards.		
Chronic toxicity					
Not available.					
Conclusion/Summary	: Not available.				
Carcinogenicity					
Not available.					
Conclusion/Summary	: Not available.				
<u>Iutagenicity</u>					
Not available.					
Conclusion/Summary	: Not available.				
<u>Feratogenicity</u>					
Not available.					
Conclusion/Summary	: Not available.				
Reproductive toxicity					
Not available.					

## Section 11. Toxicological information

## Section 11. Toxicological information

### Specific target organ toxicity

Name		Route of exposure	Target organs
•	Category 2 Category 1	-	-

### Aspiration hazard

Not available.

### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Oral	101.01 mg/kg
	797.98 mg/kg
Inhalation (vapours)	5.15 mg/l

Other information

: Not available.

## Section 12. Ecological information

Ecotoxicity

: This material is harmful to aquatic life with long lasting effects.

### Aquatic and terrestrial toxicity

Product/ingredient name	Result	Species	Exposure
pentane-2,4-dione	Acute EC50 75000 µg/l Fresh water	Crustaceans - Ceriodaphnia reticulata - Larvae	48 hours
	Acute LC50 47600 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 60100 µg/l Fresh water	Fish - Lepomis macrochirus	96 hours
dibutyltin dilaurate	Acute EC50 1 mg/l	Algae	72 hours
-	Acute EC50 463 µg/l	Daphnia	48 hours
	Acute LC50 3.1 mg/l	Fish	96 hours
	Chronic EC10 >2 mg/l Fresh water	Algae - Desmodesmus subspicatus	96 hours

**Conclusion/Summary** : Not available.

#### Persistence/degradability

pentane-2,4-dione OECD 301C >80 % - Readily - 28 days	Product/ingredient name	Test	Result	Dose	Inoculum
	pentane-2,4-dione	OECD 301C	>80 % - Readily - 28 days	-	-

Conclusion/Summary	: Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
pentane-2,4-dione	-	-	Readily

### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
pentane-2,4-dione	0.68	-	low
dibutyltin dilaurate	4.44	2.91	low

## Section 12. Ecological information

MODILITY IN SOIL	
Soil/water partition coefficient (K <sub>oc</sub> )	: Not available.
Mobility	: Not available.
Other adverse effects	: No known significant effects or critical hazards.

### Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

•				
	New Zealand Class (5433)	IMDG	ΙΑΤΑ	
UN number	UN2310	UN2310	UN2310	
UN proper shipping name		PENTANE-2,4-DIONE	Pentane-2,4-dione	
Transport hazard class(es)	3 (6.1)	3 (6.1)	3 (6.1)	
Packing group	111	Ш		
Environmental hazards	No.	No.	No.	
Additional information				

New Zealand	: <u>Hazchem code</u> 2Y
IMDG	: Emergency schedules F-E, S-D
ΙΑΤΑ	<ul> <li><u>Quantity limitation</u> Passenger and Cargo Aircraft: 60 L. Packaging instructions: 355. Cargo Aircraft Only: 220 L. Packaging instructions: 366. Limited Quantities - Passenger Aircraft: 2 L. Packaging instructions: Y343.</li> </ul>
Hazchem code	: •2Y

## Section 14. Transport information

Special precautions for user	: <b>Transport within user's premises:</b> always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do i the event of an accident or spillage.	
Transport in bulk according to IMO instruments	: Not available.	
	Proper shipping name	: Not available.
	Ship type	: Not available.
	Pollution category	: Not available.

The actual shipping description for this product may vary based several factors including, but not limited to, the volume of material, size of the container, mode of transport and use of exemptions or exceptions found in the applicable regulations. The information provided in Section 14 is one possible shipping description for this product. Consult your shipping specialist or supplier for appropriate assignment information.

## Section 15. Regulatory information

HSNO Approval Number	: HSR002667
HSNO Group Standard	: Surface Coatings and Colourants (Flammable, Acutely Toxic) Group Standard 2020
HSNO Classification	<ul> <li>FLAMMABLE LIQUIDS - Category 3         ACUTE TOXICITY (oral) - Category 3         ACUTE TOXICITY (dermal) - Category 3         ACUTE TOXICITY (inhalation) - Category 3         EYE IRRITATION - Category 2         SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2         LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3         </li> </ul>

## Section 16. Other information

<u>History</u>	
Date of issue	: 8/9/2022
Version	: 1
Prepared by	Product stewardship and regulatory compliance.
Key to abbreviations	<ul> <li>ACGIH = Association Advancing Occupational and Environmental Health ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals HSWA = Health and Safety at Work Act 2015 IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) TLV = Threshold Limit Value WES = Workplace Exposure Standards</li> </ul>
Indicates information f	that has changed from previously issued version.

### Indicates information that has changed from previously issued version.

#### Notice to reader

## Section 16. Other information

This product is intended for industrial use only.

Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

© 2018 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.