

SAFETY DATA SHEET

Section 1. Identi	fication
Product identifier	: 1250088675
Product name	: Syrox S801 Tint Violet Effect
Other means of identification	: Not available.
Date of issue	: 10/3/2022
Version	: 8
Relevant identified uses of	of the substance or mixture and uses advised against
Identified uses	: Coating component.
Uses advised against	: Not for sale to or use by consumers.
Supplier's details	 Axalta Coating Systems Australia Pty Limited 16 Darling Street, Marsden Park NSW 2765, Australia Importer: Resene Automotive & Light Industrial 4 Te Apunga Place, Mt Wellington, Auckland, New Zealand Telephone: +64 (09) 259 2738
Product information	: +61 (0)2 8818 4300
Emergency telephone number	: +(64) 9801 0034 NZ Poisons Information Center: 0800 764 766 or +(64) 3 479 7248

Section 2. Hazards identification

This material is classified as hazardous according to criteria in the Hazardous Substances (Hazard Classification) Notice 2020.

This material is not classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

HSNO Classification

: FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (oral) - Category 4

GHS label elements

Symbol

Signal word **Hazard statements**

- : Warning
- : Flammable liquid and vapour. Harmful if swallowed.

Precautionary statements

Section 2. Hazards identification

Prevention	:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wear protective gloves, protective clothing and eye or face protection.
Response	:	IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell. Rinse mouth. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not result in classification	:	None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture		
Ingredient name		% (w/w)	CAS number
1-pentanol 1-methoxy-2-propanol		5 - <10 1 - <3	71-41-0 107-98-2

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necess	ary first aid measures
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Section 4. First aid measures

Most important symptoms/effects, acute and delayed

Potential acute health effect	<u>ts</u>
Inhalation	: No known significant effects or critical hazards.
Ingestion	: Harmful if swallowed.
Skin contact	: No known significant effects or critical hazards.
Eye contact	: No known significant effects or critical hazards.
<u>Over-exposure signs/symp</u>	toms
Inhalation	: No specific data.
Ingestion	: No specific data.
Skin	: No specific data.
Eyes	: No specific data.
Indication of immediate med	ical attention and special treatment needed, if necessary
Specific treatments	: Not available.
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
See toxicological informatio	n (Section 11)

Section 5. Firefighting measures

-		
Extinguishing media		
Suitable	Jse dry chemical, CO ₂ , water spray (fog) or foam.	
Not suitable	Do not use water jet.	
Specific hazards arising from the chemical	Flammable liquid and vapour. Runoff to sewer may create fire or explosion haz n a fire or if heated, a pressure increase will occur and the container may burst he risk of a subsequent explosion.	
Hazardous thermal decomposition products	Decomposition products may include the following materials: carbon dioxide carbon monoxide netal oxide/oxides	
Hazchem code	Not available.	
Special precautions for fire- fighters	Promptly isolate the scene by removing all persons from the vicinity of the incide here is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk Jse water spray to keep fire-exposed containers cool.	
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained preathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.	;
Remark	Not available.	

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	 If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and material for co	ntainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling	Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
Conditions for safe storage, including any incompatibilities	Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits	
1-methoxy-2-propanol	NZ HSWA 2015 - GRWM 2016 (New Zealand, 11/20 WES-TWA: 100 ppm 8 hours. WES-TWA: 369 mg/m ³ 8 hours. WES-STEL: 553 mg/m ³ 15 minutes. WES-STEL: 150 ppm 15 minutes.	20).
Appropriate engineering controls	Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering contaiso need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.	
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensitive they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.	
Individual protection measu		
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, be eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated cloth Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.	
Respiratory protection	Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other import aspects of use.	
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard sho be worn at all times when handling chemical products if a risk assessment indicat this is necessary. Considering the parameters specified by the glove manufactur check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.	ates rer,
Eye protection	Safety eyewear complying with an approved standard should be used when a ris assessment indicates this is necessary to avoid exposure to liquid splashes, mis gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses w side-shields.	sts,
Skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should b approved by a specialist before handling this product.	е

Section 9. Physical and chemical properties

<u>Appearance</u>		
Physical state	iquid.	
Colour	Vhite.	
Odour	lot available.	
Odour threshold	lot available.	
рН	.5 to 8	
Melting point	lot applicable.	
Boiling point	00 to 139°C (212 to 282.2°F)	
Flash point	Closed cup: 60°C (140°F) [Product does not sustain comb	oustion.]
Fire point	lot available.	
Evaporation rate	lot available.	
Flammability (solid, gas)	lot available.	
Lower and upper explosive (flammable) limits	ower: 1.4% Ipper: 10%	
Vapour pressure	.3 kPa (17.4 mm Hg)	
Vapour density	lot available.	
Density	.047 g/cm ³	
Solubility	oluble in the following materials: cold water.	
Partition coefficient: n- octanol/water	lot applicable.	
Auto-ignition temperature	70°C (518°F)	
Decomposition temperature	lot applicable.	
SADT	lot available.	
SAPT	lot available.	
Viscosity)ynamic: 140 mPa·s (140 cP) íinematic: 134 mm²/s (134 cSt)	
Flow time (ISO 2431)	lot available.	

Section 10. Stability and reactivity

Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: Reactive or incompatible with the following materials: oxidising materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Inhalation	
IIIIalation	: No known significant effects or critical hazards.
Ingestion	: Harmful if swallowed.
Skin contact	: No known significant effects or critical hazards.
Eye contact	: No known significant effects or critical hazards.
Symptoms related to the p	hysical, chemical and toxicological characteristics
Inhalation	: No specific data.
Ingestion	: No specific data.
Skin contact	: No specific data.
Symptoms related to the p Inhalation	hysical, chemical and toxicological characteristics : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
1-methoxy-2-propanol	LD50 Dermal LD50 Oral		13 g/kg 6600 mg/kg	-

Conclusion/Summary : Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
1-pentanol	Eyes - Severe irritant	Rabbit	-	81 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 uL	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-
				mg	
	Skin - Severe irritant	Rabbit	-	24 hours	-
1 month and 0 minutes and	Obia Milel invite at	Dabbit		3200 mg	
1-methoxy-2-propanol	Skin - Mild irritant	Rabbit	-	500 mg	-
Skin	: Not available.				
Eyes	: Not available.				
Respiratory	: Not available.				
<u>Sensitisation</u>					
Not available.					
Skin	: Not available.				
Respiratory	: Not available.				
Potential chronic health eff	<u>ects</u>				
General	: No known significant effects or critical hazards.				
Inhalation	: No known significant effects or critical hazards.				
Ingestion	: No known significant effects or critical hazards.				
Skin contact	: No known significant effects or critical hazards.				
Eye contact	: No known significant effects or critical hazards.				
Carcinogenicity	: No known significant effects or critical hazards.				
Mutagenicity	: No known significant effects or critical hazards.				

Section 11. Toxicological information

	<u> </u>
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Chronic toxicity	
Not available.	
Conclusion/Summary	: Not available.
<u>Carcinogenicity</u>	
Not available.	
Conclusion/Summary	: Not available.
<u>Mutagenicity</u>	
Not available.	
Conclusion/Summary	: Not available.
<u>Teratogenicity</u>	
Not available.	
Conclusion/Summary	: Not available.
Reproductive toxicity	
Not available.	
Conclusion/Summary	· Not available
Specific target organ toxici	
Not available.	
Achiration bozard	
Aspiration hazard Not available.	
Numerical measures of tox	icity
Acute toxicity estimates	

Route	ATE value
Oral	1860.03 mg/kg
Dermal	20460.3 mg/kg
Inhalation (vapours)	204.6 mg/l
Other information (vapours)	204.0 mg/i

Section 12. Ecological information

Ecotoxicity

: No known significant effects or critical hazards.

Aquatic and terrestrial toxicity

Product/ingredient name	Result	Species	Exposure
1-pentanol	Acute EC50 714 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 180000 µg/l Marine water	Fish - Menidia beryllina	96 hours
1-methoxy-2-propanol	Acute LC50 >21100 mg/l	Daphnia	48 hours
	Acute LC50 ≥1000 mg/l	Fish	96 hours

Conclusion/Summary : Not available. Persistence/degradability Product/ingredient name Test Result Dose Inoculum OECD 301E 96 % - 28 days 1-methoxy-2-propanol **Conclusion/Summary** : Not available. Product/ingredient name Aquatic half-life Photolysis **Biodegradability** 1-methoxy-2-propanol Readily **Bioaccumulative potential** Product/ingredient name LogP_{ow} BCF Potential 1.51 low 1-pentanol 1-methoxy-2-propanol <1 low Mobility in soil Soil/water partition : Not available. coefficient (Koc) : Not available. Mobility Other adverse effects : No known significant effects or critical hazards. Section 13. Disposal considerations **Disposal methods** : The generation of waste should be avoided or minimised wherever possible.

Disposal methods Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

Section 12. Ecological information

	New Zealand Class (5433)	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-

Section 14. Transport information Transport hazard class(es) Packing group -_ Environmental No. No. No. hazards Hazchem code : Not available. Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. Transport in bulk according : Not available. to IMO instruments Proper shipping name : Not available. : Not available. Ship type Pollution category : Not available.

The actual shipping description for this product may vary based several factors including, but not limited to, the volume of material, size of the container, mode of transport and use of exemptions or exceptions found in the applicable regulations. The information provided in Section 14 is one possible shipping description for this product. Consult your shipping specialist or supplier for appropriate assignment information.

Section 15. Regulatory information

HSNO Approval Number	: HSR002662
HSNO Group Standard	: Surface Coatings and Colourants (Flammable) Group Standard 2020
HSNO Classification	: FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (oral) - Category 4

Section 16. Other information

<u>History</u>	
Date of issue	: 10/3/2022
Version	: 8
Prepared by	Product stewardship and regulatory compliance.
Key to abbreviations	: ACGIH = Association Advancing Occupational and Environmental Health ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals HSWA = Health and Safety at Work Act 2015 IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships,

Section 16. Other information

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) TLV = Threshold Limit Value

WES = Workplace Exposure Standards

Indicates information that has changed from previously issued version.

Notice to reader

This product is intended for industrial use only.

Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

© 2018 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.