

### SAFETY DATA SHEET

Section 1. Identification		
Product identifier	: 1250093917	
Product name	: Cromax Pro WB2010 Binder I	
Other means of identification	: Not available.	
Date of issue	: 8/10/2022	
Version	: 7.04	
Relevant identified uses of	of the substance or mixture and uses advised against	
Identified uses	: Coating component.	
Uses advised against	: Not for sale to or use by consumers.	
Supplier's details	<ul> <li>Axalta Coating Systems Australia Pty Limited</li> <li>16 Darling Street, Marsden Park NSW 2765, Australia</li> <li>Importer: Resene Automotive &amp; Light Industrial</li> <li>4 Te Apunga Place, Mt Wellington, Auckland, New Zealand</li> <li>Telephone: +64 (09) 259 2738</li> </ul>	
Product information	: +61 (0)2 8818 4300	
Emergency telephone number	: +(64) 9801 0034 NZ Poisons Information Center: 0800 764 766 or +(64) 3 479 7248	

### Section 2. Hazards identification

This material is classified as hazardous according to criteria in the Hazardous Substances (Hazard Classification) Notice 2020.

This material is not classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

HSNO Classification	: FLAMMABLE LIQUIDS ACUTE TOXICITY (ora
GHS label elements	
Symbol	
Signal word	: Warning
Hazard statements	: Combustible liquid. Harmful if swallowed.

**Precautionary statements** 

: FLAMMABLE LIQUIDS - Category 4 Y (oral) - Category 4

## Section 2. Hazards identification

Prevention	:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wear protective gloves, protective clothing and eye or face protection.
Response	:	IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell. Rinse mouth.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not result in classification	:	None known.

### Section 3. Composition/information on ingredients

Substance/mixture	: Mixture		
Ingredient name		% (w/w)	CAS number
1-pentanol acetone		5 - <10 1 - <3	71-41-0 67-64-1

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### **Description of necessary first aid measures**

Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

# Section 4. First aid measures

Most important symptoms/effects, acute and delayed		
Potential acute health effec	<u>ts</u>	
Inhalation	:	No known significant effects or critical hazards.
Ingestion	:	Harmful if swallowed.
Skin contact	:	No known significant effects or critical hazards.
Eye contact	:	No known significant effects or critical hazards.
Over-exposure signs/sympt	ton	<u>15</u>
Inhalation	:	No specific data.
Ingestion	:	No specific data.
Skin	:	No specific data.
Eyes	:	No specific data.
Indication of immediate medical attention and special treatment needed, if necessary		
Specific treatments	:	Not available.
Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
See toxicological information (Section 11)		

# Section 5. Firefighting measures

Extinguishing media	
Suitable	: Use dry chemical, CO <sub>2</sub> , water spray (fog) or foam.
Not suitable	: Do not use water jet.
Specific hazards arising from the chemical	: Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide
Hazchem code	: Not available.
Special precautions for fire- fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	<ul> <li>Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.</li> </ul>
Remark	: Not available.

# Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	<ul> <li>If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".</li> </ul>
Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and material for co	ntainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

Precautions for safe handling	Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous. Do not reuse container.
Conditions for safe storage, including any incompatibilities	Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

## Section 8. Exposure controls/personal protection

#### Control parameters

#### **Occupational exposure limits**

Ingredient name			Exposure limits
acetone			NZ HSWA 2015 - GRWM 2016 (New Zealand, 11/2020). WES-TWA: 500 ppm 8 hours. WES-TWA: 1185 mg/m <sup>3</sup> 8 hours. WES-STEL: 2375 mg/m <sup>3</sup> 15 minutes. WES-STEL: 1000 ppm 15 minutes.
Appropriate engineering controls	:	ventilation or other engine contaminants below any re	entilation. Use process enclosures, local exhaust ering controls to keep worker exposure to airborne ecommended or statutory limits. The engineering controls pour or dust concentrations below any lower explosive of ventilation equipment.
Environmental exposure controls	:	they comply with the requi cases, fume scrubbers, fil	n or work process equipment should be checked to ensure rements of environmental protection legislation. In some ters or engineering modifications to the process ary to reduce emissions to acceptable levels.
Individual protection measu	ires		
Hygiene measures	:	eating, smoking and using Appropriate techniques sh Wash contaminated clothi	In the face thoroughly after handling chemical products, before the lavatory and at the end of the working period. Hould be used to remove potentially contaminated clothing. Ing before reusing. Ensure that eyewash stations and to the workstation location.
Respiratory protection	:	appropriate standard or ce	potential for exposure, select a respirator that meets the ertification. Respirators must be used according to a gram to ensure proper fitting, training, and other important
Hand protection	:	be worn at all times when this is necessary. Conside check during use that the should be noted that the ti different for different glove	vious gloves complying with an approved standard should handling chemical products if a risk assessment indicates ering the parameters specified by the glove manufacturer, gloves are still retaining their protective properties. It me to breakthrough for any glove material may be a manufacturers. In the case of mixtures, consisting of rotection time of the gloves cannot be accurately
Eye protection	:	assessment indicates this gases or dusts. If contact	with an approved standard should be used when a risk is necessary to avoid exposure to liquid splashes, mists, is possible, the following protection should be worn, dicates a higher degree of protection: safety glasses with
Skin protection	:	selected based on the tas	any additional skin protection measures should be k being performed and the risks involved and should be efore handling this product.

## **Section 9. Physical and chemical properties**

AppearancePhysical state:lquid.Colour:Milky.Odour threshold:Not available.Odour threshold:Not available.pH::Not available.pIf::Not available.Boiling point::Not available.Flash point:::Flash point:::Flash point:::Socied cup: 69°C (156.2°F) [Product does not sustain combustion.]Fire point:::::Ramability (solid, gas)::::::Apour pressure::: <th></th> <th></th>		
Colour:Milky.Odour:Not available.Odour threshold:Not available.pH:7.5 to 9Melting point:Not applicable.Boiling point:100 to 139°C (212 to 282.2°F)Flash point:Closed cup: 69°C (156.2°F) [Product does not sustain combustion.]Fire point:Not available.Evaporation rate:Not available.Flammability (solid, gas):Not available.Lower and upper explosive (flammable) limits:Lower: 1.4% Upper: 10%Vapour pressure:2.5 kPa (18.9 mm Hg)Vapour density:Not available.Density:Soluble in the following materials: cold water.Partition coefficient: n- octanol/water:300°C (572°F)Pecomposition temperature:Not available.SADT:Not available.SAPT:Not available.Viscosity:Not available.Viscosity:Not available.	<u>Appearance</u>	
Odour:Nut available.Odour threshold:Not available.pH:7.5 to 9Melting point:Not applicable.Boiling point:100 to 139°C (212 to 282.2°F)Flash point:Closed cup: 69°C (156.2°F) [Product does not sustain combustion.]Fire point:Not available.Evaporation rate:Not available.Flammability (solid, gas):Not available.Lower and upper explosive:Lower: 1.4% Upper: 10%Vapour pressure:2.5 kPa (18.9 mm Hg)Vapour density:Not available.Density:Soluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not applicable.Auto-ignition temperature:300°C (572°F)Decomposition temperature:Not available.SADT:Not available.SAPT:Not available.Viscosity:Not available.Viscosity:Not available.	Physical state	: Liquid.
Odour threshold:Not available.pH:7.5 to 9Melting point:Not applicable.Boiling point:100 to 139°C (212 to 282.2°F)Flash point::Flash point:::Not available.Evaporation rate:Not available.Flammability (solid, gas):Not available.Lower and upper explosive:Lower: 1.4% Upper: 10%Vapour pressure:2.5 kPa (18.9 mm Hg)Vapour density:Not available.Density::Solubility:Soluble in the following materials: cold water.Partition coefficient: n- octanol/water::Auto-ignition temperature::SADT:Not available.SAPT:Not available.Viscosity:Not available.Viscosity:Not available.	Colour	: Milky.
pH:7.5 to 9Melting point:Not applicable.Boiling point:100 to 139°C (212 to 282.2°F)Flash point:Closed cup: 69°C (156.2°F) [Product does not sustain combustion.]Fire point:Not available.Evaporation rate:Not available.Flammability (solid, gas):Not available.Lower and upper explosive:Lower: 1.4% Upper: 10%Vapour pressure:2.5 kPa (18.9 mm Hg)Vapour density:Not available.Density:Soluble in the following materials: cold water.Partition coefficient: n- octanol/water:300°C (572°F)Decomposition temperature:300°C (572°F)Decomposition temperature:Not available.SADT:Not available.SAPT:Not available.Viscosity:Not available.	Odour	: Not available.
Melting point:Not applicable.Boiling point:100 to 139°C (212 to 282.2°F)Flash point:Closed cup: 69°C (156.2°F) [Product does not sustain combustion.]Fire point:Not available.Evaporation rate:Not available.Flammability (solid, gas):Not available.Lower and upper explosive (flammable) limits:Lower: 1.4% Upper: 10%Vapour pressure:2.5 kPa (18.9 mm Hg)Vapour density:Not available.Density:Soluble in the following materials: cold water.Partition coefficient: n- octanol/water:300°C (572°F)Decomposition temperature:300°C (572°F)Decomposition temperature:Not applicable.SADT:Not available.SAPT:Not available.Viscosity:Not available.	Odour threshold	: Not available.
Boiling point:100 to 139°C (212 to 282.2°F)Flash point:Closed cup: 69°C (156.2°F) [Product does not sustain combustion.]Fire point:Not available.Evaporation rate:Not available.Flammability (solid, gas):Not available.Lower and upper explosive (flammable) limits:Lower: 1.4% Upper: 10%Vapour pressure:2.5 kPa (18.9 mm Hg)Vapour density:Not available.Density:Soluble in the following materials: cold water.Solubility:Soluble in the following materials: cold water.Partition coefficient: n- octanol/water:300°C (572°F)Decomposition temperature:300°C (572°F)Decomposition temperature:Not available.SADT:Not available.SAPT:Not available.Viscosity:Not available.	рН	: 7.5 to 9
Flash point:Closed cup: 69°C (156.2°F) [Product does not sustain combustion.]Fire point:Not available.Evaporation rate:Not available.Flammability (solid, gas):Not available.Lower and upper explosive (flammable) limits:Lower: 1.4% Upper: 10%Vapour pressure:2.5 kPa (18.9 mm Hg)Vapour density:Not available.Density:Soluble in the following materials: cold water.Partition coefficient: n- octanol/water:300°C (572°F)Auto-ignition temperature::SADT:Not available.SAPT:Not available.Viscosity:Not available.	Melting point	: Not applicable.
Fire point:Not available.Evaporation rate:Not available.Flammability (solid, gas):Not available.Lower and upper explosive (flammable) limits:Lower: 1.4% Upper: 10%Vapour pressure:2.5 kPa (18.9 mm Hg)Vapour density:Not available.Density:1.013 g/cm³Solubility:Soluble in the following materials: cold water.Partition coefficient: n- octanol/water:300°C (572°F)Decomposition temperature SADT:Not available.SAPT:Not available.Viscosity:Not available.	Boiling point	: 100 to 139°C (212 to 282.2°F)
Evaporation rate:Not available.Flammability (solid, gas):Not available.Lower and upper explosive (flammable) limits:Lower: 1.4% Upper: 10%Vapour pressure:2.5 kPa (18.9 mm Hg)Vapour density:Not available.Density:Soluble in the following materials: cold water.Partition coefficient: n- octanol/water:Soluble in the following materials: cold water.Partition temperature octanol/water:300°C (572°F)Decomposition temperature SADT:Not available.SAPT:Not available.Viscosity:Not available.	Flash point	: Closed cup: 69°C (156.2°F) [Product does not sustain combustion.]
Flammability (solid, gas):Not available.Lower and upper explosive (flammable) limits:Lower: 1.4% Upper: 10%Vapour pressure:2.5 kPa (18.9 mm Hg)Vapour density:Not available.Density:Not available.Solubility:Soluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not applicable.Auto-ignition temperature SADT:300°C (572°F)Decomposition temperature SAPT:Not available.SAPT:Not available.Viscosity:Not available.	Fire point	: Not available.
Lower and upper explosive (flammable) limits: Lower: 1.4% Upper: 10%Vapour pressure: 2.5 kPa (18.9 mm Hg)Vapour density: Not available.Density: 1.013 g/cm³Solubility: Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not applicable.Auto-ignition temperature: 300°C (572°F)Decomposition temperature: Not applicable.SADT: Not available.SAPT: Not available.Viscosity: Not available.	Evaporation rate	: Not available.
(flammable) limitsUpper: 10%Vapour pressure:2.5 kPa (18.9 mm Hg)Vapour density:Not available.Density:1.013 g/cm³Solubility:Soluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not applicable.Auto-ignition temperature:300°C (572°F)Decomposition temperature:Not applicable.SADT:Not available.SAPT:Not available.Viscosity:Not available.	Flammability (solid, gas)	: Not available.
Vapour pressure:2.5 kPa (18.9 mm Hg)Vapour density:Not available.Density:1.013 g/cm³Solubility:Soluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not applicable.Auto-ignition temperature:300°C (572°F)Decomposition temperature:Not applicable.SADT:Not available.SAPT:Not available.Viscosity:Not available.		
Vapour density:Not available.Density:1.013 g/cm³Solubility:Soluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not applicable.Auto-ignition temperature:300°C (572°F)Decomposition temperature:Not applicable.SADT:Not available.SAPT:Not available.Viscosity:Not available.	· · · ·	
Density: 1.013 g/cm³Solubility: Soluble in the following materials: cold water.Partition coefficient: n- octanol/water: Not applicable.Auto-ignition temperature: 300°C (572°F)Decomposition temperature: Not applicable.SADT: Not available.SAPT: Not available.Viscosity: Not available.	• •	
Solubility:Soluble in the following materials: cold water.Partition coefficient: n- octanol/water:Not applicable.Auto-ignition temperature: $300^{\circ}C (572^{\circ}F)$ Decomposition temperature:Not applicable.SADT:Not available.SAPT:Not available.Viscosity:Not available.		
Partition coefficient: n- octanol/water: Not applicable.Auto-ignition temperature: 300°C (572°F)Decomposition temperature: Not applicable.SADT: Not available.SAPT: Not available.Viscosity: Not available.	•	
octanol/waterAuto-ignition temperature: 300°C (572°F)Decomposition temperature: Not applicable.SADT: Not available.SAPT: Not available.Viscosity: Not available.	•	
Decomposition temperature: Not applicable.SADT: Not available.SAPT: Not available.Viscosity: Not available.		
SADT: Not available.SAPT: Not available.Viscosity: Not available.	Auto-ignition temperature	: 300°C (572°F)
SAPT: Not available.Viscosity: Not available.	Decomposition temperature	: Not applicable.
Viscosity : Not available.	SADT	: Not available.
•	SAPT	: Not available.
Flow time (ISO 2431) : Not available.	Viscosity	: Not available.
	Flow time (ISO 2431)	: Not available.

# Section 10. Stability and reactivity

Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Incompatible materials	: Reactive or incompatible with the following materials: oxidising materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

Information on likely r	outes of exposure	
Inhalation	: No known significant effects or critical hazards.	
Ingestion	: Harmful if swallowed.	
Skin contact	: No known significant effects or critical hazards.	
Eye contact	: No known significant effects or critical hazards.	
Symptoms related to the physical, chemical and toxicological characteristics		
Inhalation	: No specific data.	
Ingestion	: No specific data.	
Skin contact	: No specific data.	
Eye contact	: No specific data.	

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
acetone	LC50 Inhalation Vapour LD50 Dermal LD50 Oral	Rabbit	21 mg/l 2001 mg/kg 5800 mg/kg	4 hours - -

**Conclusion/Summary** : Not available.

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
1-pentanol	Eyes - Severe irritant	Rabbit	-	81 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 uL	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-
				mg	
	Skin - Severe irritant	Rabbit	-	24 hours	-
				3200 mg	
acetone	Eyes - Mild irritant	Human	-	186300 ppm	-
	Eyes - Mild irritant	Rabbit	-	10 uL	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 20	-
				mg	
	Eyes - Severe irritant	Rabbit	-	20 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Skin - Mild irritant	Rabbit	-	395 mg	-
Skin	: Not available.				
Eyes	: Not available.				
Respiratory	: Not available.				
<u>Sensitisation</u>					
Not available.					
Skin	: Not available.				
Respiratory	: Not available.				
Potential chronic health eff	ects				
General	: No known significant ef	fects or critica	l hazards.		

# Section 11. Toxicological information

	5
Inhalation	No known significant effects or critical hazards.
Ingestion	No known significant effects or critical hazards.
Skin contact	No known significant effects or critical hazards.
Eye contact	No known significant effects or critical hazards.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.
Chronic toxicity	
Not available.	
Conclusion/Summary	Not available.
Carcinogenicity Not available.	
Conclusion/Summary	Not available.
<u>Mutagenicity</u> Not available.	
Conclusion/Summary	Not available.
<u>Teratogenicity</u> Not available.	
Conclusion/Summary	Not available.
Reproductive toxicity Not available.	
Conclusion/Summary	Not available.
Specific target organ toxic Not available.	
Aspiration hazard Not available.	
Numerical measures of to	<u>l</u>
Acute toxicity estimates	
Route	ATE value
Oral	1732.2 mg/kg

Other information

Inhalation (vapours)

Dermal

: Not available.

19054.22 mg/kg

190.54 mg/l

### Section 12. Ecological information

#### Ecotoxicity

: No known significant effects or critical hazards.

#### Aquatic and terrestrial toxicity

Product/ingredient name	Result	Species	Exposure
1-pentanol	Acute EC50 714 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
•	Acute LC50 180000 µg/l Marine water	Fish - Menidia beryllina	96 hours
acetone	Acute EC50 20.565 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute LC50 4.42589 ml/L Marine water	Crustaceans - Acartia tonsa - Copepodid	48 hours
	Acute LC50 10000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 5600 ppm Fresh water	Fish - Poecilia reticulata	96 hours
	Chronic NOEC 4.95 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 0.016 ml/L Fresh water	Crustaceans - Daphniidae	21 days
	Chronic NOEC 0.1 ml/L Fresh water	Daphnia - Daphnia magna - Neonate	21 days

**Conclusion/Summary** : Not available.

#### Persistence/degradability

Not available.

Mobility

#### **Conclusion/Summary** : Not available.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
1-pentanol acetone	1.51 -0.23	-	low low
Mobility in soil Soil/water partition coefficient (Koc)	: Not available.		

### : Not available.

**Other adverse effects** : No known significant effects or critical hazards.

### Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with
	thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

### Section 14. Transport information

New Zealand Class (5433)	IMDG	ΙΑΤΑ
Not regulated.	Not regulated.	Not regulated.
-	-	-
-	-	-
-	-	-
No.	No.	No.
	Not regulated.	Not regulated.     Not regulated.       -     -       -     -       -     -       -     -       -     -

**code** : Not available.

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according	:	Not available.
to IMO instruments		

Proper shipping name	: Not available.
Ship type	: Not available.
Pollution category	: Not available.

The actual shipping description for this product may vary based several factors including, but not limited to, the volume of material, size of the container, mode of transport and use of exemptions or exceptions found in the applicable regulations. The information provided in Section 14 is one possible shipping description for this product. Consult your shipping specialist or supplier for appropriate assignment information.

### Section 15. Regulatory information

HSNO Approval Number	: HSR002657
HSNO Group Standard	: Surface Coatings and Colourants (Combustible) Group Standard 2020
HSNO Classification	: FLAMMABLE LIQUIDS - Category 4 ACUTE TOXICITY (oral) - Category 4

### Section 16. Other information

#### <u>History</u>

Date of issue	: 8/10/2022
Version	: 7.04
Prepared by	: Product stewardship and regulatory compliance.

### Section 16. Other information

Key to abbreviations	: ACGIH = Association Advancing Occupational and Environmental Health
	ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	HSWA = Health and Safety at Work Act 2015
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships,
	1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	TLV = Threshold Limit Value
	WES = Workplace Exposure Standards

Indicates information that has changed from previously issued version.

#### Notice to reader

This product is intended for industrial use only.

Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

© 2018 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.