

SAFETY DATA SHEET

Section 1. Identification		
Product identifier	: 4024669502442	
Product name	: Standoblue MIX144 Midnight Blue	
Other means of identification	: Not available.	
Date of issue	: 8/10/2022	
Version	: 7	
Relevant identified uses of	of the substance or mixture and uses advised against	
Identified uses	: Coating component.	
Uses advised against	: Not for sale to or use by consumers.	
Supplier's details	 Axalta Coating Systems Australia Pty Limited 16 Darling Street, Marsden Park NSW 2765, Australia Importer: Resene Automotive & Light Industrial 4 Te Apunga Place, Mt Wellington, Auckland, New Zealand Telephone: +64 (09) 259 2738 	
Product information	: +61 (0)2 8818 4300	
Emergency telephone number	: +(64) 9801 0034 NZ Poisons Information Center: 0800 764 766 or +(64) 3 479 7248	

Section 2. Hazards identification

This material is classified as hazardous according to criteria in the Hazardous Substances (Hazard Classification) Notice 2020.

This material is not classified as DANGEROUS GOODS according to criteria in New Zealand Standard 5433:2012 Transport of Dangerous Goods on Land.

HSNO Classification

: FLAMMABLE LIQUIDS - Category 3 RESPIRATORY SENSITISATION - Category 1 REPRODUCTIVE TOXICITY - Category 2

<u>GHS label elements</u>

Symbol



: Danger

Signal word Hazard statements

: Flammable liquid and vapour. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of damaging fertility or the unborn child.

Precautionary statements

Section 2. Hazards identification

Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear respiratory protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing vapour. Wear protective gloves, protective clothing and eye or face protection.
Response	: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Other hazards which do not result in classification	: None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture		
Ingredient name	% (w/w)	CAS number
magnesium fluoride	3 - <5	7783-40-6
propan-1-ol	1 - <3	71-23-8
1-methoxy-2-propanol	1 - <3	107-98-2
1-pentanol	1 - <3	71-41-0
chromium	0.3 - <1	7440-47-3

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If necessary, call a poison center or physician. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In the event of any complaints or symptoms, avoid further exposure.
Ingestion	Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Section 4. First ai	d measures
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Most important symptoms/e	effects, acute and delayed
Potential acute health effe	<u>cts</u>
Inhalation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Ingestion	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Eye contact	: No known significant effects or critical hazards.
Over-exposure signs/symp	<u>otoms</u>
Inhalation	: Adverse symptoms may include the following: wheezing and breathing difficulties asthma reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
Skin	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
Eyes	: No specific data.
Indication of immediate me	dical attention and special treatment needed, if necessary
Specific treatments	: Not available.
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
• • • • • • • •	

See toxicological information (Section 11)

Section 5. Firefighting measures

Extinguishing media	
Suitable	: Use dry chemical, CO ₂ , water spray (fog) or foam.
Not suitable	: Do not use water jet.
Specific hazards arising from the chemical	: Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion.

Section 5. Firefighting measures

Hazardous thermal decomposition products	:	Decomposition products may include the following materials: carbon dioxide carbon monoxide halogenated compounds metal oxide/oxides
Hazchem code	:	Not available.
Special precautions for fire- fighters	:	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Remark	:	Not available.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and material for co	ntainment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spill product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

 Precautions for safe handling Put on appropriate personal protective equipment (see Section 8). Persons history of asthma, allergies or chronic or recurrent respiratory disease shou employed in any process in which this product is used. Avoid exposure - ot special instructions before use. Avoid exposure during pregnancy. Do not until all safety precautions have been read and understood. Do not get in e skin or clothing. Do not ingest. Avoid breathing vapour or mist. Use only wadequate ventilation. Wear appropriate respirator when ventilation is inader Do not enter storage areas and confined spaces unless adequately ventilated Keep in the original container or an approved alternative made from a composite or an approved alte	ld not be otain handle yes or on vith quate. ed.
--	--

Section 7. Handling and storage

material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container. Conditions for safe storage, Store between the following temperatures: 5 to 35°C (41 to 95°F). Store in : including any accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated incompatibilities area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name		Exposure limits
propan-1-ol 1-methoxy-2-propanol		NZ HSWA 2015 - GRWM 2016 (New Zealand, 11/2020). Absorbed through skin. WES-TWA: 200 ppm 8 hours. WES-TWA: 492 mg/m ³ 8 hours. WES-STEL: 614 mg/m ³ 15 minutes. WES-STEL: 250 ppm 15 minutes. NZ HSWA 2015 - GRWM 2016 (New Zealand, 11/2020). WES-TWA: 100 ppm 8 hours. WES-TWA: 369 mg/m ³ 8 hours. WES-STEL: 553 mg/m ³ 15 minutes. WES-STEL: 150 ppm 15 minutes.
Appropriate engineering controls	ventilation or other engin contaminants below any	entilation. Use process enclosures, local exhaust eering controls to keep worker exposure to airborne recommended or statutory limits. The engineering controls apour or dust concentrations below any lower explosive of ventilation equipment.
Environmental exposure controls	they comply with the requ cases, fume scrubbers, f	n or work process equipment should be checked to ensure lirements of environmental protection legislation. In some liters or engineering modifications to the process ary to reduce emissions to acceptable levels.
ndividual protection measures		
Hygiene measures	eating, smoking and usin Appropriate techniques s Wash contaminated cloth	nd face thoroughly after handling chemical products, before g the lavatory and at the end of the working period. hould be used to remove potentially contaminated clothing. hing before reusing. Ensure that eyewash stations and to the workstation location.

Section 8. Exposure controls/personal protection

Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Eye protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Section 9. Physical and chemical properties

Appearance

Appearance	
Physical state	: Liquid.
Colour	: Blue.
Odour	: Not available.
Odour threshold	: Not available.
рН	: 7.5 to 9
Melting point	: Not applicable.
Boiling point	: 100 to 100.1°C (212 to 212.2°F)
Flash point	: Closed cup: 56°C (132.8°F) [Product does not sustain combustion.]
Fire point	: Not available.
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Not available.
Vapour pressure	: 2.6 kPa (19.6 mm Hg)
Vapour density	: Not available.
Density	: 1.028 g/cm ³
Solubility	: Soluble in the following materials: cold water.
Partition coefficient: n- octanol/water	: Not applicable.
Auto-ignition temperature	: 270°C (518°F)
Decomposition temperature	: Not applicable.

Section 9. Physical and chemical properties

SADT	: Not available.
SAPT	: Not available.
Viscosity	: Not available.
Flow time (ISO 2431)	: Not available.

Section 10. Stability and reactivity

: The product is stable.
: Under normal conditions of storage and use, hazardous reactions will not occur.
: Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
: Reactive or incompatible with the following materials: oxidising materials
: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on likely ro	outes of exposure
Inhalation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Ingestion	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Eye contact	: No known significant effects or critical hazards.
Symptoms related to the	ne physical, chemical and toxicological characteristics
Inhalation	: Adverse symptoms may include the following: wheezing and breathing difficulties asthma reduced foetal weight increase in foetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: reduced foetal weight increase in foetal deaths skeletal malformations
Eye contact	: No specific data.
Delayed and immediate	effects as well as chronic effects from short and long-term exposure
Acute toxicity	

Acute toxicity

Section 11. Toxicological information

	•			
Product/ingredient name	Result	Species	Dose	Exposure
magnesium fluoride	LD50 Oral	Rat	2330 mg/kg	-
propan-1-ol	LD50 Dermal	Rabbit	5040 mg/kg	-
	LD50 Oral	Rat	2200 mg/kg	-
1-methoxy-2-propanol	LD50 Dermal	Rabbit	13 g/kg	-
	LD50 Oral	Rat	6600 mg/kg	-

Conclusion/Summary : Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation		
propan-1-ol	Eyes - Moderate irritant	Rabbit	-	24 hours 20	-		
				mg			
	Skin - Mild irritant	Human	-	47 hours 100	-		
	Skin - Mild irritant	Human		% 24 hours 100			
	Skill - Mild Initalit	Tuman	-	%	-		
	Skin - Mild irritant	Rabbit	-	500 mg	_		
1-methoxy-2-propanol	Skin - Mild irritant	Rabbit	-	500 mg	-		
1-pentanol	Eyes - Severe irritant	Rabbit	-	81 mg	-		
	Eyes - Severe irritant	Rabbit	-	24 hours 5 uL	-		
	Skin - Moderate irritant	Rabbit	-	24 hours 20	-		
	Skip Sovere irritent	Pabbit		mg 24 bours			
	Skin - Severe irritant	Rabbit	-	24 hours 3200 mg	-		
				5200 mg			
Skin	: Not available.						
Eyes	: Not available.						
Respiratory	: Not available.						
<u>Sensitisation</u>							
Not available.							
Skin	: Not available.						
Respiratory	: Not available.						
Potential chronic health eff	<u>iects</u>						
General	: Once sensitized, a sevent	ere allergic rea	ction may oc	cur when subsequ	uently exposed		
	to very low levels.	-	•				
Inhalation	: Once sensitized, a seve	ere allergic rea	ction may oc	cur when subsequ	uently exposed		
	to very low levels.	-	-				
Ingestion	: No known significant ef	ffects or critica	l hazards.				
Skin contact	: No known significant et	ffects or critica	l hazards.				
Eye contact	: No known significant et	ffects or critica	l hazards.				
Carcinogenicity	: No known significant el						
Mutagenicity	: No known significant el	fects or critica	l hazards.				
Teratogenicity	: Suspected of damaging						
Developmental effects	: No known significant effects or critical hazards.						
Fertility effects	: Suspected of damaging fertility.						
i oranity eneolo	· Cuspected of damaging fermity.						

4024669502442

Section 11. Toxicological information

		•
Chronic toxicity Not available.		
Conclusion/Summary Carcinogenicity Not available.	:	Not available.
Conclusion/Summary <u>Mutagenicity</u> Not available.	:	Not available.
Conclusion/Summary <u>Teratogenicity</u> Not available.	:	Not available.
Conclusion/Summary <u>Reproductive toxicity</u> Not available.	:	Not available.
Conclusion/Summary Specific target organ toxicity Not available.	-	Not available.

Aspiration hazard

Not available.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Dermal	4273.5 mg/kg 57894.74 mg/kg 578.95 mg/l

Other information

: Not available.

Section 12. Ecological information

Ecotoxicity

: No known significant effects or critical hazards.

Aquatic and terrestrial toxicity

Product/ingredient name	Result	Species	Exposure
propan-1-ol	Acute EC50 4480000 µg/l Fresh water	Algae - Selenastrum sp.	96 hours
	Acute LC50 1000000 µg/l Fresh water	Crustaceans - Gammarus pulex	48 hours
	Acute LC50 2950000 µg/l Fresh water	Daphnia - Daphnia pulex	48 hours
	Acute LC50 3800000 µg/l Marine water	Fish - Alburnus alburnus	96 hours
1-methoxy-2-propanol	Acute LC50 >21100 mg/l	Daphnia	48 hours
	Acute LC50 ≥1000 mg/l	Fish	96 hours
1-pentanol	Acute EC50 714 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
-	Acute LC50 180000 µg/l Marine water	Fish - Menidia beryllina	96 hours

gical infor	mation					
: Not available	Э.					
Test	Result			Dose		Inoculum
OECD 301E	96 % - 28 0	days		-		-
: Not available	Э.			1		1
Aquatic half-lif	e		Photolysi	S		Biodegradability
-			-			Readily
						1
LogPow		BCF			Poter	itial
0.2		-			low	
<1		-			low	
1.51		-			IOW	
: Not available	Э.					
: Not available	Э.					
: No known si	gnificant effec	ts or criti	cal hazards			
sal consid	lerations	;				
	 Not available Test OECD 301E Not available Aquatic half-lift - LogPow 0.2 1.51 Not available Not available Not available Not available No known si 	OECD 301E 96 % - 28 d : Not available. Aquatic half-life - LogPow 0.2 <1	: Not available. Result OECD 301E 96 % - 28 days OECD 301E 96 % - 28 days i Not available. Aquatic half-life - BCF 0.2 - <1	 Not available. Test Result OECD 301E 96 % - 28 days Not available. Aquatic half-life Photolysi - LogPow BCF 0.2 <1 1.51 - Not available. Not available. No known significant effects or critical hazards 	Test Result Dose OECD 301E 96 % - 28 days - : Not available. - - Aquatic half-life Photolysis - - LogPow BCF 0.2 - <1	 Not available. Test Result Dose OECD 301E 96 % - 28 days - Not available. Aquatic half-life Photolysis - - CogPow BCF Poten 0.2 - 1.51 - Iow low 1.51 - Not available.

Disposal methods	:	The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with
		soil, waterways, drains and sewers.

Section 14. Transport information

Section 14. Transport information

	New Zealand Class (5433)	IMDG	ΙΑΤΑ			
UN number	Not regulated.	Not regulated.	Not regulated.			
UN proper shipping name	-	-	-			
Transport hazard class(es)	-	-	-			
Packing group	-	-	-			
Environmental hazards	No.	No.	No.			

Hazchem code

: Not available.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not available. to IMO instruments

Proper shipping name	: Not available.
Ship type	: Not available.
Pollution category	: Not available.

The actual shipping description for this product may vary based several factors including, but not limited to, the volume of material, size of the container, mode of transport and use of exemptions or exceptions found in the applicable regulations. The information provided in Section 14 is one possible shipping description for this product. Consult your shipping specialist or supplier for appropriate assignment information.

Section 15. Regulatory information

HSNO Approval Number	: HSR002662
HSNO Group Standard	: Surface Coatings and Colourants (Flammable) Group Standard 2020
HSNO Classification	: FLAMMABLE LIQUIDS - Category 3 RESPIRATORY SENSITISATION - Category 1 REPRODUCTIVE TOXICITY - Category 2

Section 16. Other information

<u>History</u>

Date of issue	: 8/10/2022
Version	: 7
Prepared by	: Product stewardship and regulatory compliance.

Section 16. Other information

Key to abbreviations	: ACGIH = Association Advancing Occupational and Environmental Health
	ATE = Acute Toxicity Estimate
	BCF = Bioconcentration Factor
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals
	HSWA = Health and Safety at Work Act 2015
	IATA = International Air Transport Association
	IBC = Intermediate Bulk Container
	IMDG = International Maritime Dangerous Goods
	LogPow = logarithm of the octanol/water partition coefficient
	MARPOL = International Convention for the Prevention of Pollution From Ships,
	1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
	TLV = Threshold Limit Value
	WES = Workplace Exposure Standards

Indicates information that has changed from previously issued version.

Notice to reader

This product is intended for industrial use only.

Safety Data Sheet (SDS) content is believed to be accurate as of its issue date, but is subject to change as new information is received by Axalta Coatings Systems, LLC or any of its subsidiaries or affiliates (Axalta). This SDS may incorporate information that has been provided to Axalta by its suppliers. Users should ensure that they are referring to the most current version of the SDS. Users are responsible for following the precautions identified in this SDS. It is the users' responsibility to comply with all laws and regulations applicable to the safe handling, use, and disposal of the product.

Users of Axalta products should read all relevant product information prior to use, and make their own determination as to the suitability of the products for their intended use. Except as otherwise required by applicable law, AXALTA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. The information on this SDS relates only to the specific product identified in Section 1, Identification, and does not relate to its possible use in combination with any other material or in any specific process. If this product is to be used in combination with other products, Axalta encourages you to read and understand the SDS for all products prior to use.

© 2018 Axalta Coating Systems, LLC and all affiliates. All rights reserved. Copies may be made only for those using Axalta Coating Systems products.