

Safety Data Sheet according to the Model Work Health and Safety Regulations Date of issue:14/12/2016 Revision date:03/05/2019

	according to the Model Work Health and Safety Regulations Date of issue:14/12/2016 Revision date:03/05/2019 Supersedes: 15/01/2018 Version: 2.
	oduct identifier and chemical identity
I.1. Product identifier	. Mindours
Product form	: Mixture
Trade name	: GOLD FINE FINISHING FILLER
Product code	: GOLDLWFF, GOLDLWFF/1
I.2. Other means of identification	
No additional information available	
I.3. Recommended use of the ch	emical and restrictions on use
Recommended use	: Fillers
1.4. Supplier's details	
Supplier U-POL AUSTRALIA PTY LIMITED Unit A, 16 - 20 Cassola Place Penrith, NSW 2750 - Australia T 02 4731 2655 - F 02 4731 2611 info@u-pol.co.nz - www.u-pol.com.au	Supplier U-POL NEW ZEALAND LIMITED c/o Lindsay & Associates Unit H, 12 Amera Place, East Tamaki Manukau City 2013 - New Zealand T + 612 4731 2655 - F + 612 4731 2611 technicalsupport@u-pol.com - www.u-pol.com
I.5. Emergency phone number	
Emergency number	: Australia (CHEMTREC): + (61) - 290372994 ; New Zealand (National Poisons Centre): 0800 764 766
SECTION 2: Hazards identifica	tion
2.1. Classification of the hazardo	
Classification according to the model	Work Usekh and Sefety Remulations (WUS Remulations)
-	Work Health and Safety Regulations (WHS Regulations)
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Categ	jory 2A H319
Reproductive toxicity, Category 2	H361
Specific target organ toxicity — Repeated exposure, Category 1	d H372
2.2. Label elements	
Hazard pictograms (GHS AU)	
Signal word (GHS AU)	: Danger
Contains	: styrene (5 - 23 %)
Hazard statements (GHS AU)	 H315 - Causes skin irritation. H319 - Causes serious eye irritation. H361 - Suspected of damaging the unborn child. H372 - Causes damage to organs (hearing organs) through prolonged or repeated exposure (i inhaled).
Precautionary statements (GHS AU)	: P260 - Do not breathe fume, vapours. P264 - Wash hands thoroughly after handling.
	P280 - Wear eye protection, protective clothing, protective gloves. P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation
2.3. Other hazards	P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P501 - Dispose of contents/container to hazardous or special waste collection point, in
2.3. Other hazards	P332+P313 - If skin irritation occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P501 - Dispose of contents/container to hazardous or special waste collection point, in

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
styrene ()	100-42-5	5 - 23	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 STOT RE 1, H372 Asp. Tox. 1, H304
Other substances (not contributing to the classification of this product)		82.26 - 88.38	

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.
4.2. Symptoms caused by exposure	
Symptoms/effects after skin contact	: Irritation.
4.3. Indication of any immediate medical	attention and special treatment needed
Other medical advice or treatment	: Treat symptomatically.
SECTION 5: Firefighting measures	
5.1. Extinguishing media Suitable extinguishing media	: Water spray. Dry powder. Foam.
5.2. Special hazards arising from the sub	
General measures	: Remove ignition sources. No open flames. No smoking.
5.3. Special protective equipment and pr	•
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
SECTION 6: Accidental release meas	sures
6.1. Personal precautions, protective equ	uipment and emergency procedures
General measures	: Remove ignition sources. No open flames. No smoking.
6.1.1. For non-emergency personnel	
Protective equipment	: Safety glasses. Protective clothing. Gloves.
Emergency procedures	: Ventilate spillage area. Do not breathe vapours, fume. Avoid contact with skin and eyes.
6.1.2. For emergency responders	
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
6.2. Environmental precautions	
Avoid release to the environment.	
6.3. Methods and material for containme	nt and cleaning up
For containment	: Contain released product, pump into suitable containers. Collect spillage.
Methods for cleaning up	: Mechanically recover the product. Notify authorities if product enters sewers or public waters.
SECTION 7: Handling and storage, ir	cluding how the chemical may be safely used
7.1. Precautions for safe handling	
Precautions for safe handling	: Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe vapours, fume. Avoid contact with skin and eyes.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
7.2. Conditions for safe storage, includin	ig any incompatibilities
Storage conditions	: Store locked up. Store in a well-ventilated place. Keep cool.

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Storage temperature

Storage area

: <25 °C

: Store in a well-ventilated place.

Special rules on packaging

: Keep only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters - exposure standards

styrene (100-42-5)		
Australia	Local name	Styrene, monomer (Phenylethylene; Vinyl benzene)
Australia	TWA (mg/m³)	213 mg/m ³
Australia	TWA (ppm)	50 ppm
Australia	STEL (mg/m ³)	426 mg/m ³
Australia	STEL (ppm)	100 ppm
New Zealand	Local name	Phenylethylene (Styrene, monomer) (Vinyl benzene)
New Zealand	TWA (mg/m³)	213 mg/m ³
New Zealand	TWA (ppm)	50 ppm
New Zealand	STEL (mg/m ³)	426 mg/m ³
New Zealand	STEL (ppm)	100 ppm
New Zealand	Remark (NZ)	skin (Skin absorption), 6.7A (Confirmed carcinogen)
New Zealand	Regulatory reference	Worplace Exposure Standards and Biological Exposure Indices, 9th Edition

Exposure limit values for the other components

8.2. Monitoring

No additional information available

8.3. Appropriat	e engineering	controls					
Appropriate engineering controls		: Ensure good ventilat	ion of the work station.				
8.4. Personal protective equipment							
Personal protective equipment		: Gloves. Protective cl	othing. Safety glasses.				
Materials for protective clothing		: Impermeable clothing					
Hand protection		: Protective gloves					
Туре	Material		Permeation	Thickness (mm)	Penetratio	'n	Standard
Protective gloves	Nitrile rubb Neoprene i (HNBR), Polyvinylak (PVA), Vito	rubber cohol	6 (> 480 minutes)	0.4			EN 374-3
Eye protection : Safety glasses							
Туре	vpe Use		Characteristics			Standard	
Safety glasses		Dust		clear			
Skin and body protection : Wear suitable prote			tive clothing				

Respiratory protection

: [In case of inadequate ventilation] wear respiratory protection.

Device	Filter type	Condition	Standard
Breathing apparatus, Gas filters	Type A - High-boiling (>65 °C) organic compounds	Vapour protection	EN 140, EN 136, EN 143, EN 145, EN 149

Personal protective equipment symbol(s)



Environmental exposure controls

: Avoid release to the environment.

Safety Data Sheet

according to the Model Work Health and Safety Regulations

according to the Model Work Health and Safety Regula	ations
SECTION 9: Physical and chemica	l properties
Physical state	: Solid
Appearance	
	Paste.
Colour	: No data available
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: Freezing point : Not applicable
Boiling point	: No data available
Flash point	: 34 °C
Auto-ignition temperature	: Not applicable
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative density	: No data available
Density	: Density : ≈ 1.81 (1.79 - 1.83) g/cm³ Relative density : Not applicable
Solubility	: insoluble in water. soluble in most organic solvents.
Log Pow	: No data available
Viscosity, dynamic	: ~
Explosive properties	: No data available
Explosive limits	: Not applicable
Minimum ignition energy	: No data available
VOC content	: 219 g/l
VOC content - Regulatory	: 219 g/l
	·
SECTION 10: Stability and reactivity	
Reactivity	: The product is non-reactive under normal conditions of use, storage and transport. The product is non-reactive under normal conditions of use, storage and transport
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None under recommended storage and handling conditions (see section 7).
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
SECTION 11: Toxicological inform	ation
Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
styrene (100-42-5)	
LD50 oral rat	> 6000 mg/kg bodyweight (Rat, Male, Weight of evidence, Oral)
LD50 oral	 > 6000 mg/kg bodyweight (Hamster, Male, Experimental value, Oral)
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male/female, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	11.8 mg/l air (4 h, Rat, Inconclusive, insufficient data, Inhalation (vapours))
LC50 inhalation rat (Vapours - mg/l/4h)	< 6000 mg/l/4h
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Suspected of damaging the unborn child.
STOT-single exposure	: Not classified
STOT-repeated exposure	 Causes damage to organs (hearing organs) through prolonged or repeated exposure (if inhaled).

inhaled). EN (English)

Safety Data Sheet

Esstautate

according to the Model Work Health and Safety Regulations

Aspiration hazard

: Not classified

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request 12.1

12.1. Ecotoxicity	
Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Not classified
styrene (100-42-5)	
LC50 fish 1	10 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	4.7 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Flow- through system, Fresh water, Experimental value, GLP)
ErC50 (algae)	4.9 mg/l (EPA OTS 797.1050, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
BCF fish 1	35.5 (Carassius auratus, Literature study)
Log Pow	2.96 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Log Koc	2.55 (log Koc, Estimated value)

12.2. Persistence and degradability

styrene (100-42-5)		
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.	
Chemical oxygen demand (COD)	2.8 g O ₂ /g substance	
ThOD	3.07 g O ₂ /g substance	
BOD (% of ThOD)	0.42 (Literature study)	
12.3. Bioaccumulative potential		
styrene (100-42-5)		
BCF fish 1	See section 12.1 on ecotoxicology	

BCF fish 1	See section 12.1 on ecotoxicology	
Log Pow	See section 12.1 on ecotoxicology	
Log Koc	See section 12.1 on ecotoxicology	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	

12.4. Mobility in soil

styrene (100-42-5)	
Surface tension	0.032 N/m (20 °C)
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Ecology - soil	Low potential for adsorption in soil.
12.5. Other adverse effects	
Ozone	: Not classified
Other adverse effects	: No additional information available
GOLD FINE FINISHING FILLER	
Fluorinated greenhouse gases	False
styrene (100-42-5)	
Fluorinated greenhouse gases	False
SECTION 13: Disposal consideration	ns
Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
SECTION 14: Transport information	
14.1. UN number	

Not regulated for transport

14.2.	Proper Shipping Name - Addition		
Not applic	cable		
03/05/2019	9	EN (English)	5/7

Safety Data Sheet

according to the Model Work Health and Safety Regulations

14.3. Transport hazard class(es)					
ADG					
Transport hazard class(es) (ADG) :	Not applicable				
IMDC					
IMDG Transport hazard class(es) (IMDG) :	Not applicable				
Tansport nazaru class(es) (IMDG)					
ΙΑΤΑ					
	Not applicable				
14.4. Packing group					
Packing group (ADG) :	Not applicable				
Packing group (IMDG)	Not applicable				
Packing group (IATA) :	Not applicable				
14.5. Environmental hazards					
	No				
14.6. Special precautions for user					
Specific storage requirement :	No data available				
Shock sensitivity :	No data available				
14.7. Additional information					
Other information :	No supplementary information available				
Transport by road and rail					
Not applicable					
Transport by sea					
Not applicable					
Air transport					
Not applicable					
14.8. Hazchem or Emergency Action Code					
Hazchemcode :	Not applicable				
SECTION 15: Regulatory information					
	lations/legislation specific for the substance or mixture				
No additional information available					
Hazardous Substances and New Organisms Ac	t				
HSNO Approval Number :	HSR002670				
Group standard :	Surface coatings and colourants				
45.2 Internetional environments					
15.2. International agreements No additional information available					
SECTION 16: Any other relevant inform					
Revision date :	03/05/2019				
Classification:					
Skin Irrit. 2	H315				
Eye Irrit. 2A	H319				
Repr. 2	H361				
STOT RE 1	H372				
Full text of H-statements:					
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4				
Asp. Tox. 1	Aspiration hazard, Category 1				
Eye Irrit. 2A Flam. Liq. 3	Serious eye damage/eye irritation, Category 2A Flammable liquids, Category 3				
Repr. 2	Reproductive toxicity, Category 2				
Skin Irrit. 2	Skin corrosion/irritation, Category 2				

Safety Data Sheet

according to the Model Work Health and Safety Regulations

STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.

SDS Australia U-POL

For professional use only. The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.