

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Date of issue:03/01/2017 Revision date:03/05/2019

SECTION 1: Identification: Product identifier and chemical identity

1.1. Product identifier

Product form : Mixture

Trade name : RAPTOR LINER - BLACK

Product code : RLB/1, RLB/5

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Coating

1.4. Supplier's details

Supplier

U-POL AUSTRALIA PTY LIMITED
Unit A, 16 - 20 Cassola Place
Penrith, NSW 2750 - Australia
T 02 4731 2655 - F 02 4731 2611
info@u-pol.co.nz - www.u-pol.com.au

Supplier

U-POL NEW ZEALAND LIMITED c/o Lindsay & Associates
Unit H, 12 Amera Place, East Tamaki
Manukau City 2013 - New Zealand
T + 612 4731 2655 - F + 612 4731 2611
technicalsupport@u-pol.com - www.u-pol.com

Version: 3.2

Supersedes: 08/11/2018

1.5. Emergency phone number

Emergency number : Australia (CHEMTREC): + (61) - 290372994 ; New Zealand (National Poisons Centre): 0800

764 766

SECTION 2: Hazards identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable liquids, Category 2 H225
Serious eye damage/eye irritation, Category 2A H319
Skin sensitisation, Category 1 H317
Specific target organ toxicity — Single exposure, H336

Category 3, Narcosis

2.2. Label elements

Hazard pictograms (GHS AU)





Signal word (GHS AU) : Danger

Contains : acetone (5 - 23 %); n-butyl acetate (< 23 %); reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-

tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (< 5 %); reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (< 5

%)

Hazard statements (GHS AU) : H225 - Highly flammable liquid and vapour.

H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H336 - May cause drowsiness or dizziness.

Precautionary statements (GHS AU) : P210 - Keep away from heat, hot surfaces, open flames, sparks. No smoking.

P261 - Avoid breathing fume, vapours, spray. P264 - Wash hands thoroughly after handling.

P280 - Wear face protection, protective clothing, protective gloves. P337+P313 - If eye irritation persists: Get medical advice/attention.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

03/05/2019 EN (English) 1/9

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Name	CAS-No.	%	Classification according to the model Work Health and Safety Regulations (WHS Regulations)
acetone ()	67-64-1	5 - 23	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
n-butyl acetate ()	123-86-4	< 23	Flam. Liq. 3, H226 STOT SE 3, H336
reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) ()	104810-47-1	< 5	Skin Sens. 1, H317 Aquatic Chronic 2, H411
reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ()	1065336-91-5	< 5	Acute Tox. 5 (Oral), H303 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Other substances (not contributing to the classification of this product)		93.05 - 96.36	

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing. If skin irritation or

rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Symptoms caused by exposure

Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after skin contact : May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Other medical advice or treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry sand. Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

Hazchemcode : 3YE

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Protective clothing. Gloves. Safety glasses.

Emergency procedures : Do not breathe vapours. No open flames, no sparks, and no smoking. Only qualified personnel

equipped with suitable protective equipment may intervene. Avoid breathing vapours, spray,

fume.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain released product. Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. This material and its container must be disposed of

in a safe way, and as per local legislation. Notify authorities if product enters sewers or public

waters.

03/05/2019 EN (English) 2/9

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SECTION 7: Handling and storage, including how the chemical may be safely used

7.1. Precautions for safe handling

Additional hazards when processed

: Keep away from Heat and ignition sources. No smoking.

Precautions for safe handling

Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid breathing vapours, spray, fume. Avoid contact with skin and eves.

Hygiene measures

: Separate working clothes from town clothes. Launder separately. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

Storage temperature : < 25 °C

Storage area : Store in well ventilated area.

Special rules on packaging : Keep only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters - exposure standards

acetone (67-64-1)		
Australia	Local name	Acetone
Australia	TWA (mg/m³)	1185 mg/m³
Australia	TWA (ppm)	500 ppm
Australia	STEL (mg/m³)	2375 mg/m³
Australia	STEL (ppm)	1000 ppm
New Zealand	Local name	Acetone
New Zealand	TWA (mg/m³)	1185 mg/m³
New Zealand	TWA (ppm)	500 ppm
New Zealand	STEL (mg/m³)	2375 mg/m³
New Zealand	STEL (ppm)	1000 ppm
New Zealand	Regulatory reference	Worplace Exposure Standards and Biological Exposure Indices, 9th Edition

n-butyl acetate (123-86-4)		
Australia	Local name	n-Butyl acetate
Australia	TWA (mg/m³)	713 mg/m³
Australia	TWA (ppm)	150 ppm
Australia	STEL (mg/m³)	950 mg/m³
Australia	STEL (ppm)	200 ppm
New Zealand	Local name	n-Butyl acetate
New Zealand	TWA (mg/m³)	713 mg/m³
New Zealand	TWA (ppm)	150 ppm
New Zealand	STEL (mg/m³)	950 mg/m³
New Zealand	STEL (ppm)	200 ppm
New Zealand	Regulatory reference	Worplace Exposure Standards and Biological Exposure Indices, 9th Edition

Exposure limit values for the other components

8.2. Monitoring

No additional information available

03/05/2019 EN (English) 3/9

Safety Data Sheet

according to the Model Work Health and Safety Regulations

8.3. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

8.4. Personal protective equipment

Personal protective equipment : Gloves. Protective clothing. Safety glasses. Gas mask.

Materials for protective clothing : Impermeable clothing
Hand protection : Protective gloves

Eye protection : Chemical goggles or face shield. Safety glasses

Skin and body protection : Wear suitable protective clothing

Respiratory protection : Air-fed respiratory protective equipment should be worn when this product is sprayed. [In case

of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s)









Environmental exposure controls

: Avoid release to the environment.

SECTION 9: Physical and chemical properties

Physical state : Liquid

Appearance

Viscous. Liquid.

Colour : No data available

Odour : No data available

Odour threshold : No data available

pH : No data available

Relative evaporation rate (butylacetate=1) : No data available

Melting point / Freezing point : Melting point : Not applicable

Boiling point : > 35 °C Flash point : < 0 °C

Auto-ignition temperature : No data available Flammability (solid, gas) : No data available Vapour pressure : No data available Relative density : No data available

Density : Density : $\approx 1.125 (1.1 - 1.14) \text{ g/cm}^3$

Solubility : insoluble in water. soluble in most organic solvents.

Log Pow: No data availableViscosity, kinematic: \approx 7777.778 mm²/s

Viscosity, dynamic : ≈ 8750 (7500 - 10000) cP (20°C)

Explosive properties : No data available
Explosive limits : No data available
Minimum ignition energy : No data available
VOC content - Regulatory : No data available

SECTION 10: Stability and reactivity

Reactivity : Highly flammable liquid and vapour. Highly flammable liquid and vapour.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No dangerous reactions known under normal conditions of use.

Conditions to avoid : Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be

produced.

: Not classified

SECTION 11: Toxicological information

Acute toxicity (oral)

03/05/2019 EN (English) 4/9

Safety Data Sheet

according to the Model Work Health and Safety Regulations

Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Equivalent or similar to OECD 401, Rat, Female, Experimental value, Oral)
LD50 dermal rabbit	20000 mg/kg (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	76 mg/l (Other, 4 h, Rat, Female, Experimental value, Inhalation (vapours))
n-butyl acetate (123-86-4)	
LD50 oral rat	10760 - 12789 mg/kg bodyweight (Equivalent or similar to OECD 423, Rat, Male/female, Experimental value, Oral)
LD50 dermal rabbit	14112 mg/kg bodyweight (Equivalent or similar to OECD 402, Rabbit, Male/female, Experimental value, Dermal)
LC50 inhalation rat (ppm)	390 ppm/4h
LC50 inhalation rat (Vapours - mg/l/4h)	> 21 mg/l/4h (4 h, OECD Test Guideline 403, rat, vapours)
reaction mass of a-3-/3-/2H-henzotriazol-2-v	N M I . I A I I I I N . I I I I I I I I I I I I I I
	l)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H- nyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4- ne) (104810-47-1)
benzotriazol-2-yl)-5-tert-butyl-4-hydroxypher	nyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-
benzotriazol-2-yl)-5-tert-butyl-4-hydroxypher hydroxyphenyl)propionyloxypoly(oxyethyler	nyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4- ne) (104810-47-1) > 5000 mg/kg (OECD Guideline No. 401 (equivalent to Annex V), limit test, rat,
benzotriazol-2-yl)-5-tert-butyl-4-hydroxypher hydroxyphenyl)propionyloxypoly(oxyethyler LD50 oral rat	hyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4- ne) (104810-47-1) > 5000 mg/kg (OECD Guideline No. 401 (equivalent to Annex V), limit test, rat, male/female) > 2000 mg/kg (OECD Guideline No. 402 (equivalent to Annex V), limit test, rat,
benzotriazol-2-yl)-5-tert-butyl-4-hydroxypher hydroxyphenyl)propionyloxypoly(oxyethyler LD50 oral rat LD50 dermal rat LC50 inhalation rat (mg/l)	nyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4- ne) (104810-47-1) > 5000 mg/kg (OECD Guideline No. 401 (equivalent to Annex V), limit test, rat, male/female) > 2000 mg/kg (OECD Guideline No. 402 (equivalent to Annex V), limit test, rat, male/female)
benzotriazol-2-yl)-5-tert-butyl-4-hydroxypher hydroxyphenyl)propionyloxypoly(oxyethyler LD50 oral rat LD50 dermal rat LC50 inhalation rat (mg/l)	hyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4- he) (104810-47-1) > 5000 mg/kg (OECD Guideline No. 401 (equivalent to Annex V), limit test, rat, male/female) > 2000 mg/kg (OECD Guideline No. 402 (equivalent to Annex V), limit test, rat, male/female) 5800 mg/l (OECD Guideline 403, 14d, rat)

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

							_
DADTOD LINED - BLACK		 		 	 	_	П

Viscosity, kinematic ≈ 7777.778 mm²/s

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Acute aquatic toxicity : Not classified Chronic aquatic toxicity : Not classified

acetone (67-64-1)	
LC50 fish 1	5540 mg/l (EU Method C.1, 96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Nominal concentration)
BCF fish 1	0.69 (Pisces)
BCF other aquatic organisms 1	3 (BCFWIN, Calculated value)
Log Pow	-0.24 (Test data)
n-butyl acetate (123-86-4)	
LC50 fish 1	18 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
LC50 fish 2	62 mg/l (Leuciscus idus, static system)
EC50 Daphnia 1	44 mg/l (48 h, Daphnia sp., Static system, Fresh water, Experimental value)
NOEC chronic crustacea	23 mg/l

03/05/2019 EN (English) 5/9

Safety Data Sheet

according to the Model Work Health and Safety Regulations

n-butyl acetate (123-86-4)	
BCF fish 1	15.3 (Calculated value)
Log Pow	2.3 (Test data, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 25 °C)
Log Koc	1.268 - 1.844 (log Koc, SRC PCKOCWIN v2.0, QSAR)
	iazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2H- roxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4- xyethylene) (104810-47-1)
LC50 fish 1	2.8 mg/l (96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	4 mg/l (48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 (algae)	> 100 mg/l (72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)
BCF fish 1	2658 - 3430 (502 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Experimental value)
	value)

12.2. Persistence and degradability

acetone (67-64-1)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance
Chemical oxygen demand (COD)	1.92 g O₂/g substance
ThOD	2.2 g O ₂ /g substance
BOD (% of ThOD)	0.872 (20 day(s), Literature study)
n-butyl acetate (123-86-4)	
Persistence and degradability	Readily biodegradable in water.
ThOD	2.21 g O ₂ /g substance
BOD (% of ThOD)	0.46

12.3. Bioaccumulative potential

acetone (67-64-1)	
BCF fish 1	See section 12.1 on ecotoxicology
BCF other aquatic organisms 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Bioaccumulative potential	Not bioaccumulative.
n-butyl acetate (123-86-4)	
BCF fish 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (104810-47-1)

hydroxyphenyl)propionyloxypoly(oxyethyle	ne) (104810-47-1)
BCF fish 1	See section 12.1 on ecotoxicology
Log Pow	See section 12.1 on ecotoxicology

12.4. Mobility in soil

acetone (67-64-1)	
Surface tension	0.0237 N/m
Log Pow	See section 12.1 on ecotoxicology
Ecology - soil	No (test)data on mobility of the substance available.
n-butyl acetate (123-86-4)	
Surface tension	0.0163 N/m (20 °C)
Log Pow	See section 12.1 on ecotoxicology
Log Koc	See section 12.1 on ecotoxicology
Ecology - soil	Low potential for adsorption in soil.

reaction mass of α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -hydroxypoly(oxyethylene) and α -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl- ω -3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene) (104810-47-1)

Log Pow See section 12.1 on ecotoxicology

03/05/2019 EN (English) 6/9

Safety Data Sheet

according to the Model Work Health and Safety Regulations

12.5. Other adverse effects

Ozone : Not classified

: No additional information available Other adverse effects

RAPTOR LINER - BLACK

False Fluorinated greenhouse gases

acetone (67-64-1)

Fluorinated greenhouse gases False

n-butyl acetate (123-86-4)

False Fluorinated greenhouse gases

reaction mass of α-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-hydroxypoly(oxyethylene) and α-3-(3-(2Hbenzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-ω-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4hydroxyphenyl)propionyloxypoly(oxyethylene) (104810-47-1)

Fluorinated greenhouse gases False

reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)

Fluorinated greenhouse gases False

SECTION 13: Disposal considerations

Regional legislation (waste) : Disposal must be done according to official regulations.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

UN number 14.1

UN-No. (ADG) 1263 UN-No. (IMDG) 1263 UN-No. (IATA) 1263

Proper Shipping Name - Addition

Proper Shipping Name (ADG) **PAINT** Proper Shipping Name (IMDG) **PAINT** Proper Shipping Name (IATA) Paint

14.3. Transport hazard class(es)

ADG

Transport hazard class(es) (ADG) 3 3

Danger labels (ADG)



IMDG

Transport hazard class(es) (IMDG) Danger labels (IMDG) 3



IATA

Transport hazard class(es) (IATA) 3 Hazard labels (IATA) 3



03/05/2019 EN (English) 7/9

Safety Data Sheet

according to the Model Work Health and Safety Regulations

14.4. Packing group

Packing group (ADG) : II
Packing group (IMDG) : II
Packing group (IATA) : II

14.5. Environmental hazards

Marine pollutant : No

14.6. Special precautions for user

Specific storage requirement : No data available
Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available

Transport by road and rail

UN-No. (ADG) : 1263
Special provision (ADG) : 163
Limited quantities (ADG) : 5

Packing instructions (ADG) : P001, IBC02 Special packing provisions (ADG) : PP1

Portable tank and bulk container instructions

(ADG)

Portable tank and bulk container special

provisions (ADG)

: TP1, TP8, TP28

: T4

Transport by sea

UN-No. (IMDG) : 1263 Special provisions (IMDG) : 163, 367 Limited quantities (IMDG) : 5 L Excepted quantities (IMDG) : E2 : P001 Packing instructions (IMDG) Special packing provisions (IMDG) : PP1 IBC packing instructions (IMDG) : IBC02 Tank instructions (IMDG) : T4

Tank special provisions (IMDG) : TP1, TP8, TP28

EmS-No. (Fire) : F-E - FIRE SCHEDULE Echo - NON-WATER-REACTIVE FLAMMABLE LIQUIDS
EmS-No. (Spillage) : S-E - SPILLAGE SCHEDULE Echo - FLAMMABLE LIQUIDS, FLOATING ON WATER

Stowage category (IMDG) : B

Properties and observations (IMDG) : Miscibility with water depends upon the composition.

Air transport

: 1263 UN-No. (IATA) PCA Excepted quantities (IATA) : E2 PCA Limited quantities (IATA) : Y341 PCA limited quantity max net quantity (IATA) : 1L PCA packing instructions (IATA) : 353 PCA max net quantity (IATA) : 5L CAO packing instructions (IATA) : 364 CAO max net quantity (IATA) : 60L

Special provisions (IATA) : A3, A72, A192

ERG code (IATA) : 3L

14.8. Hazchem or Emergency Action Code

Hazchemcode : 3YE

03/05/2019 EN (English) 8/9

Safety Data Sheet

according to the Model Work Health and Safety Regulations

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No additional information available

Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR002662

Group standard : Surface coatings and colourants

ethylbenzene (100-41-4)

Hazardous Substances and New Organisms Act

HSNO Approval Number : HSR001151

15.2. International agreements

No additional information available

SECTION 16: Any other relevant information

Revision date : 03/05/2019

Classification:

Flam. Liq. 2	H225
Eye Irrit. 2A	H319
Skin Sens. 1	H317
STOT SE 3	H336

Full text of H-statements:

Acute Tox. 5 (Oral)	Acute toxicity (oral), Category 5
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H303	May be harmful if swallowed
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

SDS Australia U-POL

For professional use only.

The information contained within this Safety Data Sheet (SDS) is believed to be correct as of the date issued however it is subject to change from time to time. It does not purport to be all inclusive or exhaustive and shall only be used as a guide. U-POL makes no warranties, expressed or implied, including but not limited to, any implied warranty of fitness for a given purpose or usage. It is the Buyers responsibility to ensure the suitability of the products for their own use and to check the information is up to date. U-POL cannot be held responsible for the suitability of use for any of its products, considering the wide range of factors such as application, substrates and handling methods. Since these conditions of use are outside of our control, the company shall not be held liable for any damage resulting from handling or from contact with the product detailed. Moreover, addition of reducers, hardeners or other additives over and above U-POL's recommendations for use, may substantially alter the composition and hazards of the product. U-POL data sheets are available via the U-POL website at WWW.U-POL.COM.

03/05/2019 EN (English) 9/9